


# JCE

JOE CASALI ENGINEERING, INC.  
CIVIL · SITE DEVELOPMENT · TRANSPORTATION  
DRAINAGE · WETLANDS · ISDS · TRAFFIC · FLOODPLAIN  
300 POST ROAD, WARWICK, RI 02888  
(401) 944-1300 (401) 944-1313 FAX WWW.JOECASALI.COM



## Drainage Memorandum

---


<b>To:</b> Rick Nardella, Malibu Investments LLC	<b>Date:</b> October 27, 2022; Revised October 2023
<b>CC:</b> Steve Medeiros, Malibu Investments LLC	<b>Project:</b> Post Road Retail & Contractor Units
<b>From:</b> Joseph A. Casali, PE, MBA	<b>Re:</b> Phase II Modifications

---

### Introduction / Purpose

Joe Casali Engineering, Inc., (JCE) has prepared this drainage memorandum summarizing changes to the site layout, grading and drainage design, and utility design for the Proposed Retail & Contractor Units, located at 2826 Post Road in Warwick, Rhode Island (Tax Assessor's Plat Map (AP) 267, Lot 217).

This project was originally designed to be constructed in three phases. Phase I of the construction was completed in Summer of 2022. Phases II and III are now proposed to be combined and incorporate some changes to the building size and layout, which caused modifications to the drainage design and the utility design for the project. Phase I included the project consisted of six (6) self-storage buildings with a total of 152,900 sq. ft. of building area and a 1,600 sq. ft. office building along the southern portion of the project area. Phase I construction was completed in early Summer 2022. Phase II previously included the construction of a 19,500 sq. ft. two-story mixed-use building along with four (4) additional storage buildings ranging in size from 8,000 sq. ft. to 10,800 sq. ft. The Applicant proposes modifications to Phase II which is now proposed to include a 9,500 sq. ft. mixed-use building along with two (2) 24,000 sq. ft. contractor rental unit buildings and one (1) 6,900 sq. ft. mini-storage building.



**Figure 1 – General Locus Map (Existing Conditions – Phase I Complete)**

NOT TO SCALE

This project was previously approved by the Rhode Island Department of Environmental Management (RIDEM) for a RIPDES permit on June 8, 2018 (RIPDES No. RIR101718), WQC No. 18-037, UIC No. 001834). A wetlands permit was not required. In addition, this project was previously approved by the Rhode Island Department of Transportation for a Physical Alteration Permit (PAPA No. 18-0314). The Applicant has received approved permit modifications to both the RIDEM and RIDOT permits as of January 2023.

## History

This project was originally designed and permitted by Cherenzia & Associates, Ltd. (Cherenzia). As noted above, the project has received the requisite permit approvals from RIDEM and RIDOT. Cherenzia has provided JCE with digital and hard copy files including the following:

- *Stormwater Management Report, Malibu Investments, LLC, Retail and Mini Storage Facility, 2826 Post Road, Warwick, Rhode Island*, prepared by Cherenzia & Associates Ltd., stamped by Sergio F. Cherenzia, PE, dated May 2018.
- *Drainage Memorandum*, prepared by Cherenzia & Associates Ltd., dated September 2018.
- *Site Plans titled Retail & Mini Storage Facility, 2826 Post Road, AP 267, Lot 217, 218 & 219, Warwick, Rhode Island, Issued for Permitting*, prepared by Cherenzia & Associates Ltd., stamped by Sergio F. Cherenzia, PE, dated September 20, 2018.

These documents were used as a basis for the design modifications and incorporate the original survey, hydrologic modeling, etc.

## Proposed Phase II Development Modifications

Phase I included the project consisted of six (6) storage buildings with a total of 152,900 sq. ft. of building area and a 1,600 sq. ft. office building along the southern portion of the project area. Phase I construction was completed in early Summer 2022. Phase II previously included the construction of a 19,500 sq. ft. two-story mixed-use building along with four (4) additional storage buildings ranging in size from 8,000 sq. ft. to 10,800 sq. ft. The Applicant proposes modifications to Phase II which is now proposed to include a 9,500 sq. ft. mixed-use building along with two (2) 24,000 sq. ft. contractor rental unit buildings and one (1) 6,900 sq. ft. mini-storage building.

The project was previously approved by the Rhode Island Department of Environmental Management (RIDEM) on June 18, 2018 via RIPDES Permit No. RIR101718, WQC No. 18-037 and UIC No. 001834 and by the Rhode Island Department of Transportation (RIDOT) under Physical Alteration Permit No. 18-0314. The scope of this report and application is to modify these two permits based on the modifications proposed to Phase II and to file for and obtain Preliminary Plan and Final Plan approval from the City of Warwick for Phase II.

As noted above, the changes between the previously approved overall project (including Phase II) and the currently proposed Phase II scope includes the following significant changes:

- Reduction in the overall size and scope of the proposed mixed-use building from 19,500 sq. ft. (previously approved) to 9,500 sq. ft. (currently proposed).
- Increase in the overall size and scope of the proposed storage buildings from 37,100 sq. ft. (previously approved) to 54,900 sq. ft. buildings for contractor rental units and mini-storage (currently proposed). The three (3) proposed buildings will contain a total of 46 contractor units and 23 mini-storage units.
- Modifications to the site design and layout to accommodate the building footprint modifications described above; including modifications to curb cut locations along Post Road, and modifications to sewer and water utilities.

- Modifications to the stormwater management system design and layout.

Access to the development will be provided utilizing one of two new curb cuts along Post Road. With respect to parking, the City of Warwick Zoning Ordinance does not have a parking requirement for contractor rental units; instead noting that the Building Official is responsible for determining parking requirements. Per the Building Official, one (1) parking space is required per 500 sq. ft. of building area. The total square footage of storage space is 172,685 sq. ft. globally (Phases I & II) necessitating 338 spaces. The storage facility office requires 1 space per 250 sq. ft.; therefore 6 additional spaces are required.

With respect to parking for the proposed mixed-use building; the City of Warwick Zoning Ordinance has varied parking requirements for the anticipated uses including 1 space per 200 sq. ft. for medical uses; 1 space per 250 sq. ft. of business uses; 1 space per 200 sq. ft. of retail uses; and 1 space per 100 sq. ft. of restaurant uses. Tenants are not yet known, so the parking requirements presented below are theoretical varied mixed-uses in the proposed building:

- 1,850 sq. ft. medical use (1 space / 200 sq. ft.) = 9 spaces required
- 2,750 sq. ft. business use (1 space / 250 sq. ft.) = 11 spaces required
- 2,500 sq. ft. other retail use (1 space / 200 sq. ft.) = 13 spaces required
- 2,400 sq. ft. restaurant use (1 space / 100 sq. ft.) = 24 spaces required

As shown above, the total parking spaces required for the proposed mixed-use building is approximately 57 spaces. Sitewide, a total of 401 spaces is required and a total of 199 spaces are proposed. Requisite accessible parking spaces are provided in all areas in accordance with the Americans with Disabilities Act (ADA). The project received approval from the Zoning Board of Review for less than the required parking at the September 2023 meeting. Additional variances for landscaping were also approved.

All exterior lighting will be dark sky complaint, downward facing lighting designed to minimize negative impacts on neighboring properties. Glare from outdoor lights, signs, and from the movement of vehicles on site will be shielded from the view of adjacent properties.

## **Phase II Utility Modifications**

Water: The proposed Phase II scope includes providing domestic water to all buildings via a new domestic water service from Post Road. The new service will be routed into a utility room at the north corner of the mixed-use building, within 100-ft of the property line, therefore not necessitating an above-ground heated enclosure. Review and approval of the Phase II water modifications will be required by the Warwick Water District.

Sewer: The proposed Phase II scope includes sewer services from the mixed-use building and the center contractor unit building, Building #4. The eastern and southern-most Phase II building will not have restrooms and therefore do not require sewer services. Sewer service from the mixed-use building will be routed via gravity to an existing sewer manhole on site. Sewer service from Building #4 will be routed to an Environmental One sewer pump station chamber; the outlet from the pump station will be tied into the existing stub routed to the sewer main in Post Road. No new sewer service taps are proposed as part of the Phase II development. Review and approval of the Phase II sewer modifications will be required by the Warwick Sewer Authority.

Gas: The proposed Phase II scope includes a new gas service from the main within Post Road to the proposed mixed-use building. Coordination with RI Energy will be required.

Electric/Communications: The proposed Phase II scope includes coordination with RI Energy and telecommunications providers to provide primary electric service and communications services to the proposed buildings. Services are anticipated to be routed from the existing transformer pad located to the east of the office building to the various buildings.

Stormwater: The design of the original project included an infiltration basin at the southwestern portion of the property and four (4) underground infiltration chamber systems dispersed throughout the development. One (1) of the underground infiltration chamber systems and the infiltration basin were constructed as part of Phase I. The remaining systems have been modified to accommodate the proposed changes to the development design. Under the new design, six (6) new underground infiltration chamber systems are proposed for water quality and attenuation of peak stormwater runoff rates and volumes. Review of the proposed stormwater management system design will be required by the Rhode Island Department of Environmental Management. Stormwater management design is further discussed below.

### **Stormwater Design Modifications**

The proposed development is subject to the requirements of the Rhode Island Stormwater Design and Installation Standards Manual (RISDISM), implemented in December 2010, amended March 2015, by both the Rhode Island Department of Environmental Management (RIDEM) and the Rhode Island Coastal Resources Management Council (CRMC). As discussed previously, the original design included an infiltration basin and four (4) underground infiltration chamber systems dispersed throughout the development. One (1) of the underground infiltration chamber systems and the infiltration basin were constructed as part of Phase I.

The remaining systems have been modified to accommodate the proposed changes to the development design. Under the new design, six (6) new underground infiltration chamber systems are proposed. In general, most stormwater runoff from the site sheet flows in a southeasterly direction where it enters swales and ultimately discharges to an off-site wetland, Design Point 1 (DP-1). Stormwater runoff from a small portion of the property along Post Road overflows to Post Road and ultimately discharges into the existing closed drainage system within Post Road, Design Point 2 (DP-2).

The site's proposed stormwater management system has been designed to generally mimic existing conditions. The stormwater management design adheres to all State (RIDEM) and local (City of Warwick) standards. The proposed Stormwater Management Plan improves the overall quality of stormwater leaving the site by using Best Management Practices (BMPs). These water quality BMPs incorporate low-impact development techniques, including six (6) underground infiltration systems. Pre-treatment has been included with the BMP designs to help reduce overall maintenance and to extend the design life of the BMPs. Pre-treatment practices include an isolator row within each individual Underground Infiltration Chamber (UIC) system. The isolator rows have been designed to meet the minimum pre-treatment requirements for the initial 1.2-inch (water quality) design storm event.

The pre-existing conditions, as described in Cherenzia's original Stormwater Report, have not been modified and are mimic what was presented in the original report. The proposed conditions take into account work completed as part of the Phase I construction as well as the proposed modifications proposed to Phase II. As shown throughout the remainder of the report, the Phase II modifications improve upon the conditions that were previously approved by the various authorities having jurisdiction. Note only Standards where changes have occurred are presented below.

#### **Standard 2: Groundwater Recharge**

Stormwater must be recharged within the same sub-watershed to maintain base flow at pre-development recharge levels to the maximum extent practicable.

##### *Standard Met*

Groundwater recharge is being provided within six (6) separate subwatersheds through six (6) new underground infiltration chamber (UIC) systems for this portion of the project. The following calculations were completed in accordance with Section 3.3.2 of the RISDISM using the following formula:

$$\text{Rev}=(1'')(F)(I)/12$$

Based on the results from the soil evaluations, a recharge factor of 0.60 was used for Hydrologic Soil Group A.

**Table 1: Groundwater Recharge Requirements**

Subwatershed	1A & 1B	2A & 2B	3A & 3B	4A & 4B	5A & 5B	6A & 6B
Treatment System	UIC #1	UIC #2	UIC #3	UIC #4	UIC #5	UIC #6
Impervious Area (SF)	32,528	16,691	15,324	23,191	21,940	43,398
Recharge factor (in)	0.60	0.60	0.60	0.60	0.60	0.60
Required Recharge Volume (CF)	1,626	835	766	1,160	1,097	2,170
Provided Recharge Volume (CF)	7,089	4,372	3,814	4,931	4,936	10,769
Recharge Requirement Met?	Yes	Yes	Yes	Yes	Yes	Yes

- Notes: 1. Refer to Proposed Watershed Map located in Appendix D for BMP locations.  
 2. Based on Routing Analysis of WQ<sub>v</sub>, the entire volume is infiltrated.  
 3. Recharge Volumes are calculated as the Static Storage Volume.

### Standard 3: Water Quality

The stormwater runoff from the site must be treated prior to discharge.

#### Standard Met

Because the site is not considered a redevelopment, 100% treatment for water quality volume and recharge must be provided. Treatment for water quality volume will be met using six (6) new underground infiltration chamber systems (UICs). The underground infiltration chamber systems have been sized to capture and treat the required water quality volume prior to discharge. Pre-treatment will be provided via the proposed isolator rows with the UICs. Water Quality Volume (WQ<sub>v</sub>) is met through isolator rows for the UICs. Calculations were completed in accordance with Section 3.3.3 of the RISDISM using the following formula:

$$WQ_v = (1") (I) / 12 \text{ in/ft}$$

Tables 2 and 3 below provide sizing calculations for the Water Quality Volume (WQ<sub>v</sub>) of the pretreatment area and the treatment area, respectively.

**Table 2: Water Quality - Pretreatment Area Requirements**

Subwatershed	1B	2B	3B	4B	5B	6B
Treatment System	Isolator Row	Isolator Row	Isolator Row	Isolator Row	Isolator Row	Isolator Row
Impervious Area (SF)	23,528	10,191	8,824	10,191	8,940	23,498
Water Quality Factor	1.00	1.00	1.00	1.00	1.00	1.00
Required WQ <sub>v</sub> (CF)	1,961	849	735	849	745	1,958
Req. Static Volume (CF) for Pretreatment (25% of WQ <sub>v</sub> )	490	212	184	212	186	490
Prov. Static Storage Volume for Infiltration System (CF)	728	374	374	374	374	1,436
Treatment Requirement Met?	Yes	Yes	Yes	Yes	Yes	Yes

- Notes: 1. Rooftop areas are excluded from pre-treatment requirements.  
 2. Isolator Row added to Infiltration Chambers for Pretreatment.  
 3. Static Storage Volume = Volume of Chambers + Volume of Voids in Stone

**Table 3: Water Quality – Treatment Area Requirements**

Subwatershed	1A	2A	3A	4A	5A	6A
Treatment Type	UIC #1	UIC #2	UIC #3	UIC #4	UIC #5	UIC #6
Impervious Area (SF)	32,528	16,691	15,324	23,191	21,940	43,398
Water Quality Factor	1.00	1.00	1.00	1.00	1.00	1.00
Req. Water Quality Volume (CF)	2,711	1,391	1,277	1,933	1,828	3,617
Required Static Volume for Treatment (CF)(100% for UIC)	2,711	1,391	1,277	1,933	1,828	3,617
Provided Static Storage Volume for Treatment (CF)	7,089	4,372	3,814	4,931	4,936	10,769
Treatment Requirement Met?	Yes	Yes	Yes	Yes	Yes	Yes

Notes: 1. Refer to Proposed Watershed Map located in Appendix G for watershed locations.  
 2. Based on Routing Analysis, the entire volume is contained up to and including the 1-yr storm.

As shown in Tables 1 through 3 above, the site’s proposed stormwater management system greatly exceeds the requirements for groundwater recharge volume, water quality pre-treatment volume and water quality treatment volume. This is in accordance with all RISDISM and City of Warwick standards, and ultimately helps reduce stormwater flows into the State drainage system and the adjacent wetland.

**Drainage Analysis**

The comparative pre- versus post-development hydrologic analysis was performed using the Soil Conservation Service, Technical Release 20 and 55 (TR-20 and TR-55) methodology. The 1-, 2-, 10-, 25-, and 100-year storm events were modeled for a 24-hour, Type III storm utilizing HydroCAD version 10.00. HydroCAD modeling reports for the proposed conditions are attached.

The original design included an infiltration basin and four (4) underground infiltration chamber systems dispersed throughout the development. One (1) of the underground infiltration chamber systems and the infiltration basin were constructed as part of Phase I. The remaining systems have been modified to accommodate the proposed changes to the development design. Under the new design, six (6) new underground infiltration chamber systems are proposed. In general, all stormwater runoff from the majority of the site sheet flows in a southeasterly direction where it enters swales and ultimately discharges to an off-site wetland, Design Point 1 (DP-1). Stormwater runoff from a small portion of the property along Post Road overflows to Post Road and ultimately discharges into the existing closed drainage system within Post Road, Design Point 2 (DP-2). As shown in the following sections, the stormwater runoff rates, and volumes have been reduced for all design storm events for both design points. In general, existing conditions and proposed conditions associated with Phase I have been mimicked as originally designed by Cherenzia & Associates, Ltd.

**Proposed Watershed Modifications**

In general, the proposed drainage patterns mimic existing conditions, discharging to the same design points as under existing conditions. Water quality is achieved by means of infiltration practices. Stormwater runoff from the project area is conveyed through proposed drainage infrastructure in addition to the infiltration basin and UIC installed as part of Phase I, and discharges to the southern and western property lines (DP-1). The drainage systems will treat stormwater runoff pollutants and reduce peak stormwater runoff rates and volumes. These conditions are shown in detail on the Proposed Conditions Watershed Map included in Appendix G.

Design Point 1 – Southern and Western Property Lines

Subwatershed 1A: This subwatershed consists of 9,500 sq. ft. of rooftop area associated with the proposed mixed-use building. This subwatershed has a minimum TC of 6.0 minutes and a composite CN Runoff Number of 98. The roof drains associated with this building will discharge via underground piping to proposed UIC #1. Ultimately, excess stormwater runoff is conveyed towards the off-site wetlands to the south, Design Point 1.

Subwatershed 1B: Consists of 30,994 sq. ft. of a paved parking area associated with the proposed mixed-use building and landscaped areas associated with the project site. This subwatershed has a minimum TC of 6.0 minutes and a composite CN Runoff Number of 84. Stormwater runoff associated with the new parking lot is captured within catch basins and conveyed to UIC #1. Ultimately, excess stormwater runoff is conveyed towards the off-site wetlands to the south, Design Point 1.

Subwatershed 1D: This subwatershed includes Buildings #3 and #5 though #12 and surrounding pavement completed under Phase I. This area consists of 286,475 sq. ft. of mostly impervious area. Runoff from this area is collected by a network of catch basins into a closed drainage system and into a series of underground infiltration chamber systems. This subwatershed has a minimum TC of 6.0 minutes and a composite CN Runoff Number of 88. Ultimately, excess stormwater runoff is conveyed towards the off-site wetlands to the south, Design Point 1.

Subwatershed 1E: This subwatershed includes a portion of Building #12 and surrounding pavement completed under Phase I. This area consists of 76,715 sq. ft. of mostly impervious area. Runoff from this area sheet flows and via roof drains to Surface Infiltration Basin (P-1E), constructed during Phase I. This subwatershed has a minimum TC of 6.0 minutes and a composite CN Runoff Number of 80. Ultimately, excess stormwater runoff is conveyed towards the off-site wetlands to the south, Design Point 1.

Subwatershed 1F: This subwatershed includes the un-detained areas along the southern project limits of Phase I. This area consists of 20,166 sq. ft. of entirely pervious area. Runoff from this area flows directly to Design Point 1, un-detained. This subwatershed has a minimum TC of 6.0 minutes and a composite CN Runoff Number of 42.

Subwatershed 2A: This subwatershed consists of 6,500 sq. ft. of rooftop area associated with a portion of the proposed Building #4. This subwatershed has a minimum TC of 6.0 minutes and a composite CN Runoff Number of 98. The roof drains associated with this building will discharge via underground piping to proposed UIC #2. Ultimately, excess stormwater runoff is conveyed towards the off-site wetlands to the south, Design Point 1.

Subwatershed 2B: Consists of 11,917 sq. ft. of a paved parking area to the north and northwest of proposed Building #4 and landscaped areas associated with the project site. This subwatershed has a minimum TC of 6.0 minutes and a composite CN Runoff Number of 89. Stormwater runoff associated with the new parking lot is captured within catch basins and conveyed to UIC #2. Ultimately, excess stormwater runoff is conveyed towards the off-site wetlands to the south, Design Point 1.

Subwatershed 3A: This subwatershed consists of 6,500 sq. ft. of rooftop area associated with a portion of the proposed Building #4. This subwatershed has a minimum TC of 6.0 minutes and a composite CN Runoff Number of 98. The roof drains associated with this building will discharge via underground piping to proposed UIC #3. Ultimately, excess stormwater runoff is conveyed towards the off-site wetlands to the south, Design Point 1.

Subwatershed 3B: Consists of 8,824 sq. ft. of a paved parking area to the west of proposed Building #4. This subwatershed has a minimum TC of 6.0 minutes and a composite CN Runoff Number of 98.

Stormwater runoff associated with the new parking lot is captured within catch basins and conveyed to UIC #3. Ultimately, excess stormwater runoff is conveyed towards the off-site wetlands to the south, Design Point 1.

Subwatershed 4A: This subwatershed consists of 13,000 sq. ft. of rooftop area associated with a portion of the proposed Buildings #4 and #5. This subwatershed has a minimum TC of 6.0 minutes and a composite CN Runoff Number of 98. The roof drains associated with these buildings will discharge via underground piping to proposed UIC #4. Ultimately, excess stormwater runoff is conveyed towards the off-site wetlands to the south, Design Point 1.

Subwatershed 4B: Consists of 13,602 sq. ft. of a paved parking area to in-between proposed Buildings #4 and #5. This subwatershed has a minimum TC of 6.0 minutes and a composite CN Runoff Number of 83. Stormwater runoff associated with the new parking lot is captured within catch basins and conveyed to UIC #4. Ultimately, excess stormwater runoff is conveyed towards the off-site wetlands to the south, Design Point 1.

Subwatershed 5A: This subwatershed consists of 13,000 sq. ft. of rooftop area associated with a portion of the proposed Buildings #4 and #5. This subwatershed has a minimum TC of 6.0 minutes and a composite CN Runoff Number of 98. The roof drains associated with these buildings will discharge via underground piping to proposed UIC #5. Ultimately, excess stormwater runoff is conveyed towards the off-site wetlands to the south, Design Point 1.

Subwatershed 5B: Consists of 8,940 sq. ft. of a paved parking area to in-between proposed Buildings #4 and #5. This subwatershed has a minimum TC of 6.0 minutes and a composite CN Runoff Number of 98. Stormwater runoff associated with the new parking lot is captured within catch basins and conveyed to UIC #5. Ultimately, excess stormwater runoff is conveyed towards the off-site wetlands to the south, Design Point 1.

Subwatershed 6A: This subwatershed consists of 19,900 sq. ft. of rooftop area associated with a portion of the proposed Buildings #5 and all of #6. This subwatershed has a minimum TC of 6.0 minutes and a composite CN Runoff Number of 98. The roof drains associated with these buildings will discharge via underground piping to proposed UIC #6. Ultimately, excess stormwater runoff is conveyed towards the off-site wetlands to the south, Design Point 1.

Subwatershed 6B: Consists of 29,236 sq. ft. of a paved parking area behind proposed Building #5 and some landscaped areas. This subwatershed has a minimum TC of 6.0 minutes and a composite CN Runoff Number of 86. Stormwater runoff associated with the new parking lot is captured within catch basins and conveyed to UIC #6. Ultimately, excess stormwater runoff is conveyed towards the off-site wetlands to the south, Design Point 1.

#### Design Point 2 – Post Road

Subwatershed 2: Consists of 4,854 sq. ft. of the western portion of the project site along Post Road. This watershed area consists mostly of impervious area. Runoff from this area sheet flows to Design Point 2, Post Road, which ultimately discharges to the existing closed drainage system within Post Road. This watershed area has a minimum TC of 6.0 minutes and a composite CN Runoff Number of 82.

## **Results**

A runoff analysis of the pre- and post-construction conditions was completed using the TR-20 methodology and is summarized in Table 4 below. Supporting calculations for the pre-construction condition are included in Cherenzia's original report; supporting calculations for the post-construction conditions are attached.



Table 4: Watershed Characteristics

	Area (SF)	CN	Tc (min.)
<b>Existing Conditions</b>			
Watershed 1	544,237	47	51.7
Watershed 2	15,386	82	6.0
<b>Existing Total</b>	<b>559,623</b>	<b>48</b>	<b>--</b>
<b>Proposed Conditions</b>			
Subwatershed 1A	9,000	98	6.0
Subwatershed 1B	30,994	84	6.0
Subwatershed 1D	286,475	88	6.0
Subwatershed 1E	76,715	80	6.0
Subwatershed 1F	20,166	42	6.0
Subwatershed 2A	6,500	98	6.0
Subwatershed 2B	11,917	89	6.0
Subwatershed 3A	6,500	98	6.0
Subwatershed 3B	8,824	98	6.0
Subwatershed 4A	13,000	98	6.0
Subwatershed 4B	13,602	83	6.0
Subwatershed 5A	13,000	98	6.0
Subwatershed 5B	8,940	98	6.0
Subwatershed 6A	19,900	98	6.0
Subwatershed 6B	29,236	86	6.0
Watershed 2	4,854	86	6.0
<b>Proposed Total</b>	<b>559,623</b>	<b>86</b>	<b>--</b>

As shown in Table 4 above, the overall watershed area remains unchanged when comparing existing to proposed conditions. However, due to the increase in impervious areas associated with the proposed development, the CN value has been increased by 38 when comparing existing to proposed conditions.

Table 5: Stormwater Runoff Discharge Summary

	Peak Discharge (cfs) to Design Point				
	1-Year	2-Year	10-Year	25-Year	100-Year
Existing DP #1	0.0	0.2	1.6	4.8	13.3
Approved DP #1	0.0	0.0	1.6	4.8	13.2
Revised DP #1	0.0	0.0	1.1	3.9	12.4
<b>ΔQ</b>	<b>0.0</b>	<b>-0.2</b>	<b>-0.5</b>	<b>-0.9</b>	<b>-0.9</b>
Existing DP #2	0.5	0.7	1.2	1.7	2.6
Approved DP #2	0.2	0.3	0.4	0.6	0.9
Revised DP #2	0.2	0.2	0.4	0.6	0.8
<b>ΔQ</b>	<b>-0.3</b>	<b>-0.5</b>	<b>-0.8</b>	<b>-1.1</b>	<b>-1.8</b>

**Table 6: Total Stormwater Runoff Volume Summary**

	<b>Total Runoff Volume (ac-ft) to Design Point</b>				
	1-yr	2-yr	10-yr	25-yr	100-yr
Existing DP #1	0.02	0.09	0.49	1.06	2.44
Approved DP #1	0.00	0.00	0.10	0.38	1.09
Revised DP #1	0.00	0.00	0.06	0.27	0.88
<b><math>\Delta V</math></b>	<b>-0.02</b>	<b>-0.09</b>	<b>-0.43</b>	<b>-0.79</b>	<b>-1.56</b>
Existing DP #2	0.03	0.05	0.09	0.12	0.19
Approved DP #2	0.01	0.02	0.03	0.04	0.06
Revised DP #2	0.01	0.02	0.03	0.04	0.06
<b><math>\Delta V</math></b>	<b>-0.02</b>	<b>-0.03</b>	<b>-0.06</b>	<b>-0.08</b>	<b>-0.13</b>

As shown in Tables 5 and 6, the peak stormwater runoff rates and total stormwater runoff volumes realized at Design Point 1 (Southern and Western Property Lines) and Design Point 2 (Post Road) have been reduced for all design storm events. Reductions have been further improved upon when compared to the previously approved condition. This will result in a reduction of stormwater routed onto adjacent properties and will reduce stress on the public drainage system within Post Road.

### **Conclusion**

As discussed previously, the original design included an infiltration basin and four (4) underground infiltration chamber systems dispersed throughout the development. One (1) of the underground infiltration chamber systems and the infiltration basin were constructed as part of Phase I. The remaining systems have been modified to accommodate the proposed changes to the development design and layout. Under the new design, six (6) new underground infiltration chamber systems are proposed. The proposed drainage system has been designed to minimize impacts of the proposed site development on adjacent properties and the public right-of-way.







As shown above, the proposed stormwater management system has been designed in order to minimize impacts of the proposed site development by attenuating peak stormwater runoff rates and volumes for the 1-, 2-, 10, 25-, and 100-year design storm events. The proposed underground infiltration chamber systems have been designed to hold up to and including the 25-year design storm. The site's proposed stormwater management system greatly exceeds the requirements for groundwater recharge volume, water quality pre-treatment volume and water quality treatment volume. This is in accordance with all RISDISM and City of Warwick standards, and ultimately helps reduce stormwater flows into the State drainage system and adjacent properties.



**ATTACHMENT 1**

**MODIFIED POST-CONSTRUCTION WATERSHED MAP**

Q:\03-64-Rick Nardella\03-64e Post Road Storage\Drainage\Watershed Maps\Post Storage [Watershed Map] - R3.dwg, Sep. 01, 2022 11:57am

**LEGEND**

-  PROPERTY LINE
-  SUBCATCHMENT BOUNDARY
-  TIME OF CONCENTRATION
-  EX-1 SUBCATCHMENT AREA
-  DP-1 DESIGN POINT
-  P-1 STORMWATER POND

**JCE**  
 JOE CASALI ENGINEERING, INC.  
 CIVIL - SITE DEVELOPMENT - TRANSPORTATION  
 DRAINAGE - WETLANDS - ISDS - TRAFFIC - FLOODPLAIN  
 300 POST ROAD, WARWICK, RI 02886  
 (401) 944-1900 (401) 944-1313 FAX WWW.JOECASALI.COM

**MIXED-USE DEVELOPMENT**  
 2826 POST ROAD  
 WARWICK, RHODE ISLAND  
 AP 267, LOT 217

REVISIONS:

NO.	DATE	DESCRIPTION

DESIGNED BY: SD  
 DRAWN BY: SD  
 CHECKED BY: JAC  
 DATE: SEPT. 2022  
 PROJECT NO: 03-64e


STORMWATER REPORT

**PROPOSED WATERSHED MAP**

**SHEET 1 OF 1**

**ATTACHMENT 2**

**MODIFIED PROPOSED HYDROCAD CALCULATIONS**



**Routing Diagram for 2826 Post Road Phase II Modifications - Proposed**  
 Prepared by {enter your company name here}, Printed 10/6/2022  
 HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

## 2826 Post Road Phase II Modifications - Proposed

Prepared by {enter your company name here}

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Printed 10/6/2022

Page 2

### Area Listing (all nodes)

Area (sq-ft)	CN	Description (subcatchment-numbers)
16,907	68	<50% Grass cover, Poor, HSG A (PR-1D, PR-1E)
66,517	39	>75% Grass cover, Good, HSG A (PR-1B, PR-1D, PR-1E, PR-1F, PR-2, PR-2B, PR-4B, PR-6B)
536	61	>75% Grass cover, Good, HSG B (PR-1D, PR-1F)
1,253	80	>75% Grass cover, Good, HSG D (PR-2)
5,130	72	Dirt roads, HSG A (PR-1D, PR-1E)
85,172	98	Paved parking and sidewalks, HSG A (PR-1B, PR-2B, PR-3B, PR-4B, PR-5B, PR-6B)
144,295	98	Paved parking, HSG A (PR-1D, PR-1E, PR-2)
2,111	98	Paved parking, HSG B (PR-1D)
2,135	98	Paved parking, HSG D (PR-2)
202,787	98	Roofs, HSG A (PR-1A, PR-1D, PR-1E, PR-2A, PR-3A, PR-4A, PR-5A, PR-6A)
1,705	98	Roofs, HSG B (PR-1D)
12,907	36	Woods, Fair, HSG A (PR-1E, PR-1F)
3,966	60	Woods, Fair, HSG B (PR-1F)
3,402	30	Woods, Good, HSG A (PR-1D, PR-1E)
10,736	32	Woods/grass comb., Good, HSG A (PR-1D, PR-1E)
<b>559,558</b>	<b>86</b>	<b>TOTAL AREA</b>

## 2826 Post Road Phase II Modifications - Proposed

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 3

### Soil Listing (all nodes)

Area (sq-ft)	Soil Group	Subcatchment Numbers
547,852	HSG A	PR-1A, PR-1B, PR-1D, PR-1E, PR-1F, PR-2, PR-2A, PR-2B, PR-3A, PR-3B, PR-4A, PR-4B, PR-5A, PR-5B, PR-6A, PR-6B
8,318	HSG B	PR-1D, PR-1F
0	HSG C	
3,388	HSG D	PR-2
0	Other	
<b>559,558</b>		<b>TOTAL AREA</b>



## 2826 Post Road Phase II Modifications - Proposed

Prepared by {enter your company name here}

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Printed 10/6/2022

Page 4

### Ground Covers (all nodes)

HSG-A (sq-ft)	HSG-B (sq-ft)	HSG-C (sq-ft)	HSG-D (sq-ft)	Other (sq-ft)	Total (sq-ft)	Ground Cover
16,907	0	0	0	0	16,907	<50% Grass cover, Poor
66,517	536	0	1,253	0	68,307	>75% Grass cover, Good
5,130	0	0	0	0	5,130	Dirt roads
144,295	2,111	0	2,135	0	148,541	Paved parking
85,172	0	0	0	0	85,172	Paved parking and sidewalks
202,787	1,705	0	0	0	204,492	Roofs
12,907	3,966	0	0	0	16,873	Woods, Fair
3,402	0	0	0	0	3,402	Woods, Good
10,736	0	0	0	0	10,736	Woods/grass comb., Good
<b>547,852</b>	<b>8,318</b>	<b>0</b>	<b>3,388</b>	<b>0</b>	<b>559,558</b>	<b>TOTAL AREA</b>

## 2826 Post Road Phase II Modifications - Proposed

Prepared by {enter your company name here}

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Printed 10/6/2022

Page 5

### Pipe Listing (all nodes)

Line#	Node Number	In-Invert (feet)	Out-Invert (feet)	Length (feet)	Slope (ft/ft)	n	Diam/Width (inches)	Height (inches)	Inside-Fill (inches)
1	P-1D	31.40	31.00	25.0	0.0160	0.012	24.0	0.0	0.0

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 1-Year Rainfall=2.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 6

Time span=0.00-28.00 hrs, dt=0.05 hrs, 561 points  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

**SubcatchmentPR-1A: Subwatershed 1A** - Runoff Area=9,000 sf 100.00% Impervious Runoff Depth=2.47"  
Tc=6.0 min CN=98 Runoff=0.53 cfs 1,852 cf

**SubcatchmentPR-1B: Subwatershed 1B** - Runoff Area=30,994 sf 75.91% Impervious Runoff Depth=1.27"  
Tc=6.0 min CN=84 Runoff=1.04 cfs 3,289 cf

**SubcatchmentPR-1D: Bldg 3 & 5-12 and** Runoff Area=286,475 sf 80.60% Impervious Runoff Depth=1.55"  
Tc=6.0 min CN=88 Runoff=11.74 cfs 37,102 cf

**SubcatchmentPR-1E: Portion of Bldg 12 &** Runoff Area=76,715 sf 66.84% Impervious Runoff Depth=1.03"  
Tc=6.0 min CN=80 Runoff=2.04 cfs 6,583 cf

**SubcatchmentPR-1F: Undetained Area** Runoff Area=20,166 sf 0.00% Impervious Runoff Depth=0.00"  
Tc=6.0 min CN=42 Runoff=0.00 cfs 0 cf

**SubcatchmentPR-2: Area Discharging to** Runoff Area=4,789 sf 61.89% Impervious Runoff Depth=1.41"  
Tc=6.0 min CN=86 Runoff=0.18 cfs 562 cf

**SubcatchmentPR-2A: Subwatershed 2A** - Runoff Area=6,500 sf 100.00% Impervious Runoff Depth=2.47"  
Tc=6.0 min CN=98 Runoff=0.38 cfs 1,338 cf

**SubcatchmentPR-2B: Subwatershed 2B** - Runoff Area=11,917 sf 85.52% Impervious Runoff Depth=1.63"  
Tc=6.0 min CN=89 Runoff=0.51 cfs 1,620 cf

**SubcatchmentPR-3A: Subwatershed 3A** - Runoff Area=6,500 sf 100.00% Impervious Runoff Depth=2.47"  
Tc=6.0 min CN=98 Runoff=0.38 cfs 1,338 cf

**SubcatchmentPR-3B: Subwatershed 3B** - Runoff Area=8,824 sf 100.00% Impervious Runoff Depth=2.47"  
Tc=6.0 min CN=98 Runoff=0.52 cfs 1,816 cf

**SubcatchmentPR-4A: Subwatershed 4A** - Runoff Area=13,000 sf 100.00% Impervious Runoff Depth=2.47"  
Tc=6.0 min CN=98 Runoff=0.76 cfs 2,675 cf

**SubcatchmentPR-4B: Subwatershed 4B** - Runoff Area=13,602 sf 74.92% Impervious Runoff Depth=1.21"  
Tc=6.0 min CN=83 Runoff=0.43 cfs 1,371 cf

**SubcatchmentPR-5A: Subwatershed 5A** - Runoff Area=13,000 sf 100.00% Impervious Runoff Depth=2.47"  
Tc=6.0 min CN=98 Runoff=0.76 cfs 2,675 cf

**SubcatchmentPR-5B: Subwatershed 5B** - Runoff Area=8,940 sf 100.00% Impervious Runoff Depth=2.47"  
Tc=6.0 min CN=98 Runoff=0.52 cfs 1,840 cf

**SubcatchmentPR-6A: Subwatershed 6A** - Runoff Area=19,900 sf 100.00% Impervious Runoff Depth=2.47"  
Tc=6.0 min CN=98 Runoff=1.16 cfs 4,095 cf

**SubcatchmentPR-6B: Subwatershed 6B** - Runoff Area=29,236 sf 80.37% Impervious Runoff Depth=1.41"  
Tc=6.0 min CN=86 Runoff=1.09 cfs 3,432 cf

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 1-Year Rainfall=2.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 7

<b>Pond P-1A: UIC #1</b>	Peak Elev=46.68' Storage=251 cf Inflow=1.56 cfs 4,360 cf Discarded=0.83 cfs 4,355 cf Primary=0.00 cfs 0 cf Outflow=0.83 cfs 4,355 cf
<b>Pond P-1B: Isolator Row #1</b>	Peak Elev=49.35' Storage=746 cf Inflow=1.04 cfs 3,289 cf Outflow=1.07 cfs 2,508 cf
<b>Pond P-1D: Underground Infiltration</b>	Peak Elev=45.25' Storage=4,827 cf Inflow=11.74 cfs 37,102 cf Discarded=4.86 cfs 37,102 cf Primary=0.00 cfs 0 cf Outflow=4.86 cfs 37,102 cf
<b>Pond P-1E: Infiltration Basin</b>	Peak Elev=45.29' Storage=1,070 cf Inflow=2.04 cfs 6,583 cf Discarded=0.74 cfs 6,583 cf Primary=0.00 cfs 0 cf Outflow=0.74 cfs 6,583 cf
<b>Pond P-2A: UIC #2</b>	Peak Elev=46.77' Storage=208 cf Inflow=0.89 cfs 2,570 cf Discarded=0.47 cfs 2,571 cf Primary=0.00 cfs 0 cf Outflow=0.47 cfs 2,571 cf
<b>Pond P-2B: Isolator Row #2</b>	Peak Elev=49.34' Storage=383 cf Inflow=0.51 cfs 1,620 cf Outflow=0.51 cfs 1,232 cf
<b>Pond P-3A: UIC #3</b>	Peak Elev=46.94' Storage=294 cf Inflow=0.89 cfs 2,781 cf Discarded=0.41 cfs 2,774 cf Primary=0.00 cfs 0 cf Outflow=0.41 cfs 2,774 cf
<b>Pond P-3B: Isolator Row #3</b>	Peak Elev=49.34' Storage=383 cf Inflow=0.52 cfs 1,816 cf Outflow=0.51 cfs 1,443 cf
<b>Pond P-4A: UIC #4</b>	Peak Elev=46.74' Storage=210 cf Inflow=0.89 cfs 3,653 cf Discarded=0.53 cfs 3,644 cf Primary=0.00 cfs 0 cf Outflow=0.53 cfs 3,644 cf
<b>Pond P-4B: Isolator Row #4</b>	Peak Elev=49.31' Storage=380 cf Inflow=0.43 cfs 1,371 cf Outflow=0.33 cfs 977 cf
<b>Pond P-5A: UIC #5</b>	Peak Elev=47.02' Storage=477 cf Inflow=1.28 cfs 4,140 cf Discarded=0.54 cfs 4,135 cf Primary=0.00 cfs 0 cf Outflow=0.54 cfs 4,135 cf
<b>Pond P-5B: Isolator Row #5</b>	Peak Elev=49.34' Storage=383 cf Inflow=0.52 cfs 1,840 cf Outflow=0.52 cfs 1,464 cf
<b>Pond P-6A: UIC #6</b>	Peak Elev=45.05' Storage=90 cf Inflow=1.16 cfs 6,069 cf Discarded=0.99 cfs 6,075 cf Primary=0.00 cfs 0 cf Outflow=0.99 cfs 6,075 cf
<b>Pond P-6B: Isolator Row #6</b>	Peak Elev=47.81' Storage=1,458 cf Inflow=1.09 cfs 3,432 cf Outflow=0.55 cfs 1,973 cf
<b>Link DP-1: Existing Drainage System - Phase 1</b>	Inflow=0.00 cfs 0 cf Primary=0.00 cfs 0 cf
<b>Link DP-2: Post Road</b>	Inflow=0.18 cfs 562 cf Primary=0.18 cfs 562 cf

**Total Runoff Area = 559,558 sf Runoff Volume = 71,588 cf Average Runoff Depth = 1.54"**  
**21.69% Pervious = 121,354 sf 78.31% Impervious = 438,205 sf**

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 1-Year Rainfall=2.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 8

**Summary for Subcatchment PR-1A: Subwatershed 1A - Roof A**

Runoff = 0.53 cfs @ 12.09 hrs, Volume= 1,852 cf, Depth= 2.47"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 1-Year Rainfall=2.70"

Area (sf)	CN	Description
9,000	98	Roofs, HSG A
9,000	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-1B: Subwatershed 1B - Parking Lot**

Runoff = 1.04 cfs @ 12.09 hrs, Volume= 3,289 cf, Depth= 1.27"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 1-Year Rainfall=2.70"

Area (sf)	CN	Description
* 23,528	98	Paved parking and sidewalks, HSG A
7,466	39	>75% Grass cover, Good, HSG A
30,994	84	Weighted Average
7,466	39	24.09% Pervious Area
23,528	98	75.91% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-1D: Bldg 3 & 5-12 and Pvt**

Runoff = 11.74 cfs @ 12.09 hrs, Volume= 37,102 cf, Depth= 1.55"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 1-Year Rainfall=2.70"

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 1-Year Rainfall=2.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 9

Area (sf)	CN	Description
8,805	32	Woods/grass comb., Good, HSG A
2,001	72	Dirt roads, HSG A
28,102	39	>75% Grass cover, Good, HSG A
113,211	98	Roofs, HSG A
113,868	98	Paved parking, HSG A
15,161	68	<50% Grass cover, Poor, HSG A
1,158	30	Woods, Good, HSG A
1,705	98	Roofs, HSG B
2,111	98	Paved parking, HSG B
353	61	>75% Grass cover, Good, HSG B
286,475	88	Weighted Average
55,580	47	19.40% Pervious Area
230,895	98	80.60% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-1E: Portion of Bldg 12 & Pvt Draining to Basin**

Runoff = 2.04 cfs @ 12.10 hrs, Volume= 6,583 cf, Depth= 1.03"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 1-Year Rainfall=2.70"

Area (sf)	CN	Description
14,109	39	>75% Grass cover, Good, HSG A
21,676	98	Roofs, HSG A
29,598	98	Paved parking, HSG A
3,129	72	Dirt roads, HSG A
1,746	68	<50% Grass cover, Poor, HSG A
2,283	36	Woods, Fair, HSG A
2,244	30	Woods, Good, HSG A
1,931	32	Woods/grass comb., Good, HSG A
76,715	80	Weighted Average
25,442	43	33.16% Pervious Area
51,274	98	66.84% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-1F: Undetained Area**

Runoff = 0.00 cfs @ 0.00 hrs, Volume= 0 cf, Depth= 0.00"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 1-Year Rainfall=2.70"

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 1-Year Rainfall=2.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 10

Area (sf)	CN	Description
5,393	39	>75% Grass cover, Good, HSG A
10,624	36	Woods, Fair, HSG A
183	61	>75% Grass cover, Good, HSG B
3,966	60	Woods, Fair, HSG B
20,166	42	Weighted Average
20,166	42	100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-2: Area Discharging to Post Road**

Runoff = 0.18 cfs @ 12.09 hrs, Volume= 562 cf, Depth= 1.41"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 1-Year Rainfall=2.70"

Area (sf)	CN	Description
829	98	Paved parking, HSG A
572	39	>75% Grass cover, Good, HSG A
2,135	98	Paved parking, HSG D
1,253	80	>75% Grass cover, Good, HSG D
4,789	86	Weighted Average
1,825	67	38.11% Pervious Area
2,964	98	61.89% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-2A: Subwatershed 2A - Roof**

Runoff = 0.38 cfs @ 12.09 hrs, Volume= 1,338 cf, Depth= 2.47"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 1-Year Rainfall=2.70"

Area (sf)	CN	Description
6,500	98	Roofs, HSG A
6,500	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 1-Year Rainfall=2.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 11

**Summary for Subcatchment PR-2B: Subwatershed 2B - Parking Lot**

Runoff = 0.51 cfs @ 12.09 hrs, Volume= 1,620 cf, Depth= 1.63"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 1-Year Rainfall=2.70"

	Area (sf)	CN	Description
*	10,191	98	Paved parking and sidewalks, HSG A
	1,726	39	>75% Grass cover, Good, HSG A
	11,917	89	Weighted Average
	1,726	39	14.48% Pervious Area
	10,191	98	85.52% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry, SEG A

**Summary for Subcatchment PR-3A: Subwatershed 3A - Roof**

Runoff = 0.38 cfs @ 12.09 hrs, Volume= 1,338 cf, Depth= 2.47"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 1-Year Rainfall=2.70"

	Area (sf)	CN	Description
	6,500	98	Roofs, HSG A
	6,500	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry, SEG A

**Summary for Subcatchment PR-3B: Subwatershed 3B - Parking Lot**

Runoff = 0.52 cfs @ 12.09 hrs, Volume= 1,816 cf, Depth= 2.47"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 1-Year Rainfall=2.70"

	Area (sf)	CN	Description
*	8,824	98	Paved parking and sidewalks, HSG A
	8,824	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry, SEG A



**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 1-Year Rainfall=2.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 12

**Summary for Subcatchment PR-4A: Subwatershed 4A - Roof**

Runoff = 0.76 cfs @ 12.09 hrs, Volume= 2,675 cf, Depth= 2.47"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 1-Year Rainfall=2.70"

Area (sf)	CN	Description
13,000	98	Roofs, HSG A
13,000	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-4B: Subwatershed 4B - Parking Lot**

Runoff = 0.43 cfs @ 12.10 hrs, Volume= 1,371 cf, Depth= 1.21"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 1-Year Rainfall=2.70"

Area (sf)	CN	Description
* 10,191	98	Paved parking and sidewalks, HSG A
3,411	39	>75% Grass cover, Good, HSG A
13,602	83	Weighted Average
3,411	39	25.08% Pervious Area
10,191	98	74.92% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-5A: Subwatershed 5A - Roof**

Runoff = 0.76 cfs @ 12.09 hrs, Volume= 2,675 cf, Depth= 2.47"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 1-Year Rainfall=2.70"

Area (sf)	CN	Description
13,000	98	Roofs, HSG A
13,000	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-5B: Subwatershed 5B - Parking Lot**

Runoff = 0.52 cfs @ 12.09 hrs, Volume= 1,840 cf, Depth= 2.47"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 1-Year Rainfall=2.70"

Area (sf)	CN	Description
* 8,940	98	Paved parking and sidewalks, HSG A
8,940	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-6A: Subwatershed 6A - Roof**

Runoff = 1.16 cfs @ 12.09 hrs, Volume= 4,095 cf, Depth= 2.47"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 1-Year Rainfall=2.70"

Area (sf)	CN	Description
19,900	98	Roofs, HSG A
19,900	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-6B: Subwatershed 6B - Parking Lot**

Runoff = 1.09 cfs @ 12.09 hrs, Volume= 3,432 cf, Depth= 1.41"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 1-Year Rainfall=2.70"

Area (sf)	CN	Description
* 23,498	98	Paved parking and sidewalks, HSG A
5,738	39	>75% Grass cover, Good, HSG A
29,236	86	Weighted Average
5,738	39	19.63% Pervious Area
23,498	98	80.37% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Pond P-1A: UIC #1**

Inflow Area = 39,994 sf, 81.33% Impervious, Inflow Depth = 1.31" for 1-Year event  
 Inflow = 1.56 cfs @ 12.12 hrs, Volume= 4,360 cf  
 Outflow = 0.83 cfs @ 12.25 hrs, Volume= 4,355 cf, Atten= 47%, Lag= 7.8 min  
 Discarded = 0.83 cfs @ 12.25 hrs, Volume= 4,355 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 46.68' @ 12.25 hrs Surf.Area= 4,161 sf Storage= 251 cf

Plug-Flow detention time= 2.7 min calculated for 4,355 cf (100% of inflow)  
 Center-of-Mass det. time= 1.9 min ( 831.6 - 829.7 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	3,108 cf	<b>20.50'W x 202.98'L x 3.50'H Field A</b> 14,564 cf Overall - 5,145 cf Embedded = 9,418 cf x 33.0% Voids
#2A	47.00'	5,145 cf	<b>ADS_StormTech SC-740 +Cap</b> x 112 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 112 Chambers in 4 Rows
		8,253 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.83 cfs @ 12.25 hrs HW=46.68' (Free Discharge)  
 ↑1=Exfiltration (Exfiltration Controls 0.83 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)  
 ↑2=Sharp-Crested Rectangular Weir( Controls 0.00 cfs)

**Summary for Pond P-1B: Isolator Row #1**

Inflow Area = 30,994 sf, 75.91% Impervious, Inflow Depth = 1.27" for 1-Year event  
 Inflow = 1.04 cfs @ 12.09 hrs, Volume= 3,289 cf  
 Outflow = 1.07 cfs @ 12.12 hrs, Volume= 2,508 cf, Atten= 0%, Lag= 1.5 min  
 Primary = 1.07 cfs @ 12.12 hrs, Volume= 2,508 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 49.35' @ 12.10 hrs Surf.Area= 468 sf Storage= 746 cf

Plug-Flow detention time= 130.0 min calculated for 2,503 cf (76% of inflow)  
 Center-of-Mass det. time= 43.5 min ( 881.1 - 837.6 )

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 1-Year Rainfall=2.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 15

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	388 cf	<b>6.25'W x 74.82'L x 3.50'H Field A</b> 1,637 cf Overall - 459 cf Embedded = 1,177 cf x 33.0% Voids
#2A	47.00'	459 cf	<b>ADS_StormTech SC-740 +Cap</b> x 10 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		848 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>5.0' long Sharp-Crested Rectangular Weir X 2.00</b> 2 End Contraction(s)

**Primary OutFlow** Max=0.93 cfs @ 12.12 hrs HW=49.34' (Free Discharge)↑**1=Sharp-Crested Rectangular Weir**(Weir Controls 0.93 cfs @ 1.00 fps)**Summary for Pond P-1D: Underground Infiltration**

Inflow Area = 286,475 sf, 80.60% Impervious, Inflow Depth = 1.55" for 1-Year event  
 Inflow = 11.74 cfs @ 12.09 hrs, Volume= 37,102 cf  
 Outflow = 4.86 cfs @ 12.33 hrs, Volume= 37,102 cf, Atten= 59%, Lag= 14.2 min  
 Discarded = 4.86 cfs @ 12.33 hrs, Volume= 37,102 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Peak Elev= 45.25' @ 12.33 hrs Surf.Area= 23,713 sf Storage= 4,827 cf

Plug-Flow detention time= 5.7 min calculated for 37,036 cf (100% of inflow)  
 Center-of-Mass det. time= 5.7 min ( 827.9 - 822.2 )

## 2826 Post Road Phase II Modifications - Proposed

Type III 24-hr 1-Year Rainfall=2.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 16

Volume	Invert	Avail.Storage	Storage Description
#1	44.70'	18,217 cf	<b>15.75'W x 1,505.60'L x 3.50'H Crushed Stone</b> 82,996 cf Overall - 27,794 cf Embedded = 55,202 cf x 33.0% Voids
#2	45.20'	1,103 cf	<b>P-1D-A</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 24 Chambers in 3 Rows
#3	45.20'	1,929 cf	<b>P-1D-B</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 42 Chambers in 3 Rows
#4	45.20'	1,240 cf	<b>P-1D-C</b> x 27 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 27 Chambers in 3 Rows
#5	45.20'	965 cf	<b>P-1D-D</b> x 21 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 21 Chambers in 3 Rows
#6	45.20'	1,654 cf	<b>P-1D-E</b> x 36 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 36 Chambers in 3 Rows
#7	45.20'	1,654 cf	<b>P-1D-F</b> x 36 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 36 Chambers in 3 Rows
#8	45.20'	1,103 cf	<b>P-1D-G</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 24 Chambers in 3 Rows
#9	45.20'	1,286 cf	<b>P-1D-H</b> x 28 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 28 Chambers in 2 Rows
#10	45.20'	184 cf	<b>P-1D-H</b> x 4 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#11	45.20'	413 cf	<b>P-1D-H</b> x 9 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#12	45.20'	2,067 cf	<b>P-1D-I</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 45 Chambers in 3 Rows
#13	45.20'	1,929 cf	<b>P-1D-J</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 42 Chambers in 3 Rows
#14	45.20'	2,067 cf	<b>P-1D-K</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 1-Year Rainfall=2.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 17

#15	45.20'	1,929 cf	45 Chambers in 3 Rows <b>P-1D-L</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#16	45.20'	2,067 cf	42 Chambers in 3 Rows <b>P-1D-M</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#17	45.20'	1,929 cf	45 Chambers in 3 Rows <b>P-1D-N</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#18	45.20'	2,067 cf	42 Chambers in 3 Rows <b>P-1D-O</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#19	45.20'	1,103 cf	45 Chambers in 3 Rows <b>P-1D-P</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#20	45.20'	1,103 cf	24 Chambers in 3 Rows <b>P-1D-Q</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#21	46.25'	134 cf	<b>18.0" Round Pipe CB5-DMH1</b> -Impervious L= 76.0' S= 0.0031 '/'
#22	45.70'	205 cf	<b>18.0" Round Pipe CB5-CB6</b> -Impervious L= 116.0' S= 0.0025 '/'
#23	46.10'	93 cf	<b>12.0" Round Pipe CB6-CB7</b> -Impervious L= 118.0' S= 0.0033 '/'
#24	46.50'	101 cf	<b>12.0" Round Pipe CB33-CB40</b> -Impervious L= 128.0' S= 0.0098 '/'
#25	46.10'	83 cf	<b>12.0" Round Pipe CB8-CB9</b> -Impervious L= 106.0' S= 0.0036 '/'
#26	45.70'	187 cf	<b>18.0" Round Pipe CB9-CB10</b> -Impervious L= 106.0' S= 0.0027 '/'
#27	46.20'	91 cf	<b>12.0" Round Pipe CB10-CB11</b> -Impervious L= 116.0' S= 0.0025 '/'
#28	45.30'	540 cf	<b>24.0" Round 24" Header Pipe</b> -Impervious L= 172.0'
#29	45.30'	855 cf	<b>4.00'D x 4.00'H CBs</b> x 17 -Impervious
#30	46.00'	50 cf	<b>4.00'D x 4.00'H CB-6</b> -Impervious
#31	46.50'	50 cf	<b>4.00'D x 4.00'H CB-7</b> -Impervious
#32	47.80'	50 cf	<b>4.00'D x 4.00'H CB-40</b> -Impervious
#33	46.50'	50 cf	<b>4.00'D x 4.00'H CB-8</b> -Impervious
#34	46.00'	50 cf	<b>4.00'D x 4.00'H CB-9</b> -Impervious
#35	46.50'	50 cf	<b>4.00'D x 4.00'H CB-11</b> -Impervious
#36	46.50'	50 cf	<b>4.00'D x 4.00'H CB-33</b> -Impervious

48,651 cf Total Available Storage

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 1-Year Rainfall=2.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 18

Device	Routing	Invert	Outlet Devices
#1	Discarded	44.70'	<b>8.270 in/hr Exfiltration over Wetted area</b> Phase-In= 0.01'
#2	Device 4	45.70'	<b>15.0" W x 21.0" H Vert. Orifice/Grate</b> C= 0.600
#3	Device 4	48.10'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)
#4	Primary	31.40'	<b>24.0" Round Culvert</b> L= 25.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 31.40' / 31.00' S= 0.0160 '/ Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 3.14 sf

**Discarded OutFlow** Max=4.86 cfs @ 12.33 hrs HW=45.25' (Free Discharge)

↑1=**Exfiltration** (Exfiltration Controls 4.86 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=44.70' (Free Discharge)

↑4=**Culvert** (Passes 0.00 cfs of 41.88 cfs potential flow)

↑2=**Orifice/Grate** ( Controls 0.00 cfs)

↑3=**Sharp-Crested Rectangular Weir** ( Controls 0.00 cfs)

**Summary for Pond P-1E: Infiltration Basin**

Inflow Area =	76,715 sf, 66.84% Impervious,	Inflow Depth = 1.03" for 1-Year event
Inflow =	2.04 cfs @ 12.10 hrs, Volume=	6,583 cf
Outflow =	0.74 cfs @ 12.42 hrs, Volume=	6,583 cf, Atten= 64%, Lag= 19.3 min
Discarded =	0.74 cfs @ 12.42 hrs, Volume=	6,583 cf
Primary =	0.00 cfs @ 0.00 hrs, Volume=	0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Peak Elev= 45.29' @ 12.42 hrs Surf.Area= 3,843 sf Storage= 1,070 cf

Plug-Flow detention time= 9.2 min calculated for 6,572 cf (100% of inflow)  
Center-of-Mass det. time= 9.2 min ( 861.1 - 851.9 )

Volume	Invert	Avail.Storage	Storage Description
#1	45.00'	21,635 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
45.00	3,597	0	0
46.00	4,453	4,025	4,025
47.00	5,366	4,910	8,935
48.00	6,336	5,851	14,786
49.00	7,362	6,849	21,635

Device	Routing	Invert	Outlet Devices
#1	Discarded	45.00'	<b>8.270 in/hr Exfiltration over Surface area</b> Phase-In= 0.01'
#2	Primary	48.20'	<b>35.0' long x 8.0' breadth Broad-Crested Rectangular Weir</b> Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.43 2.54 2.70 2.69 2.68 2.68 2.66 2.64 2.64 2.64 2.65 2.65 2.66 2.66 2.68 2.70 2.74

**Discarded OutFlow** Max=0.74 cfs @ 12.42 hrs HW=45.29' (Free Discharge)  
 ↑1=Exfiltration (Exfiltration Controls 0.74 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=45.00' (Free Discharge)  
 ↑2=Broad-Crested Rectangular Weir( Controls 0.00 cfs)

**Summary for Pond P-2A: UIC #2**

Inflow Area = 18,417 sf, 90.63% Impervious, Inflow Depth = 1.67" for 1-Year event  
 Inflow = 0.89 cfs @ 12.09 hrs, Volume= 2,570 cf  
 Outflow = 0.47 cfs @ 12.24 hrs, Volume= 2,571 cf, Atten= 47%, Lag= 8.8 min  
 Discarded = 0.47 cfs @ 12.24 hrs, Volume= 2,571 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 46.77' @ 12.24 hrs Surf.Area= 2,352 sf Storage= 208 cf

Plug-Flow detention time= (not calculated: outflow precedes inflow)  
 Center-of-Mass det. time= 2.4 min ( 811.9 - 809.5 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	1,762 cf	<b>34.75'W x 67.70'L x 3.50'H Field A</b> 8,234 cf Overall - 2,894 cf Embedded = 5,339 cf x 33.0% Voids
#2A	47.00'	2,894 cf	<b>ADS_StormTech SC-740 +Cap</b> x 63 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 63 Chambers in 7 Rows
		4,656 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.47 cfs @ 12.24 hrs HW=46.77' (Free Discharge)  
 ↑1=Exfiltration (Exfiltration Controls 0.47 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)  
 ↑2=Sharp-Crested Rectangular Weir( Controls 0.00 cfs)

**Summary for Pond P-2B: Isolator Row #2**

Inflow Area = 11,917 sf, 85.52% Impervious, Inflow Depth = 1.63" for 1-Year event  
 Inflow = 0.51 cfs @ 12.09 hrs, Volume= 1,620 cf  
 Outflow = 0.51 cfs @ 12.09 hrs, Volume= 1,232 cf, Atten= 1%, Lag= 0.0 min  
 Primary = 0.51 cfs @ 12.09 hrs, Volume= 1,232 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3



**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 1-Year Rainfall=2.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 20

Peak Elev= 49.34' @ 12.09 hrs Surf.Area= 245 sf Storage= 383 cf

Plug-Flow detention time= 130.0 min calculated for 1,232 cf (76% of inflow)  
Center-of-Mass det. time= 45.1 min ( 863.1 - 818.0 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap x 5</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=0.50 cfs @ 12.09 hrs HW=49.34' (Free Discharge)  
 ↳ **1=Sharp-Crested Rectangular Weir** (Weir Controls 0.50 cfs @ 0.96 fps)

**Summary for Pond P-3A: UIC #3**

Inflow Area = 15,324 sf, 100.00% Impervious, Inflow Depth = 2.18" for 1-Year event  
 Inflow = 0.89 cfs @ 12.09 hrs, Volume= 2,781 cf  
 Outflow = 0.41 cfs @ 12.26 hrs, Volume= 2,774 cf, Atten= 54%, Lag= 10.5 min  
 Discarded = 0.41 cfs @ 12.26 hrs, Volume= 2,774 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 46.94' @ 12.26 hrs Surf.Area= 2,031 sf Storage= 294 cf

Plug-Flow detention time= 5.2 min calculated for 2,774 cf (100% of inflow)  
 Center-of-Mass det. time= 3.6 min ( 795.1 - 791.5 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	1,527 cf	<b>30.00'W x 67.70'L x 3.50'H Field A</b> 7,108 cf Overall - 2,481 cf Embedded = 4,627 cf x 33.0% Voids
#2A	47.00'	2,481 cf	<b>ADS_StormTech SC-740 +Cap x 54</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 54 Chambers in 6 Rows
		4,008 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 1-Year Rainfall=2.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 21

**Discarded OutFlow** Max=0.41 cfs @ 12.26 hrs HW=46.94' (Free Discharge)

↑1=Exfiltration (Exfiltration Controls 0.41 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)

↑2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

**Summary for Pond P-3B: Isolator Row #3**

Inflow Area = 8,824 sf, 100.00% Impervious, Inflow Depth = 2.47" for 1-Year event  
 Inflow = 0.52 cfs @ 12.09 hrs, Volume= 1,816 cf  
 Outflow = 0.51 cfs @ 12.09 hrs, Volume= 1,443 cf, Atten= 1%, Lag= 0.2 min  
 Primary = 0.51 cfs @ 12.09 hrs, Volume= 1,443 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 49.34' @ 12.09 hrs Surf.Area= 245 sf Storage= 383 cf

Plug-Flow detention time= 136.4 min calculated for 1,440 cf (79% of inflow)  
 Center-of-Mass det. time= 60.4 min ( 820.6 - 760.1 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap x 5</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=0.50 cfs @ 12.09 hrs HW=49.34' (Free Discharge)

↑1=Sharp-Crested Rectangular Weir (Weir Controls 0.50 cfs @ 0.96 fps)

**Summary for Pond P-4A: UIC #4**

Inflow Area = 26,602 sf, 87.18% Impervious, Inflow Depth = 1.65" for 1-Year event  
 Inflow = 0.89 cfs @ 12.15 hrs, Volume= 3,653 cf  
 Outflow = 0.53 cfs @ 12.29 hrs, Volume= 3,644 cf, Atten= 41%, Lag= 8.5 min  
 Discarded = 0.53 cfs @ 12.29 hrs, Volume= 3,644 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 46.74' @ 12.29 hrs Surf.Area= 2,674 sf Storage= 210 cf

Plug-Flow detention time= 3.6 min calculated for 3,644 cf (100% of inflow)  
 Center-of-Mass det. time= 2.1 min ( 798.5 - 796.4 )

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 1-Year Rainfall=2.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 22

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	1,997 cf	<b>39.50'W x 67.70'L x 3.50'H Field A</b> 9,359 cf Overall - 3,308 cf Embedded = 6,051 cf x 33.0% Voids
#2A	47.00'	3,308 cf	<b>ADS_StormTech SC-740 +Cap x 72</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 72 Chambers in 8 Rows
		5,305 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.53 cfs @ 12.29 hrs HW=46.74' (Free Discharge)

↑**1=Exfiltration** (Exfiltration Controls 0.53 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)

↑**2=Sharp-Crested Rectangular Weir**( Controls 0.00 cfs)

**Summary for Pond P-4B: Isolator Row #4**

Inflow Area = 13,602 sf, 74.92% Impervious, Inflow Depth = 1.21" for 1-Year event  
 Inflow = 0.43 cfs @ 12.10 hrs, Volume= 1,371 cf  
 Outflow = 0.33 cfs @ 12.17 hrs, Volume= 977 cf, Atten= 23%, Lag= 4.6 min  
 Primary = 0.33 cfs @ 12.17 hrs, Volume= 977 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3

Peak Elev= 49.31' @ 12.15 hrs Surf.Area= 245 sf Storage= 380 cf

Plug-Flow detention time= 151.0 min calculated for 976 cf (71% of inflow)

Center-of-Mass det. time= 54.5 min ( 895.7 - 841.3 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap x 5</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=0.29 cfs @ 12.17 hrs HW=49.31' (Free Discharge)

↑**1=Sharp-Crested Rectangular Weir**(Weir Controls 0.29 cfs @ 0.80 fps)

**Summary for Pond P-5A: UIC #5**

Inflow Area = 21,940 sf, 100.00% Impervious, Inflow Depth = 2.26" for 1-Year event  
 Inflow = 1.28 cfs @ 12.09 hrs, Volume= 4,140 cf  
 Outflow = 0.54 cfs @ 12.29 hrs, Volume= 4,135 cf, Atten= 58%, Lag= 12.1 min  
 Discarded = 0.54 cfs @ 12.29 hrs, Volume= 4,135 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 47.02' @ 12.29 hrs Surf.Area= 2,681 sf Storage= 477 cf

Plug-Flow detention time= 5.1 min calculated for 4,135 cf (100% of inflow)  
 Center-of-Mass det. time= 4.2 min ( 785.6 - 781.4 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	2,004 cf	<b>44.25"W x 60.58"L x 3.50'H Field A</b> 9,382 cf Overall - 3,308 cf Embedded = 6,074 cf x 33.0% Voids
#2A	47.00'	3,308 cf	<b>ADS_StormTech SC-740 +Cap</b> x 72 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 72 Chambers in 9 Rows
		5,312 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.54 cfs @ 12.29 hrs HW=47.02' (Free Discharge)  
 ↑1=Exfiltration (Exfiltration Controls 0.54 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)  
 ↑2=Sharp-Crested Rectangular Weir ( Controls 0.00 cfs)

**Summary for Pond P-5B: Isolator Row #5**

Inflow Area = 8,940 sf, 100.00% Impervious, Inflow Depth = 2.47" for 1-Year event  
 Inflow = 0.52 cfs @ 12.09 hrs, Volume= 1,840 cf  
 Outflow = 0.52 cfs @ 12.09 hrs, Volume= 1,464 cf, Atten= 1%, Lag= 0.2 min  
 Primary = 0.52 cfs @ 12.09 hrs, Volume= 1,464 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 49.34' @ 12.09 hrs Surf.Area= 245 sf Storage= 383 cf

Plug-Flow detention time= 135.8 min calculated for 1,462 cf (79% of inflow)  
 Center-of-Mass det. time= 60.2 min ( 820.3 - 760.1 )

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 1-Year Rainfall=2.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 24

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap x 5</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=0.51 cfs @ 12.09 hrs HW=49.34' (Free Discharge)

↑**1=Sharp-Crested Rectangular Weir**(Weir Controls 0.51 cfs @ 0.97 fps)

**Summary for Pond P-6A: UIC #6**

Inflow Area = 49,136 sf, 88.32% Impervious, Inflow Depth = 1.48" for 1-Year event  
 Inflow = 1.16 cfs @ 12.09 hrs, Volume= 6,069 cf  
 Outflow = 0.99 cfs @ 12.15 hrs, Volume= 6,075 cf, Atten= 15%, Lag= 3.8 min  
 Discarded = 0.99 cfs @ 12.15 hrs, Volume= 6,075 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3

Peak Elev= 45.05' @ 12.13 hrs Surf.Area= 5,074 sf Storage= 90 cf

Plug-Flow detention time= (not calculated: outflow precedes inflow)

Center-of-Mass det. time= 0.9 min ( 813.6 - 812.6 )

Volume	Invert	Avail.Storage	Storage Description
#1A	45.00'	3,738 cf	<b>34.75'W x 146.02'L x 3.50'H Field A</b> 17,759 cf Overall - 6,432 cf Embedded = 11,328 cf x 33.0% Voids
#2A	45.50'	6,432 cf	<b>ADS_StormTech SC-740 +Cap x 140</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 140 Chambers in 7 Rows
		10,170 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	45.00'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	48.00'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.99 cfs @ 12.15 hrs HW=45.05' (Free Discharge)

↑**1=Exfiltration** (Exfiltration Controls 0.99 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=45.00' (Free Discharge)

↑**2=Sharp-Crested Rectangular Weir**( Controls 0.00 cfs)

## 2826 Post Road Phase II Modifications - Proposed

Type III 24-hr 1-Year Rainfall=2.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 25

### Summary for Pond P-6B: Isolator Row #6

Inflow Area = 29,236 sf, 80.37% Impervious, Inflow Depth = 1.41" for 1-Year event  
Inflow = 1.09 cfs @ 12.09 hrs, Volume= 3,432 cf  
Outflow = 0.55 cfs @ 12.32 hrs, Volume= 1,973 cf, Atten= 50%, Lag= 13.6 min  
Primary = 0.55 cfs @ 12.32 hrs, Volume= 1,973 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
Peak Elev= 47.81' @ 12.30 hrs Surf.Area= 913 sf Storage= 1,458 cf

Plug-Flow detention time= 202.3 min calculated for 1,970 cf (57% of inflow)  
Center-of-Mass det. time= 91.5 min ( 921.6 - 830.1 )

Volume	Invert	Avail.Storage	Storage Description
#1A	45.00'	751 cf	<b>6.25'W x 146.02'L x 3.50'H Field A</b> 3,194 cf Overall - 919 cf Embedded = 2,275 cf x 33.0% Voids
#2A	45.50'	919 cf	<b>ADS_StormTech SC-740 +Cap x 20 Inside #1</b> Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		1,670 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	47.75'	<b>5.0' long Sharp-Crested Rectangular Weir X 2.00</b> 2 End Contraction(s)

**Primary OutFlow** Max=0.47 cfs @ 12.32 hrs HW=47.81' (Free Discharge)  
↑#1=Sharp-Crested Rectangular Weir (Weir Controls 0.47 cfs @ 0.79 fps)

### Summary for Link DP-1: Existing Drainage System - Phase 1

Inflow Area = 554,769 sf, 78.45% Impervious, Inflow Depth = 0.00" for 1-Year event  
Inflow = 0.00 cfs @ 0.00 hrs, Volume= 0 cf  
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs

### Summary for Link DP-2: Post Road

Inflow Area = 4,789 sf, 61.89% Impervious, Inflow Depth = 1.41" for 1-Year event  
Inflow = 0.18 cfs @ 12.09 hrs, Volume= 562 cf  
Primary = 0.18 cfs @ 12.09 hrs, Volume= 562 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs

**2826 Post Road Phase II Modifications - Proposed***Type III 24-hr 2-Year Rainfall=3.30"*

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 26

Time span=0.00-28.00 hrs, dt=0.05 hrs, 561 points  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

**SubcatchmentPR-1A: Subwatershed 1A** - Runoff Area=9,000 sf 100.00% Impervious Runoff Depth=3.07"  
Tc=6.0 min CN=98 Runoff=0.65 cfs 2,300 cf

**SubcatchmentPR-1B: Subwatershed 1B** - Runoff Area=30,994 sf 75.91% Impervious Runoff Depth=1.77"  
Tc=6.0 min CN=84 Runoff=1.44 cfs 4,562 cf

**SubcatchmentPR-1D: Bldg 3 & 5-12 and** Runoff Area=286,475 sf 80.60% Impervious Runoff Depth=2.09"  
Tc=6.0 min CN=88 Runoff=15.69 cfs 49,826 cf

**SubcatchmentPR-1E: Portion of Bldg 12 &** Runoff Area=76,715 sf 66.84% Impervious Runoff Depth=1.48"  
Tc=6.0 min CN=80 Runoff=2.97 cfs 9,457 cf

**SubcatchmentPR-1F: Undetained Area** Runoff Area=20,166 sf 0.00% Impervious Runoff Depth=0.02"  
Tc=6.0 min CN=42 Runoff=0.00 cfs 34 cf

**SubcatchmentPR-2: Area Discharging to** Runoff Area=4,789 sf 61.89% Impervious Runoff Depth=1.92"  
Tc=6.0 min CN=86 Runoff=0.24 cfs 767 cf

**SubcatchmentPR-2A: Subwatershed 2A** - Runoff Area=6,500 sf 100.00% Impervious Runoff Depth=3.07"  
Tc=6.0 min CN=98 Runoff=0.47 cfs 1,661 cf

**SubcatchmentPR-2B: Subwatershed 2B** - Runoff Area=11,917 sf 85.52% Impervious Runoff Depth=2.17"  
Tc=6.0 min CN=89 Runoff=0.68 cfs 2,158 cf

**SubcatchmentPR-3A: Subwatershed 3A** - Runoff Area=6,500 sf 100.00% Impervious Runoff Depth=3.07"  
Tc=6.0 min CN=98 Runoff=0.47 cfs 1,661 cf

**SubcatchmentPR-3B: Subwatershed 3B** - Runoff Area=8,824 sf 100.00% Impervious Runoff Depth=3.07"  
Tc=6.0 min CN=98 Runoff=0.63 cfs 2,255 cf

**SubcatchmentPR-4A: Subwatershed 4A** - Runoff Area=13,000 sf 100.00% Impervious Runoff Depth=3.07"  
Tc=6.0 min CN=98 Runoff=0.93 cfs 3,323 cf

**SubcatchmentPR-4B: Subwatershed 4B** - Runoff Area=13,602 sf 74.92% Impervious Runoff Depth=1.69"  
Tc=6.0 min CN=83 Runoff=0.61 cfs 1,917 cf

**SubcatchmentPR-5A: Subwatershed 5A** - Runoff Area=13,000 sf 100.00% Impervious Runoff Depth=3.07"  
Tc=6.0 min CN=98 Runoff=0.93 cfs 3,323 cf

**SubcatchmentPR-5B: Subwatershed 5B** - Runoff Area=8,940 sf 100.00% Impervious Runoff Depth=3.07"  
Tc=6.0 min CN=98 Runoff=0.64 cfs 2,285 cf

**SubcatchmentPR-6A: Subwatershed 6A** - Runoff Area=19,900 sf 100.00% Impervious Runoff Depth=3.07"  
Tc=6.0 min CN=98 Runoff=1.43 cfs 5,086 cf

**SubcatchmentPR-6B: Subwatershed 6B** - Runoff Area=29,236 sf 80.37% Impervious Runoff Depth=1.92"  
Tc=6.0 min CN=86 Runoff=1.48 cfs 4,683 cf

<b>Pond P-1A: UIC #1</b>	Peak Elev=47.04' Storage=810 cf Inflow=2.08 cfs 6,127 cf Discarded=0.86 cfs 6,136 cf Primary=0.00 cfs 0 cf Outflow=0.86 cfs 6,136 cf
<b>Pond P-1B: Isolator Row #1</b>	Peak Elev=49.37' Storage=751 cf Inflow=1.44 cfs 4,562 cf Outflow=1.44 cfs 3,827 cf
<b>Pond P-1D: Underground Infiltration</b>	Peak Elev=45.47' Storage=8,898 cf Inflow=15.69 cfs 49,826 cf Discarded=4.99 cfs 49,826 cf Primary=0.00 cfs 0 cf Outflow=4.99 cfs 49,826 cf
<b>Pond P-1E: Infiltration Basin</b>	Peak Elev=45.55' Storage=2,121 cf Inflow=2.97 cfs 9,457 cf Discarded=0.78 cfs 9,457 cf Primary=0.00 cfs 0 cf Outflow=0.78 cfs 9,457 cf
<b>Pond P-2A: UIC #2</b>	Peak Elev=47.02' Storage=431 cf Inflow=1.14 cfs 3,439 cf Discarded=0.48 cfs 3,449 cf Primary=0.00 cfs 0 cf Outflow=0.48 cfs 3,449 cf
<b>Pond P-2B: Isolator Row #2</b>	Peak Elev=49.36' Storage=384 cf Inflow=0.68 cfs 2,158 cf Outflow=0.67 cfs 1,778 cf
<b>Pond P-3A: UIC #3</b>	Peak Elev=47.09' Storage=482 cf Inflow=1.10 cfs 3,541 cf Discarded=0.42 cfs 3,539 cf Primary=0.00 cfs 0 cf Outflow=0.42 cfs 3,539 cf
<b>Pond P-3B: Isolator Row #3</b>	Peak Elev=49.35' Storage=384 cf Inflow=0.63 cfs 2,255 cf Outflow=0.63 cfs 1,880 cf
<b>Pond P-4A: UIC #4</b>	Peak Elev=47.09' Storage=629 cf Inflow=1.54 cfs 4,845 cf Discarded=0.55 cfs 4,845 cf Primary=0.00 cfs 0 cf Outflow=0.55 cfs 4,845 cf
<b>Pond P-4B: Isolator Row #4</b>	Peak Elev=49.35' Storage=384 cf Inflow=0.61 cfs 1,917 cf Outflow=0.60 cfs 1,523 cf
<b>Pond P-5A: UIC #5</b>	Peak Elev=47.15' Storage=774 cf Inflow=1.57 cfs 5,234 cf Discarded=0.55 cfs 5,235 cf Primary=0.00 cfs 0 cf Outflow=0.55 cfs 5,235 cf
<b>Pond P-5B: Isolator Row #5</b>	Peak Elev=49.35' Storage=384 cf Inflow=0.64 cfs 2,285 cf Outflow=0.64 cfs 1,911 cf
<b>Pond P-6A: UIC #6</b>	Peak Elev=45.51' Storage=866 cf Inflow=2.52 cfs 8,361 cf Discarded=1.02 cfs 8,363 cf Primary=0.00 cfs 0 cf Outflow=1.02 cfs 8,363 cf
<b>Pond P-6B: Isolator Row #6</b>	Peak Elev=47.86' Storage=1,476 cf Inflow=1.48 cfs 4,683 cf Outflow=1.23 cfs 3,274 cf
<b>Link DP-1: Existing Drainage System - Phase 1</b>	Inflow=0.00 cfs 34 cf Primary=0.00 cfs 34 cf
<b>Link DP-2: Post Road</b>	Inflow=0.24 cfs 767 cf Primary=0.24 cfs 767 cf

**Total Runoff Area = 559,558 sf    Runoff Volume = 95,300 cf    Average Runoff Depth = 2.04"**  
**21.69% Pervious = 121,354 sf    78.31% Impervious = 438,205 sf**



**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 2-Year Rainfall=3.30"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 28

**Summary for Subcatchment PR-1A: Subwatershed 1A - Roof A**

Runoff = 0.65 cfs @ 12.09 hrs, Volume= 2,300 cf, Depth= 3.07"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-Year Rainfall=3.30"

Area (sf)	CN	Description
9,000	98	Roofs, HSG A
9,000	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-1B: Subwatershed 1B - Parking Lot**

Runoff = 1.44 cfs @ 12.09 hrs, Volume= 4,562 cf, Depth= 1.77"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-Year Rainfall=3.30"

Area (sf)	CN	Description
* 23,528	98	Paved parking and sidewalks, HSG A
7,466	39	>75% Grass cover, Good, HSG A
30,994	84	Weighted Average
7,466	39	24.09% Pervious Area
23,528	98	75.91% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-1D: Bldg 3 & 5-12 and Pvt**

Runoff = 15.69 cfs @ 12.09 hrs, Volume= 49,826 cf, Depth= 2.09"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-Year Rainfall=3.30"

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 2-Year Rainfall=3.30"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 29

Area (sf)	CN	Description
8,805	32	Woods/grass comb., Good, HSG A
2,001	72	Dirt roads, HSG A
28,102	39	>75% Grass cover, Good, HSG A
113,211	98	Roofs, HSG A
113,868	98	Paved parking, HSG A
15,161	68	<50% Grass cover, Poor, HSG A
1,158	30	Woods, Good, HSG A
1,705	98	Roofs, HSG B
2,111	98	Paved parking, HSG B
353	61	>75% Grass cover, Good, HSG B
286,475	88	Weighted Average
55,580	47	19.40% Pervious Area
230,895	98	80.60% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-1E: Portion of Bldg 12 & Pvt Draining to Basin**

Runoff = 2.97 cfs @ 12.10 hrs, Volume= 9,457 cf, Depth= 1.48"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-Year Rainfall=3.30"

Area (sf)	CN	Description
14,109	39	>75% Grass cover, Good, HSG A
21,676	98	Roofs, HSG A
29,598	98	Paved parking, HSG A
3,129	72	Dirt roads, HSG A
1,746	68	<50% Grass cover, Poor, HSG A
2,283	36	Woods, Fair, HSG A
2,244	30	Woods, Good, HSG A
1,931	32	Woods/grass comb., Good, HSG A
76,715	80	Weighted Average
25,442	43	33.16% Pervious Area
51,274	98	66.84% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-1F: Undetained Area**

Runoff = 0.00 cfs @ 20.76 hrs, Volume= 34 cf, Depth= 0.02"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-Year Rainfall=3.30"

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 2-Year Rainfall=3.30"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 30

Area (sf)	CN	Description
5,393	39	>75% Grass cover, Good, HSG A
10,624	36	Woods, Fair, HSG A
183	61	>75% Grass cover, Good, HSG B
3,966	60	Woods, Fair, HSG B
20,166	42	Weighted Average
20,166	42	100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-2: Area Discharging to Post Road**

Runoff = 0.24 cfs @ 12.09 hrs, Volume= 767 cf, Depth= 1.92"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-Year Rainfall=3.30"

Area (sf)	CN	Description
829	98	Paved parking, HSG A
572	39	>75% Grass cover, Good, HSG A
2,135	98	Paved parking, HSG D
1,253	80	>75% Grass cover, Good, HSG D
4,789	86	Weighted Average
1,825	67	38.11% Pervious Area
2,964	98	61.89% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-2A: Subwatershed 2A - Roof**

Runoff = 0.47 cfs @ 12.09 hrs, Volume= 1,661 cf, Depth= 3.07"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-Year Rainfall=3.30"

Area (sf)	CN	Description
6,500	98	Roofs, HSG A
6,500	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 2-Year Rainfall=3.30"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 31

**Summary for Subcatchment PR-2B: Subwatershed 2B - Parking Lot**

Runoff = 0.68 cfs @ 12.09 hrs, Volume= 2,158 cf, Depth= 2.17"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-Year Rainfall=3.30"

	Area (sf)	CN	Description
*	10,191	98	Paved parking and sidewalks, HSG A
	1,726	39	>75% Grass cover, Good, HSG A
	11,917	89	Weighted Average
	1,726	39	14.48% Pervious Area
	10,191	98	85.52% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry, SEG A

**Summary for Subcatchment PR-3A: Subwatershed 3A - Roof**

Runoff = 0.47 cfs @ 12.09 hrs, Volume= 1,661 cf, Depth= 3.07"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-Year Rainfall=3.30"

	Area (sf)	CN	Description
	6,500	98	Roofs, HSG A
	6,500	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry, SEG A

**Summary for Subcatchment PR-3B: Subwatershed 3B - Parking Lot**

Runoff = 0.63 cfs @ 12.09 hrs, Volume= 2,255 cf, Depth= 3.07"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-Year Rainfall=3.30"

	Area (sf)	CN	Description
*	8,824	98	Paved parking and sidewalks, HSG A
	8,824	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry, SEG A

**Summary for Subcatchment PR-4A: Subwatershed 4A - Roof**

Runoff = 0.93 cfs @ 12.09 hrs, Volume= 3,323 cf, Depth= 3.07"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 2-Year Rainfall=3.30"

Area (sf)	CN	Description
13,000	98	Roofs, HSG A
13,000	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-4B: Subwatershed 4B - Parking Lot**

Runoff = 0.61 cfs @ 12.09 hrs, Volume= 1,917 cf, Depth= 1.69"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 2-Year Rainfall=3.30"

Area (sf)	CN	Description
* 10,191	98	Paved parking and sidewalks, HSG A
3,411	39	>75% Grass cover, Good, HSG A
13,602	83	Weighted Average
3,411	39	25.08% Pervious Area
10,191	98	74.92% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-5A: Subwatershed 5A - Roof**

Runoff = 0.93 cfs @ 12.09 hrs, Volume= 3,323 cf, Depth= 3.07"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 2-Year Rainfall=3.30"

Area (sf)	CN	Description
13,000	98	Roofs, HSG A
13,000	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 2-Year Rainfall=3.30"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 33

**Summary for Subcatchment PR-5B: Subwatershed 5B - Parking Lot**

Runoff = 0.64 cfs @ 12.09 hrs, Volume= 2,285 cf, Depth= 3.07"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-Year Rainfall=3.30"

Area (sf)	CN	Description
* 8,940	98	Paved parking and sidewalks, HSG A
8,940	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-6A: Subwatershed 6A - Roof**

Runoff = 1.43 cfs @ 12.09 hrs, Volume= 5,086 cf, Depth= 3.07"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-Year Rainfall=3.30"

Area (sf)	CN	Description
19,900	98	Roofs, HSG A
19,900	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-6B: Subwatershed 6B - Parking Lot**

Runoff = 1.48 cfs @ 12.09 hrs, Volume= 4,683 cf, Depth= 1.92"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-Year Rainfall=3.30"

Area (sf)	CN	Description
* 23,498	98	Paved parking and sidewalks, HSG A
5,738	39	>75% Grass cover, Good, HSG A
29,236	86	Weighted Average
5,738	39	19.63% Pervious Area
23,498	98	80.37% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 2-Year Rainfall=3.30"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 34

**Summary for Pond P-1A: UIC #1**

Inflow Area = 39,994 sf, 81.33% Impervious, Inflow Depth = 1.84" for 2-Year event  
 Inflow = 2.08 cfs @ 12.09 hrs, Volume= 6,127 cf  
 Outflow = 0.86 cfs @ 12.33 hrs, Volume= 6,136 cf, Atten= 59%, Lag= 14.1 min  
 Discarded = 0.86 cfs @ 12.33 hrs, Volume= 6,136 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 47.04' @ 12.33 hrs Surf.Area= 4,161 sf Storage= 810 cf

Plug-Flow detention time= (not calculated: outflow precedes inflow)  
 Center-of-Mass det. time= 4.9 min ( 824.6 - 819.6 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	3,108 cf	<b>20.50'W x 202.98'L x 3.50'H Field A</b> 14,564 cf Overall - 5,145 cf Embedded = 9,418 cf x 33.0% Voids
#2A	47.00'	5,145 cf	<b>ADS_StormTech SC-740 +Cap</b> x 112 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 112 Chambers in 4 Rows
		8,253 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.86 cfs @ 12.33 hrs HW=47.04' (Free Discharge)  
 ↑1=Exfiltration (Exfiltration Controls 0.86 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)  
 ↑2=Sharp-Crested Rectangular Weir ( Controls 0.00 cfs)

**Summary for Pond P-1B: Isolator Row #1**

Inflow Area = 30,994 sf, 75.91% Impervious, Inflow Depth = 1.77" for 2-Year event  
 Inflow = 1.44 cfs @ 12.09 hrs, Volume= 4,562 cf  
 Outflow = 1.44 cfs @ 12.10 hrs, Volume= 3,827 cf, Atten= 1%, Lag= 0.2 min  
 Primary = 1.44 cfs @ 12.10 hrs, Volume= 3,827 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 49.37' @ 12.10 hrs Surf.Area= 468 sf Storage= 751 cf

Plug-Flow detention time= 98.0 min calculated for 3,827 cf (84% of inflow)  
 Center-of-Mass det. time= 29.9 min ( 858.0 - 828.1 )

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 2-Year Rainfall=3.30"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 35

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	388 cf	<b>6.25'W x 74.82'L x 3.50'H Field A</b> 1,637 cf Overall - 459 cf Embedded = 1,177 cf x 33.0% Voids
#2A	47.00'	459 cf	<b>ADS_StormTech SC-740 +Cap</b> x 10 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		848 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>5.0' long Sharp-Crested Rectangular Weir X 2.00</b> 2 End Contraction(s)

**Primary OutFlow** Max=1.42 cfs @ 12.10 hrs HW=49.37' (Free Discharge)

↑1=Sharp-Crested Rectangular Weir (Weir Controls 1.42 cfs @ 1.15 fps)

**Summary for Pond P-1D: Underground Infiltration**

Inflow Area = 286,475 sf, 80.60% Impervious, Inflow Depth = 2.09" for 2-Year event  
 Inflow = 15.69 cfs @ 12.09 hrs, Volume= 49,826 cf  
 Outflow = 4.99 cfs @ 12.42 hrs, Volume= 49,826 cf, Atten= 68%, Lag= 19.4 min  
 Discarded = 4.99 cfs @ 12.42 hrs, Volume= 49,826 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Peak Elev= 45.47' @ 12.42 hrs Surf.Area= 23,713 sf Storage= 8,898 cf

Plug-Flow detention time= 9.9 min calculated for 49,737 cf (100% of inflow)  
 Center-of-Mass det. time= 9.9 min ( 823.7 - 813.8 )



**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 2-Year Rainfall=3.30"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 36

Volume	Invert	Avail.Storage	Storage Description
#1	44.70'	18,217 cf	<b>15.75'W x 1,505.60'L x 3.50'H Crushed Stone</b> 82,996 cf Overall - 27,794 cf Embedded = 55,202 cf x 33.0% Voids
#2	45.20'	1,103 cf	<b>P-1D-A</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 24 Chambers in 3 Rows
#3	45.20'	1,929 cf	<b>P-1D-B</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 42 Chambers in 3 Rows
#4	45.20'	1,240 cf	<b>P-1D-C</b> x 27 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 27 Chambers in 3 Rows
#5	45.20'	965 cf	<b>P-1D-D</b> x 21 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 21 Chambers in 3 Rows
#6	45.20'	1,654 cf	<b>P-1D-E</b> x 36 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 36 Chambers in 3 Rows
#7	45.20'	1,654 cf	<b>P-1D-F</b> x 36 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 36 Chambers in 3 Rows
#8	45.20'	1,103 cf	<b>P-1D-G</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 24 Chambers in 3 Rows
#9	45.20'	1,286 cf	<b>P-1D-H</b> x 28 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 28 Chambers in 2 Rows
#10	45.20'	184 cf	<b>P-1D-H</b> x 4 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#11	45.20'	413 cf	<b>P-1D-H</b> x 9 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#12	45.20'	2,067 cf	<b>P-1D-I</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 45 Chambers in 3 Rows
#13	45.20'	1,929 cf	<b>P-1D-J</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 42 Chambers in 3 Rows
#14	45.20'	2,067 cf	<b>P-1D-K</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 2-Year Rainfall=3.30"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 37

#15	45.20'	1,929 cf	45 Chambers in 3 Rows <b>P-1D-L</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#16	45.20'	2,067 cf	42 Chambers in 3 Rows <b>P-1D-M</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#17	45.20'	1,929 cf	45 Chambers in 3 Rows <b>P-1D-N</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#18	45.20'	2,067 cf	42 Chambers in 3 Rows <b>P-1D-O</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#19	45.20'	1,103 cf	45 Chambers in 3 Rows <b>P-1D-P</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#20	45.20'	1,103 cf	24 Chambers in 3 Rows <b>P-1D-Q</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#21	46.25'	134 cf	<b>18.0" Round Pipe CB5-DMH1</b> -Impervious L= 76.0' S= 0.0031 '/'
#22	45.70'	205 cf	<b>18.0" Round Pipe CB5-CB6</b> -Impervious L= 116.0' S= 0.0025 '/'
#23	46.10'	93 cf	<b>12.0" Round Pipe CB6-CB7</b> -Impervious L= 118.0' S= 0.0033 '/'
#24	46.50'	101 cf	<b>12.0" Round Pipe CB33-CB40</b> -Impervious L= 128.0' S= 0.0098 '/'
#25	46.10'	83 cf	<b>12.0" Round Pipe CB8-CB9</b> -Impervious L= 106.0' S= 0.0036 '/'
#26	45.70'	187 cf	<b>18.0" Round Pipe CB9-CB10</b> -Impervious L= 106.0' S= 0.0027 '/'
#27	46.20'	91 cf	<b>12.0" Round Pipe CB10-CB11</b> -Impervious L= 116.0' S= 0.0025 '/'
#28	45.30'	540 cf	<b>24.0" Round 24" Header Pipe</b> -Impervious L= 172.0'
#29	45.30'	855 cf	<b>4.00'D x 4.00'H CBs</b> x 17 -Impervious
#30	46.00'	50 cf	<b>4.00'D x 4.00'H CB-6</b> -Impervious
#31	46.50'	50 cf	<b>4.00'D x 4.00'H CB-7</b> -Impervious
#32	47.80'	50 cf	<b>4.00'D x 4.00'H CB-40</b> -Impervious
#33	46.50'	50 cf	<b>4.00'D x 4.00'H CB-8</b> -Impervious
#34	46.00'	50 cf	<b>4.00'D x 4.00'H CB-9</b> -Impervious
#35	46.50'	50 cf	<b>4.00'D x 4.00'H CB-11</b> -Impervious
#36	46.50'	50 cf	<b>4.00'D x 4.00'H CB-33</b> -Impervious
		48,651 cf	Total Available Storage

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 2-Year Rainfall=3.30"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 38

Device	Routing	Invert	Outlet Devices
#1	Discarded	44.70'	<b>8.270 in/hr Exfiltration over Wetted area</b> Phase-In= 0.01'
#2	Device 4	45.70'	<b>15.0" W x 21.0" H Vert. Orifice/Grate</b> C= 0.600
#3	Device 4	48.10'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)
#4	Primary	31.40'	<b>24.0" Round Culvert</b> L= 25.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 31.40' / 31.00' S= 0.0160 '/ Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 3.14 sf

**Discarded OutFlow** Max=4.99 cfs @ 12.42 hrs HW=45.47' (Free Discharge)

↳ **1=Exfiltration** (Exfiltration Controls 4.99 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=44.70' (Free Discharge)

↳ **4=Culvert** (Passes 0.00 cfs of 41.88 cfs potential flow)

↳ **2=Orifice/Grate** ( Controls 0.00 cfs)

↳ **3=Sharp-Crested Rectangular Weir** ( Controls 0.00 cfs)

**Summary for Pond P-1E: Infiltration Basin**

Inflow Area =	76,715 sf, 66.84% Impervious,	Inflow Depth = 1.48"	for 2-Year event
Inflow =	2.97 cfs @ 12.10 hrs,	Volume=	9,457 cf
Outflow =	0.78 cfs @ 12.50 hrs,	Volume=	9,457 cf, Atten= 74%, Lag= 24.1 min
Discarded =	0.78 cfs @ 12.50 hrs,	Volume=	9,457 cf
Primary =	0.00 cfs @ 0.00 hrs,	Volume=	0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Peak Elev= 45.55' @ 12.50 hrs Surf.Area= 4,071 sf Storage= 2,121 cf

Plug-Flow detention time= 17.2 min calculated for 9,440 cf (100% of inflow)  
Center-of-Mass det. time= 17.2 min ( 858.3 - 841.2 )

Volume	Invert	Avail.Storage	Storage Description
#1	45.00'	21,635 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
45.00	3,597	0	0
46.00	4,453	4,025	4,025
47.00	5,366	4,910	8,935
48.00	6,336	5,851	14,786
49.00	7,362	6,849	21,635

Device	Routing	Invert	Outlet Devices
#1	Discarded	45.00'	<b>8.270 in/hr Exfiltration over Surface area</b> Phase-In= 0.01'
#2	Primary	48.20'	<b>35.0' long x 8.0' breadth Broad-Crested Rectangular Weir</b> Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.43 2.54 2.70 2.69 2.68 2.68 2.66 2.64 2.64 2.64 2.65 2.65 2.66 2.66 2.68 2.70 2.74

**Discarded OutFlow** Max=0.78 cfs @ 12.50 hrs HW=45.55' (Free Discharge)  
 ↑1=Exfiltration (Exfiltration Controls 0.78 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=45.00' (Free Discharge)  
 ↑2=Broad-Crested Rectangular Weir ( Controls 0.00 cfs)

**Summary for Pond P-2A: UIC #2**

Inflow Area = 18,417 sf, 90.63% Impervious, Inflow Depth = 2.24" for 2-Year event  
 Inflow = 1.14 cfs @ 12.09 hrs, Volume= 3,439 cf  
 Outflow = 0.48 cfs @ 12.31 hrs, Volume= 3,449 cf, Atten= 58%, Lag= 12.9 min  
 Discarded = 0.48 cfs @ 12.31 hrs, Volume= 3,449 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 47.02' @ 12.31 hrs Surf.Area= 2,352 sf Storage= 431 cf

Plug-Flow detention time= (not calculated: outflow precedes inflow)  
 Center-of-Mass det. time= 4.5 min ( 806.6 - 802.1 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	1,762 cf	<b>34.75'W x 67.70'L x 3.50'H Field A</b> 8,234 cf Overall - 2,894 cf Embedded = 5,339 cf x 33.0% Voids
#2A	47.00'	2,894 cf	<b>ADS_StormTech SC-740 +Cap</b> x 63 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 63 Chambers in 7 Rows
		4,656 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.48 cfs @ 12.31 hrs HW=47.02' (Free Discharge)  
 ↑1=Exfiltration (Exfiltration Controls 0.48 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)  
 ↑2=Sharp-Crested Rectangular Weir ( Controls 0.00 cfs)

**Summary for Pond P-2B: Isolator Row #2**

Inflow Area = 11,917 sf, 85.52% Impervious, Inflow Depth = 2.17" for 2-Year event  
 Inflow = 0.68 cfs @ 12.09 hrs, Volume= 2,158 cf  
 Outflow = 0.67 cfs @ 12.09 hrs, Volume= 1,778 cf, Atten= 1%, Lag= 0.2 min  
 Primary = 0.67 cfs @ 12.09 hrs, Volume= 1,778 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 2-Year Rainfall=3.30"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 40

Peak Elev= 49.36' @ 12.09 hrs Surf.Area= 245 sf Storage= 384 cf

Plug-Flow detention time= 106.3 min calculated for 1,778 cf (82% of inflow)  
Center-of-Mass det. time= 35.6 min ( 845.4 - 809.9 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap x 5</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=0.66 cfs @ 12.09 hrs HW=49.35' (Free Discharge)  
 ↖ **1=Sharp-Crested Rectangular Weir**(Weir Controls 0.66 cfs @ 1.05 fps)

**Summary for Pond P-3A: UIC #3**

Inflow Area = 15,324 sf, 100.00% Impervious, Inflow Depth = 2.77" for 2-Year event  
 Inflow = 1.10 cfs @ 12.09 hrs, Volume= 3,541 cf  
 Outflow = 0.42 cfs @ 12.33 hrs, Volume= 3,539 cf, Atten= 62%, Lag= 14.3 min  
 Discarded = 0.42 cfs @ 12.33 hrs, Volume= 3,539 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 47.09' @ 12.33 hrs Surf.Area= 2,031 sf Storage= 482 cf

Plug-Flow detention time= 6.0 min calculated for 3,539 cf (100% of inflow)  
 Center-of-Mass det. time= 5.6 min ( 790.6 - 785.0 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	1,527 cf	<b>30.00'W x 67.70'L x 3.50'H Field A</b> 7,108 cf Overall - 2,481 cf Embedded = 4,627 cf x 33.0% Voids
#2A	47.00'	2,481 cf	<b>ADS_StormTech SC-740 +Cap x 54</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 54 Chambers in 6 Rows
		4,008 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 2-Year Rainfall=3.30"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 41

**Discarded OutFlow** Max=0.42 cfs @ 12.33 hrs HW=47.09' (Free Discharge)

↑1=Exfiltration (Exfiltration Controls 0.42 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)

↑2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

**Summary for Pond P-3B: Isolator Row #3**

Inflow Area = 8,824 sf, 100.00% Impervious, Inflow Depth = 3.07" for 2-Year event  
 Inflow = 0.63 cfs @ 12.09 hrs, Volume= 2,255 cf  
 Outflow = 0.63 cfs @ 12.09 hrs, Volume= 1,880 cf, Atten= 1%, Lag= 0.2 min  
 Primary = 0.63 cfs @ 12.09 hrs, Volume= 1,880 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 49.35' @ 12.09 hrs Surf.Area= 245 sf Storage= 384 cf

Plug-Flow detention time= 123.5 min calculated for 1,880 cf (83% of inflow)  
 Center-of-Mass det. time= 55.1 min ( 810.8 - 755.8 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap x 5</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=0.61 cfs @ 12.09 hrs HW=49.35' (Free Discharge)

↑1=Sharp-Crested Rectangular Weir (Weir Controls 0.61 cfs @ 1.03 fps)

**Summary for Pond P-4A: UIC #4**

Inflow Area = 26,602 sf, 87.18% Impervious, Inflow Depth = 2.19" for 2-Year event  
 Inflow = 1.54 cfs @ 12.09 hrs, Volume= 4,845 cf  
 Outflow = 0.55 cfs @ 12.37 hrs, Volume= 4,845 cf, Atten= 65%, Lag= 16.8 min  
 Discarded = 0.55 cfs @ 12.37 hrs, Volume= 4,845 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 47.09' @ 12.37 hrs Surf.Area= 2,674 sf Storage= 629 cf

Plug-Flow detention time= 5.4 min calculated for 4,845 cf (100% of inflow)  
 Center-of-Mass det. time= 5.4 min ( 796.7 - 791.3 )

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 2-Year Rainfall=3.30"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 42

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	1,997 cf	<b>39.50'W x 67.70'L x 3.50'H Field A</b> 9,359 cf Overall - 3,308 cf Embedded = 6,051 cf x 33.0% Voids
#2A	47.00'	3,308 cf	<b>ADS_StormTech SC-740 +Cap x 72</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 72 Chambers in 8 Rows
		5,305 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.55 cfs @ 12.37 hrs HW=47.09' (Free Discharge)

↑**1=Exfiltration** (Exfiltration Controls 0.55 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)

↑**2=Sharp-Crested Rectangular Weir**( Controls 0.00 cfs)

**Summary for Pond P-4B: Isolator Row #4**

Inflow Area = 13,602 sf, 74.92% Impervious, Inflow Depth = 1.69" for 2-Year event  
 Inflow = 0.61 cfs @ 12.09 hrs, Volume= 1,917 cf  
 Outflow = 0.60 cfs @ 12.10 hrs, Volume= 1,523 cf, Atten= 0%, Lag= 0.2 min  
 Primary = 0.60 cfs @ 12.10 hrs, Volume= 1,523 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3

Peak Elev= 49.35' @ 12.10 hrs Surf.Area= 245 sf Storage= 384 cf

Plug-Flow detention time= 117.0 min calculated for 1,523 cf (79% of inflow)

Center-of-Mass det. time= 37.4 min ( 868.9 - 831.5 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap x 5</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=0.59 cfs @ 12.10 hrs HW=49.35' (Free Discharge)

↑**1=Sharp-Crested Rectangular Weir**(Weir Controls 0.59 cfs @ 1.02 fps)

## 2826 Post Road Phase II Modifications - Proposed

Type III 24-hr 2-Year Rainfall=3.30"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 43

### Summary for Pond P-5A: UIC #5

Inflow Area = 21,940 sf, 100.00% Impervious, Inflow Depth = 2.86" for 2-Year event  
Inflow = 1.57 cfs @ 12.09 hrs, Volume= 5,234 cf  
Outflow = 0.55 cfs @ 12.36 hrs, Volume= 5,235 cf, Atten= 65%, Lag= 16.2 min  
Discarded = 0.55 cfs @ 12.36 hrs, Volume= 5,235 cf  
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
Peak Elev= 47.15' @ 12.36 hrs Surf.Area= 2,681 sf Storage= 774 cf

Plug-Flow detention time= (not calculated: outflow precedes inflow)  
Center-of-Mass det. time= 6.7 min ( 782.3 - 775.6 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	2,004 cf	<b>44.25'W x 60.58'L x 3.50'H Field A</b> 9,382 cf Overall - 3,308 cf Embedded = 6,074 cf x 33.0% Voids
#2A	47.00'	3,308 cf	<b>ADS_StormTech SC-740 +Cap</b> x 72 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 72 Chambers in 9 Rows
		5,312 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.55 cfs @ 12.36 hrs HW=47.15' (Free Discharge)  
↑1=Exfiltration (Exfiltration Controls 0.55 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)  
↑2=Sharp-Crested Rectangular Weir ( Controls 0.00 cfs)

### Summary for Pond P-5B: Isolator Row #5

Inflow Area = 8,940 sf, 100.00% Impervious, Inflow Depth = 3.07" for 2-Year event  
Inflow = 0.64 cfs @ 12.09 hrs, Volume= 2,285 cf  
Outflow = 0.64 cfs @ 12.09 hrs, Volume= 1,911 cf, Atten= 1%, Lag= 0.2 min  
Primary = 0.64 cfs @ 12.09 hrs, Volume= 1,911 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
Peak Elev= 49.35' @ 12.09 hrs Surf.Area= 245 sf Storage= 384 cf

Plug-Flow detention time= 122.1 min calculated for 1,911 cf (84% of inflow)  
Center-of-Mass det. time= 54.4 min ( 810.2 - 755.8 )



**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr 2-Year Rainfall=3.30"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 44

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap x 5</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=0.62 cfs @ 12.09 hrs HW=49.35' (Free Discharge)

↑1=Sharp-Crested Rectangular Weir (Weir Controls 0.62 cfs @ 1.03 fps)

**Summary for Pond P-6A: UIC #6**

Inflow Area = 49,136 sf, 88.32% Impervious, Inflow Depth = 2.04" for 2-Year event  
 Inflow = 2.52 cfs @ 12.12 hrs, Volume= 8,361 cf  
 Outflow = 1.02 cfs @ 12.37 hrs, Volume= 8,363 cf, Atten= 59%, Lag= 15.1 min  
 Discarded = 1.02 cfs @ 12.37 hrs, Volume= 8,363 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 45.51' @ 12.37 hrs Surf.Area= 5,074 sf Storage= 866 cf

Plug-Flow detention time= (not calculated: outflow precedes inflow)  
 Center-of-Mass det. time= 3.9 min ( 807.9 - 804.0 )

Volume	Invert	Avail.Storage	Storage Description
#1A	45.00'	3,738 cf	<b>34.75'W x 146.02'L x 3.50'H Field A</b> 17,759 cf Overall - 6,432 cf Embedded = 11,328 cf x 33.0% Voids
#2A	45.50'	6,432 cf	<b>ADS_StormTech SC-740 +Cap x 140</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 140 Chambers in 7 Rows
		10,170 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	45.00'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	48.00'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=1.02 cfs @ 12.37 hrs HW=45.51' (Free Discharge)

↑1=Exfiltration (Exfiltration Controls 1.02 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=45.00' (Free Discharge)

↑2=Sharp-Crested Rectangular Weir ( Controls 0.00 cfs)

# 2826 Post Road Phase II Modifications - Proposed

Type III 24-hr 2-Year Rainfall=3.30"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 45

## Summary for Pond P-6B: Isolator Row #6

Inflow Area = 29,236 sf, 80.37% Impervious, Inflow Depth = 1.92" for 2-Year event  
 Inflow = 1.48 cfs @ 12.09 hrs, Volume= 4,683 cf  
 Outflow = 1.23 cfs @ 12.15 hrs, Volume= 3,274 cf, Atten= 17%, Lag= 3.3 min  
 Primary = 1.23 cfs @ 12.15 hrs, Volume= 3,274 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 47.86' @ 12.15 hrs Surf.Area= 913 sf Storage= 1,476 cf

Plug-Flow detention time= 152.4 min calculated for 3,269 cf (70% of inflow)  
 Center-of-Mass det. time= 57.7 min ( 878.9 - 821.2 )

Volume	Invert	Avail.Storage	Storage Description
#1A	45.00'	751 cf	<b>6.25'W x 146.02'L x 3.50'H Field A</b> 3,194 cf Overall - 919 cf Embedded = 2,275 cf x 33.0% Voids
#2A	45.50'	919 cf	<b>ADS_StormTech SC-740 +Cap x 20 Inside #1</b> Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		1,670 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	47.75'	<b>5.0' long Sharp-Crested Rectangular Weir X 2.00</b> 2 End Contraction(s)

**Primary OutFlow** Max=1.21 cfs @ 12.15 hrs HW=47.86' (Free Discharge)  
 ↑#1=Sharp-Crested Rectangular Weir(Weir Controls 1.21 cfs @ 1.09 fps)

## Summary for Link DP-1: Existing Drainage System - Phase 1

Inflow Area = 554,769 sf, 78.45% Impervious, Inflow Depth = 0.00" for 2-Year event  
 Inflow = 0.00 cfs @ 20.76 hrs, Volume= 34 cf  
 Primary = 0.00 cfs @ 20.76 hrs, Volume= 34 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs

## Summary for Link DP-2: Post Road

Inflow Area = 4,789 sf, 61.89% Impervious, Inflow Depth = 1.92" for 2-Year event  
 Inflow = 0.24 cfs @ 12.09 hrs, Volume= 767 cf  
 Primary = 0.24 cfs @ 12.09 hrs, Volume= 767 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs

**2826 Post Road Phase II Modifications - Proposed**    *Type III 24-hr 10-Year Rainfall=4.80"*

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 46

Time span=0.00-28.00 hrs, dt=0.05 hrs, 561 points  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

**SubcatchmentPR-1A: Subwatershed 1A** - Runoff Area=9,000 sf 100.00% Impervious Runoff Depth=4.56"  
Tc=6.0 min CN=98 Runoff=0.95 cfs 3,423 cf

**SubcatchmentPR-1B: Subwatershed 1B** - Runoff Area=30,994 sf 75.91% Impervious Runoff Depth=3.09"  
Tc=6.0 min CN=84 Runoff=2.51 cfs 7,976 cf

**SubcatchmentPR-1D: Bldg 3 & 5-12 and** Runoff Area=286,475 sf 80.60% Impervious Runoff Depth=3.48"  
Tc=6.0 min CN=88 Runoff=25.69 cfs 83,061 cf

**SubcatchmentPR-1E: Portion of Bldg 12 &** Runoff Area=76,715 sf 66.84% Impervious Runoff Depth=2.72"  
Tc=6.0 min CN=80 Runoff=5.50 cfs 17,383 cf

**SubcatchmentPR-1F: Undetained Area** Runoff Area=20,166 sf 0.00% Impervious Runoff Depth=0.26"  
Tc=6.0 min CN=42 Runoff=0.04 cfs 440 cf

**SubcatchmentPR-2: Area Discharging to** Runoff Area=4,789 sf 61.89% Impervious Runoff Depth=3.28"  
Tc=6.0 min CN=86 Runoff=0.41 cfs 1,309 cf

**SubcatchmentPR-2A: Subwatershed 2A** - Runoff Area=6,500 sf 100.00% Impervious Runoff Depth=4.56"  
Tc=6.0 min CN=98 Runoff=0.68 cfs 2,472 cf

**SubcatchmentPR-2B: Subwatershed 2B** - Runoff Area=11,917 sf 85.52% Impervious Runoff Depth=3.58"  
Tc=6.0 min CN=89 Runoff=1.09 cfs 3,556 cf

**SubcatchmentPR-3A: Subwatershed 3A** - Runoff Area=6,500 sf 100.00% Impervious Runoff Depth=4.56"  
Tc=6.0 min CN=98 Runoff=0.68 cfs 2,472 cf

**SubcatchmentPR-3B: Subwatershed 3B** - Runoff Area=8,824 sf 100.00% Impervious Runoff Depth=4.56"  
Tc=6.0 min CN=98 Runoff=0.93 cfs 3,356 cf

**SubcatchmentPR-4A: Subwatershed 4A** - Runoff Area=13,000 sf 100.00% Impervious Runoff Depth=4.56"  
Tc=6.0 min CN=98 Runoff=1.37 cfs 4,944 cf

**SubcatchmentPR-4B: Subwatershed 4B** - Runoff Area=13,602 sf 74.92% Impervious Runoff Depth=2.99"  
Tc=6.0 min CN=83 Runoff=1.07 cfs 3,393 cf

**SubcatchmentPR-5A: Subwatershed 5A** - Runoff Area=13,000 sf 100.00% Impervious Runoff Depth=4.56"  
Tc=6.0 min CN=98 Runoff=1.37 cfs 4,944 cf

**SubcatchmentPR-5B: Subwatershed 5B** - Runoff Area=8,940 sf 100.00% Impervious Runoff Depth=4.56"  
Tc=6.0 min CN=98 Runoff=0.94 cfs 3,400 cf

**SubcatchmentPR-6A: Subwatershed 6A** - Runoff Area=19,900 sf 100.00% Impervious Runoff Depth=4.56"  
Tc=6.0 min CN=98 Runoff=2.09 cfs 7,568 cf

**SubcatchmentPR-6B: Subwatershed 6B** - Runoff Area=29,236 sf 80.37% Impervious Runoff Depth=3.28"  
Tc=6.0 min CN=86 Runoff=2.50 cfs 7,993 cf

**2826 Post Road Phase II Modifications - Proposed**    *Type III 24-hr 10-Year Rainfall=4.80"*

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 47

<b>Pond P-1A: UIC #1</b>	Peak Elev=47.50' Storage=2,357 cf Inflow=3.44 cfs 10,673 cf Discarded=0.90 cfs 10,665 cf Primary=0.00 cfs 0 cf Outflow=0.90 cfs 10,665 cf
<b>Pond P-1B: Isolator Row #1</b>	Peak Elev=49.43' Storage=760 cf Inflow=2.51 cfs 7,976 cf Outflow=2.50 cfs 7,251 cf
<b>Pond P-1D: Underground Infiltration</b>	Peak Elev=46.10' Storage=20,631 cf Inflow=25.69 cfs 83,061 cf Discarded=5.36 cfs 80,935 cf Primary=1.03 cfs 2,126 cf Outflow=6.39 cfs 83,061 cf
<b>Pond P-1E: Infiltration Basin</b>	Peak Elev=46.31' Storage=5,440 cf Inflow=5.50 cfs 17,383 cf Discarded=0.91 cfs 17,383 cf Primary=0.00 cfs 0 cf Outflow=0.91 cfs 17,383 cf
<b>Pond P-2A: UIC #2</b>	Peak Elev=47.40' Storage=1,132 cf Inflow=1.77 cfs 5,657 cf Discarded=0.49 cfs 5,664 cf Primary=0.00 cfs 0 cf Outflow=0.49 cfs 5,664 cf
<b>Pond P-2B: Isolator Row #2</b>	Peak Elev=49.40' Storage=388 cf Inflow=1.09 cfs 3,556 cf Outflow=1.09 cfs 3,185 cf
<b>Pond P-3A: UIC #3</b>	Peak Elev=47.46' Storage=1,081 cf Inflow=1.61 cfs 5,455 cf Discarded=0.43 cfs 5,457 cf Primary=0.00 cfs 0 cf Outflow=0.43 cfs 5,457 cf
<b>Pond P-3B: Isolator Row #3</b>	Peak Elev=49.38' Storage=386 cf Inflow=0.93 cfs 3,356 cf Outflow=0.92 cfs 2,983 cf
<b>Pond P-4A: UIC #4</b>	Peak Elev=47.65' Storage=1,826 cf Inflow=2.43 cfs 7,961 cf Discarded=0.57 cfs 7,971 cf Primary=0.00 cfs 0 cf Outflow=0.57 cfs 7,971 cf
<b>Pond P-4B: Isolator Row #4</b>	Peak Elev=49.39' Storage=388 cf Inflow=1.07 cfs 3,393 cf Outflow=1.07 cfs 3,017 cf
<b>Pond P-5A: UIC #5</b>	Peak Elev=47.58' Storage=1,675 cf Inflow=2.30 cfs 7,970 cf Discarded=0.57 cfs 7,966 cf Primary=0.00 cfs 0 cf Outflow=0.57 cfs 7,966 cf
<b>Pond P-5B: Isolator Row #5</b>	Peak Elev=49.38' Storage=387 cf Inflow=0.94 cfs 3,400 cf Outflow=0.94 cfs 3,027 cf
<b>Pond P-6A: UIC #6</b>	Peak Elev=46.11' Storage=3,340 cf Inflow=4.56 cfs 14,095 cf Discarded=1.07 cfs 14,093 cf Primary=0.00 cfs 0 cf Outflow=1.07 cfs 14,093 cf
<b>Pond P-6B: Isolator Row #6</b>	Peak Elev=47.93' Storage=1,497 cf Inflow=2.50 cfs 7,993 cf Outflow=2.47 cfs 6,528 cf
<b>Link DP-1: Existing Drainage System - Phase 1</b>	Inflow=1.07 cfs 2,566 cf Primary=1.07 cfs 2,566 cf
<b>Link DP-2: Post Road</b>	Inflow=0.41 cfs 1,309 cf Primary=0.41 cfs 1,309 cf

**Total Runoff Area = 559,558 sf    Runoff Volume = 157,689 cf    Average Runoff Depth = 3.38"**  
**21.69% Pervious = 121,354 sf    78.31% Impervious = 438,205 sf**

**Summary for Subcatchment PR-1A: Subwatershed 1A - Roof A**

Runoff = 0.95 cfs @ 12.09 hrs, Volume= 3,423 cf, Depth= 4.56"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 10-Year Rainfall=4.80"

Area (sf)	CN	Description
9,000	98	Roofs, HSG A
9,000	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-1B: Subwatershed 1B - Parking Lot**

Runoff = 2.51 cfs @ 12.09 hrs, Volume= 7,976 cf, Depth= 3.09"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 10-Year Rainfall=4.80"

Area (sf)	CN	Description
* 23,528	98	Paved parking and sidewalks, HSG A
7,466	39	>75% Grass cover, Good, HSG A
30,994	84	Weighted Average
7,466	39	24.09% Pervious Area
23,528	98	75.91% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-1D: Bldg 3 & 5-12 and Pvt**

Runoff = 25.69 cfs @ 12.09 hrs, Volume= 83,061 cf, Depth= 3.48"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 10-Year Rainfall=4.80"

**2826 Post Road Phase II Modifications - Proposed**    *Type III 24-hr 10-Year Rainfall=4.80"*

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 49

Area (sf)	CN	Description
8,805	32	Woods/grass comb., Good, HSG A
2,001	72	Dirt roads, HSG A
28,102	39	>75% Grass cover, Good, HSG A
113,211	98	Roofs, HSG A
113,868	98	Paved parking, HSG A
15,161	68	<50% Grass cover, Poor, HSG A
1,158	30	Woods, Good, HSG A
1,705	98	Roofs, HSG B
2,111	98	Paved parking, HSG B
353	61	>75% Grass cover, Good, HSG B
286,475	88	Weighted Average
55,580	47	19.40% Pervious Area
230,895	98	80.60% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-1E: Portion of Bldg 12 & Pvt Draining to Basin**

Runoff = 5.50 cfs @ 12.09 hrs, Volume= 17,383 cf, Depth= 2.72"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 10-Year Rainfall=4.80"

Area (sf)	CN	Description
14,109	39	>75% Grass cover, Good, HSG A
21,676	98	Roofs, HSG A
29,598	98	Paved parking, HSG A
3,129	72	Dirt roads, HSG A
1,746	68	<50% Grass cover, Poor, HSG A
2,283	36	Woods, Fair, HSG A
2,244	30	Woods, Good, HSG A
1,931	32	Woods/grass comb., Good, HSG A
76,715	80	Weighted Average
25,442	43	33.16% Pervious Area
51,274	98	66.84% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-1F: Undetained Area**

Runoff = 0.04 cfs @ 12.41 hrs, Volume= 440 cf, Depth= 0.26"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 10-Year Rainfall=4.80"

**2826 Post Road Phase II Modifications - Proposed**    *Type III 24-hr 10-Year Rainfall=4.80"*

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 50

Area (sf)	CN	Description
5,393	39	>75% Grass cover, Good, HSG A
10,624	36	Woods, Fair, HSG A
183	61	>75% Grass cover, Good, HSG B
3,966	60	Woods, Fair, HSG B
20,166	42	Weighted Average
20,166	42	100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-2: Area Discharging to Post Road**

Runoff = 0.41 cfs @ 12.09 hrs, Volume= 1,309 cf, Depth= 3.28"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10-Year Rainfall=4.80"

Area (sf)	CN	Description
829	98	Paved parking, HSG A
572	39	>75% Grass cover, Good, HSG A
2,135	98	Paved parking, HSG D
1,253	80	>75% Grass cover, Good, HSG D
4,789	86	Weighted Average
1,825	67	38.11% Pervious Area
2,964	98	61.89% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-2A: Subwatershed 2A - Roof**

Runoff = 0.68 cfs @ 12.09 hrs, Volume= 2,472 cf, Depth= 4.56"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10-Year Rainfall=4.80"

Area (sf)	CN	Description
6,500	98	Roofs, HSG A
6,500	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-2B: Subwatershed 2B - Parking Lot**

Runoff = 1.09 cfs @ 12.09 hrs, Volume= 3,556 cf, Depth= 3.58"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 10-Year Rainfall=4.80"

	Area (sf)	CN	Description
*	10,191	98	Paved parking and sidewalks, HSG A
	1,726	39	>75% Grass cover, Good, HSG A
	11,917	89	Weighted Average
	1,726	39	14.48% Pervious Area
	10,191	98	85.52% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-3A: Subwatershed 3A - Roof**

Runoff = 0.68 cfs @ 12.09 hrs, Volume= 2,472 cf, Depth= 4.56"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 10-Year Rainfall=4.80"

	Area (sf)	CN	Description
	6,500	98	Roofs, HSG A
	6,500	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-3B: Subwatershed 3B - Parking Lot**

Runoff = 0.93 cfs @ 12.09 hrs, Volume= 3,356 cf, Depth= 4.56"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 10-Year Rainfall=4.80"

	Area (sf)	CN	Description
*	8,824	98	Paved parking and sidewalks, HSG A
	8,824	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>



**Summary for Subcatchment PR-4A: Subwatershed 4A - Roof**

Runoff = 1.37 cfs @ 12.09 hrs, Volume= 4,944 cf, Depth= 4.56"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 10-Year Rainfall=4.80"

Area (sf)	CN	Description
13,000	98	Roofs, HSG A
13,000	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-4B: Subwatershed 4B - Parking Lot**

Runoff = 1.07 cfs @ 12.09 hrs, Volume= 3,393 cf, Depth= 2.99"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 10-Year Rainfall=4.80"

Area (sf)	CN	Description
* 10,191	98	Paved parking and sidewalks, HSG A
3,411	39	>75% Grass cover, Good, HSG A
13,602	83	Weighted Average
3,411	39	25.08% Pervious Area
10,191	98	74.92% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-5A: Subwatershed 5A - Roof**

Runoff = 1.37 cfs @ 12.09 hrs, Volume= 4,944 cf, Depth= 4.56"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 10-Year Rainfall=4.80"

Area (sf)	CN	Description
13,000	98	Roofs, HSG A
13,000	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-5B: Subwatershed 5B - Parking Lot**

Runoff = 0.94 cfs @ 12.09 hrs, Volume= 3,400 cf, Depth= 4.56"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 10-Year Rainfall=4.80"

Area (sf)	CN	Description
* 8,940	98	Paved parking and sidewalks, HSG A
8,940	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-6A: Subwatershed 6A - Roof**

Runoff = 2.09 cfs @ 12.09 hrs, Volume= 7,568 cf, Depth= 4.56"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 10-Year Rainfall=4.80"

Area (sf)	CN	Description
19,900	98	Roofs, HSG A
19,900	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-6B: Subwatershed 6B - Parking Lot**

Runoff = 2.50 cfs @ 12.09 hrs, Volume= 7,993 cf, Depth= 3.28"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 10-Year Rainfall=4.80"

Area (sf)	CN	Description
* 23,498	98	Paved parking and sidewalks, HSG A
5,738	39	>75% Grass cover, Good, HSG A
29,236	86	Weighted Average
5,738	39	19.63% Pervious Area
23,498	98	80.37% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Pond P-1A: UIC #1**

Inflow Area =            39,994 sf, 81.33% Impervious, Inflow Depth = 3.20" for 10-Year event  
 Inflow        =        3.44 cfs @ 12.09 hrs, Volume=            10,673 cf  
 Outflow      =        0.90 cfs @ 12.47 hrs, Volume=        10,665 cf, Atten= 74%, Lag= 22.6 min  
 Discarded =        0.90 cfs @ 12.47 hrs, Volume=        10,665 cf  
 Primary     =        0.00 cfs @ 0.00 hrs, Volume=            0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 47.50' @ 12.47 hrs Surf.Area= 4,161 sf Storage= 2,357 cf

Plug-Flow detention time= 15.2 min calculated for 10,665 cf (100% of inflow)  
 Center-of-Mass det. time= 14.6 min ( 820.8 - 806.1 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	3,108 cf	<b>20.50'W x 202.98'L x 3.50'H Field A</b> 14,564 cf Overall - 5,145 cf Embedded = 9,418 cf x 33.0% Voids
#2A	47.00'	5,145 cf	<b>ADS_StormTech SC-740 +Cap</b> x 112 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 112 Chambers in 4 Rows
		8,253 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.90 cfs @ 12.47 hrs HW=47.50' (Free Discharge)  
 ↑1=**Exfiltration** (Exfiltration Controls 0.90 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)  
 ↑2=**Sharp-Crested Rectangular Weir** ( Controls 0.00 cfs)

**Summary for Pond P-1B: Isolator Row #1**

Inflow Area =            30,994 sf, 75.91% Impervious, Inflow Depth = 3.09" for 10-Year event  
 Inflow        =        2.51 cfs @ 12.09 hrs, Volume=            7,976 cf  
 Outflow      =        2.50 cfs @ 12.09 hrs, Volume=        7,251 cf, Atten= 0%, Lag= 0.1 min  
 Primary     =        2.50 cfs @ 12.09 hrs, Volume=            7,251 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 49.43' @ 12.09 hrs Surf.Area= 468 sf Storage= 760 cf

Plug-Flow detention time= 66.1 min calculated for 7,251 cf (91% of inflow)  
 Center-of-Mass det. time= 21.1 min ( 833.3 - 812.2 )

**2826 Post Road Phase II Modifications - Proposed**    *Type III 24-hr 10-Year Rainfall=4.80"*

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 55

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	388 cf	<b>6.25'W x 74.82'L x 3.50'H Field A</b> 1,637 cf Overall - 459 cf Embedded = 1,177 cf x 33.0% Voids
#2A	47.00'	459 cf	<b>ADS_StormTech SC-740 +Cap</b> x 10 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		848 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>5.0' long Sharp-Crested Rectangular Weir X 2.00</b> 2 End Contraction(s)

**Primary OutFlow** Max=2.45 cfs @ 12.09 hrs HW=49.43' (Free Discharge)

↳ **1=Sharp-Crested Rectangular Weir** (Weir Controls 2.45 cfs @ 1.38 fps)

**Summary for Pond P-1D: Underground Infiltration**

Inflow Area = 286,475 sf, 80.60% Impervious, Inflow Depth = 3.48" for 10-Year event  
 Inflow = 25.69 cfs @ 12.09 hrs, Volume= 83,061 cf  
 Outflow = 6.39 cfs @ 12.48 hrs, Volume= 83,061 cf, Atten= 75%, Lag= 23.1 min  
 Discarded = 5.36 cfs @ 12.48 hrs, Volume= 80,935 cf  
 Primary = 1.03 cfs @ 12.48 hrs, Volume= 2,126 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Peak Elev= 46.10' @ 12.48 hrs Surf.Area= 23,713 sf Storage= 20,631 cf

Plug-Flow detention time= 21.7 min calculated for 82,913 cf (100% of inflow)  
 Center-of-Mass det. time= 21.7 min ( 821.1 - 799.4 )

**2826 Post Road Phase II Modifications - Proposed**      *Type III 24-hr 10-Year Rainfall=4.80"*

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 56

Volume	Invert	Avail.Storage	Storage Description
#1	44.70'	18,217 cf	<b>15.75'W x 1,505.60'L x 3.50'H Crushed Stone</b> 82,996 cf Overall - 27,794 cf Embedded = 55,202 cf x 33.0% Voids
#2	45.20'	1,103 cf	<b>P-1D-A</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 24 Chambers in 3 Rows
#3	45.20'	1,929 cf	<b>P-1D-B</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 42 Chambers in 3 Rows
#4	45.20'	1,240 cf	<b>P-1D-C</b> x 27 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 27 Chambers in 3 Rows
#5	45.20'	965 cf	<b>P-1D-D</b> x 21 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 21 Chambers in 3 Rows
#6	45.20'	1,654 cf	<b>P-1D-E</b> x 36 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 36 Chambers in 3 Rows
#7	45.20'	1,654 cf	<b>P-1D-F</b> x 36 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 36 Chambers in 3 Rows
#8	45.20'	1,103 cf	<b>P-1D-G</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 24 Chambers in 3 Rows
#9	45.20'	1,286 cf	<b>P-1D-H</b> x 28 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 28 Chambers in 2 Rows
#10	45.20'	184 cf	<b>P-1D-H</b> x 4 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#11	45.20'	413 cf	<b>P-1D-H</b> x 9 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#12	45.20'	2,067 cf	<b>P-1D-I</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 45 Chambers in 3 Rows
#13	45.20'	1,929 cf	<b>P-1D-J</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 42 Chambers in 3 Rows
#14	45.20'	2,067 cf	<b>P-1D-K</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap

**2826 Post Road Phase II Modifications - Proposed**      *Type III 24-hr 10-Year Rainfall=4.80"*

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 57

#15	45.20'	1,929 cf	45 Chambers in 3 Rows <b>P-1D-L</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#16	45.20'	2,067 cf	42 Chambers in 3 Rows <b>P-1D-M</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#17	45.20'	1,929 cf	45 Chambers in 3 Rows <b>P-1D-N</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#18	45.20'	2,067 cf	42 Chambers in 3 Rows <b>P-1D-O</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#19	45.20'	1,103 cf	45 Chambers in 3 Rows <b>P-1D-P</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#20	45.20'	1,103 cf	24 Chambers in 3 Rows <b>P-1D-Q</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#21	46.25'	134 cf	<b>18.0" Round Pipe CB5-DMH1</b> -Impervious L= 76.0' S= 0.0031 '/'
#22	45.70'	205 cf	<b>18.0" Round Pipe CB5-CB6</b> -Impervious L= 116.0' S= 0.0025 '/'
#23	46.10'	93 cf	<b>12.0" Round Pipe CB6-CB7</b> -Impervious L= 118.0' S= 0.0033 '/'
#24	46.50'	101 cf	<b>12.0" Round Pipe CB33-CB40</b> -Impervious L= 128.0' S= 0.0098 '/'
#25	46.10'	83 cf	<b>12.0" Round Pipe CB8-CB9</b> -Impervious L= 106.0' S= 0.0036 '/'
#26	45.70'	187 cf	<b>18.0" Round Pipe CB9-CB10</b> -Impervious L= 106.0' S= 0.0027 '/'
#27	46.20'	91 cf	<b>12.0" Round Pipe CB10-CB11</b> -Impervious L= 116.0' S= 0.0025 '/'
#28	45.30'	540 cf	<b>24.0" Round 24" Header Pipe</b> -Impervious L= 172.0'
#29	45.30'	855 cf	<b>4.00'D x 4.00'H CBs</b> x 17 -Impervious
#30	46.00'	50 cf	<b>4.00'D x 4.00'H CB-6</b> -Impervious
#31	46.50'	50 cf	<b>4.00'D x 4.00'H CB-7</b> -Impervious
#32	47.80'	50 cf	<b>4.00'D x 4.00'H CB-40</b> -Impervious
#33	46.50'	50 cf	<b>4.00'D x 4.00'H CB-8</b> -Impervious
#34	46.00'	50 cf	<b>4.00'D x 4.00'H CB-9</b> -Impervious
#35	46.50'	50 cf	<b>4.00'D x 4.00'H CB-11</b> -Impervious
#36	46.50'	50 cf	<b>4.00'D x 4.00'H CB-33</b> -Impervious
		48,651 cf	Total Available Storage

Device	Routing	Invert	Outlet Devices
#1	Discarded	44.70'	<b>8.270 in/hr Exfiltration over Wetted area</b> Phase-In= 0.01'
#2	Device 4	45.70'	<b>15.0" W x 21.0" H Vert. Orifice/Grate</b> C= 0.600
#3	Device 4	48.10'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)
#4	Primary	31.40'	<b>24.0" Round Culvert</b> L= 25.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 31.40' / 31.00' S= 0.0160 '/ Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 3.14 sf

**Discarded OutFlow** Max=5.36 cfs @ 12.48 hrs HW=46.10' (Free Discharge)  
 ↳ **1=Exfiltration** (Exfiltration Controls 5.36 cfs)

**Primary OutFlow** Max=1.03 cfs @ 12.48 hrs HW=46.10' (Free Discharge)  
 ↳ **4=Culvert** (Passes 1.03 cfs of 44.21 cfs potential flow)  
 ↳ **2=Orifice/Grate** (Orifice Controls 1.03 cfs @ 2.04 fps)  
 ↳ **3=Sharp-Crested Rectangular Weir** ( Controls 0.00 cfs)

**Summary for Pond P-1E: Infiltration Basin**

Inflow Area = 76,715 sf, 66.84% Impervious, Inflow Depth = 2.72" for 10-Year event  
 Inflow = 5.50 cfs @ 12.09 hrs, Volume= 17,383 cf  
 Outflow = 0.91 cfs @ 12.60 hrs, Volume= 17,383 cf, Atten= 84%, Lag= 30.2 min  
 Discarded = 0.91 cfs @ 12.60 hrs, Volume= 17,383 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Peak Elev= 46.31' @ 12.60 hrs Surf.Area= 4,734 sf Storage= 5,440 cf

Plug-Flow detention time= 45.3 min calculated for 17,352 cf (100% of inflow)  
 Center-of-Mass det. time= 45.2 min ( 868.8 - 823.6 )

Volume	Invert	Avail.Storage	Storage Description
#1	45.00'	21,635 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
45.00	3,597	0	0
46.00	4,453	4,025	4,025
47.00	5,366	4,910	8,935
48.00	6,336	5,851	14,786
49.00	7,362	6,849	21,635

Device	Routing	Invert	Outlet Devices
#1	Discarded	45.00'	<b>8.270 in/hr Exfiltration over Surface area</b> Phase-In= 0.01'
#2	Primary	48.20'	<b>35.0' long x 8.0' breadth Broad-Crested Rectangular Weir</b> Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.43 2.54 2.70 2.69 2.68 2.68 2.66 2.64 2.64 2.64 2.65 2.65 2.66 2.66 2.68 2.70 2.74

**Discarded OutFlow** Max=0.91 cfs @ 12.60 hrs HW=46.31' (Free Discharge)  
 ↑1=Exfiltration (Exfiltration Controls 0.91 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=45.00' (Free Discharge)  
 ↑2=Broad-Crested Rectangular Weir ( Controls 0.00 cfs)

**Summary for Pond P-2A: UIC #2**

Inflow Area =            18,417 sf, 90.63% Impervious, Inflow Depth = 3.69" for 10-Year event  
 Inflow        =        1.77 cfs @ 12.09 hrs, Volume=            5,657 cf  
 Outflow       =        0.49 cfs @ 12.44 hrs, Volume=            5,664 cf, Atten= 72%, Lag= 21.0 min  
 Discarded    =        0.49 cfs @ 12.44 hrs, Volume=            5,664 cf  
 Primary       =        0.00 cfs @ 0.00 hrs, Volume=            0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 47.40' @ 12.44 hrs Surf.Area= 2,352 sf Storage= 1,132 cf

Plug-Flow detention time= (not calculated: outflow precedes inflow)  
 Center-of-Mass det. time= 12.0 min ( 802.6 - 790.6 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	1,762 cf	<b>34.75'W x 67.70'L x 3.50'H Field A</b> 8,234 cf Overall - 2,894 cf Embedded = 5,339 cf x 33.0% Voids
#2A	47.00'	2,894 cf	<b>ADS_StormTech SC-740 +Cap</b> x 63 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 63 Chambers in 7 Rows
		4,656 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.49 cfs @ 12.44 hrs HW=47.40' (Free Discharge)  
 ↑1=Exfiltration (Exfiltration Controls 0.49 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)  
 ↑2=Sharp-Crested Rectangular Weir ( Controls 0.00 cfs)

**Summary for Pond P-2B: Isolator Row #2**

Inflow Area =            11,917 sf, 85.52% Impervious, Inflow Depth = 3.58" for 10-Year event  
 Inflow        =        1.09 cfs @ 12.09 hrs, Volume=            3,556 cf  
 Outflow       =        1.09 cfs @ 12.09 hrs, Volume=            3,185 cf, Atten= 0%, Lag= 0.1 min  
 Primary       =        1.09 cfs @ 12.09 hrs, Volume=            3,185 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3



Peak Elev= 49.40' @ 12.09 hrs    Surf.Area= 245 sf    Storage= 388 cf

Plug-Flow detention time= 76.5 min calculated for 3,179 cf (89% of inflow)  
 Center-of-Mass det. time= 27.3 min ( 823.1 - 795.8 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap</b> x 5 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=1.06 cfs @ 12.09 hrs HW=49.39' (Free Discharge)  
 ↑**1=Sharp-Crested Rectangular Weir**(Weir Controls 1.06 cfs @ 1.24 fps)

### Summary for Pond P-3A: UIC #3

Inflow Area = 15,324 sf, 100.00% Impervious, Inflow Depth = 4.27" for 10-Year event  
 Inflow = 1.61 cfs @ 12.09 hrs, Volume= 5,455 cf  
 Outflow = 0.43 cfs @ 12.44 hrs, Volume= 5,457 cf, Atten= 73%, Lag= 21.2 min  
 Discarded = 0.43 cfs @ 12.44 hrs, Volume= 5,457 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 47.46' @ 12.44 hrs    Surf.Area= 2,031 sf    Storage= 1,081 cf

Plug-Flow detention time= (not calculated: outflow precedes inflow)  
 Center-of-Mass det. time= 12.5 min ( 785.8 - 773.2 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	1,527 cf	<b>30.00'W x 67.70'L x 3.50'H Field A</b> 7,108 cf Overall - 2,481 cf Embedded = 4,627 cf x 33.0% Voids
#2A	47.00'	2,481 cf	<b>ADS_StormTech SC-740 +Cap</b> x 54 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 54 Chambers in 6 Rows
		4,008 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.43 cfs @ 12.44 hrs HW=47.46' (Free Discharge)  
 ↑1=Exfiltration (Exfiltration Controls 0.43 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)  
 ↑2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

**Summary for Pond P-3B: Isolator Row #3**

Inflow Area = 8,824 sf, 100.00% Impervious, Inflow Depth = 4.56" for 10-Year event  
 Inflow = 0.93 cfs @ 12.09 hrs, Volume= 3,356 cf  
 Outflow = 0.92 cfs @ 12.09 hrs, Volume= 2,983 cf, Atten= 0%, Lag= 0.1 min  
 Primary = 0.92 cfs @ 12.09 hrs, Volume= 2,983 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 49.38' @ 12.09 hrs Surf.Area= 245 sf Storage= 386 cf

Plug-Flow detention time= 97.5 min calculated for 2,978 cf (89% of inflow)  
 Center-of-Mass det. time= 44.9 min ( 793.6 - 748.7 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap x 5</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=0.90 cfs @ 12.09 hrs HW=49.38' (Free Discharge)  
 ↑1=Sharp-Crested Rectangular Weir (Weir Controls 0.90 cfs @ 1.17 fps)

**Summary for Pond P-4A: UIC #4**

Inflow Area = 26,602 sf, 87.18% Impervious, Inflow Depth = 3.59" for 10-Year event  
 Inflow = 2.43 cfs @ 12.09 hrs, Volume= 7,961 cf  
 Outflow = 0.57 cfs @ 12.49 hrs, Volume= 7,971 cf, Atten= 77%, Lag= 24.0 min  
 Discarded = 0.57 cfs @ 12.49 hrs, Volume= 7,971 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 47.65' @ 12.49 hrs Surf.Area= 2,674 sf Storage= 1,826 cf

Plug-Flow detention time= (not calculated: outflow precedes inflow)  
 Center-of-Mass det. time= 17.5 min ( 800.4 - 782.9 )

**2826 Post Road Phase II Modifications - Proposed** Type III 24-hr 10-Year Rainfall=4.80"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 62

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	1,997 cf	<b>39.50'W x 67.70'L x 3.50'H Field A</b> 9,359 cf Overall - 3,308 cf Embedded = 6,051 cf x 33.0% Voids
#2A	47.00'	3,308 cf	<b>ADS_StormTech SC-740 +Cap x 72</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 72 Chambers in 8 Rows
		5,305 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.57 cfs @ 12.49 hrs HW=47.65' (Free Discharge)

↑**1=Exfiltration** (Exfiltration Controls 0.57 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)

↑**2=Sharp-Crested Rectangular Weir**( Controls 0.00 cfs)

**Summary for Pond P-4B: Isolator Row #4**

Inflow Area = 13,602 sf, 74.92% Impervious, Inflow Depth = 2.99" for 10-Year event  
 Inflow = 1.07 cfs @ 12.09 hrs, Volume= 3,393 cf  
 Outflow = 1.07 cfs @ 12.09 hrs, Volume= 3,017 cf, Atten= 0%, Lag= 0.1 min  
 Primary = 1.07 cfs @ 12.09 hrs, Volume= 3,017 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3

Peak Elev= 49.39' @ 12.09 hrs Surf.Area= 245 sf Storage= 388 cf

Plug-Flow detention time= 76.0 min calculated for 3,017 cf (89% of inflow)

Center-of-Mass det. time= 23.8 min ( 838.9 - 815.1 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap x 5</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=1.04 cfs @ 12.09 hrs HW=49.39' (Free Discharge)

↑**1=Sharp-Crested Rectangular Weir**(Weir Controls 1.04 cfs @ 1.23 fps)

**Summary for Pond P-5A: UIC #5**

Inflow Area =            21,940 sf, 100.00% Impervious, Inflow Depth = 4.36" for 10-Year event  
 Inflow        =        2.30 cfs @ 12.09 hrs, Volume=            7,970 cf  
 Outflow       =        0.57 cfs @ 12.46 hrs, Volume=            7,966 cf, Atten= 75%, Lag= 22.7 min  
 Discarded    =        0.57 cfs @ 12.46 hrs, Volume=            7,966 cf  
 Primary       =        0.00 cfs @ 0.00 hrs, Volume=            0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 47.58' @ 12.46 hrs Surf.Area= 2,681 sf Storage= 1,675 cf

Plug-Flow detention time= 15.3 min calculated for 7,951 cf (100% of inflow)  
 Center-of-Mass det. time= 14.9 min ( 780.5 - 765.6 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	2,004 cf	<b>44.25'W x 60.58'L x 3.50'H Field A</b> 9,382 cf Overall - 3,308 cf Embedded = 6,074 cf x 33.0% Voids
#2A	47.00'	3,308 cf	<b>ADS_StormTech SC-740 +Cap</b> x 72 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 72 Chambers in 9 Rows
		5,312 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.57 cfs @ 12.46 hrs HW=47.58' (Free Discharge)  
 ↑1=Exfiltration (Exfiltration Controls 0.57 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)  
 ↑2=Sharp-Crested Rectangular Weir ( Controls 0.00 cfs)

**Summary for Pond P-5B: Isolator Row #5**

Inflow Area =            8,940 sf, 100.00% Impervious, Inflow Depth = 4.56" for 10-Year event  
 Inflow        =        0.94 cfs @ 12.09 hrs, Volume=            3,400 cf  
 Outflow       =        0.94 cfs @ 12.09 hrs, Volume=            3,027 cf, Atten= 0%, Lag= 0.1 min  
 Primary       =        0.94 cfs @ 12.09 hrs, Volume=            3,027 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 49.38' @ 12.09 hrs Surf.Area= 245 sf Storage= 387 cf

Plug-Flow detention time= 97.4 min calculated for 3,027 cf (89% of inflow)  
 Center-of-Mass det. time= 44.6 min ( 793.3 - 748.7 )

**2826 Post Road Phase II Modifications - Proposed** Type III 24-hr 10-Year Rainfall=4.80"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 64

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap x 5</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=0.91 cfs @ 12.09 hrs HW=49.38' (Free Discharge)

↑1=Sharp-Crested Rectangular Weir(Weir Controls 0.91 cfs @ 1.18 fps)

**Summary for Pond P-6A: UIC #6**

Inflow Area = 49,136 sf, 88.32% Impervious, Inflow Depth = 3.44" for 10-Year event  
 Inflow = 4.56 cfs @ 12.09 hrs, Volume= 14,095 cf  
 Outflow = 1.07 cfs @ 12.49 hrs, Volume= 14,093 cf, Atten= 77%, Lag= 24.1 min  
 Discarded = 1.07 cfs @ 12.49 hrs, Volume= 14,093 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 46.11' @ 12.49 hrs Surf.Area= 5,074 sf Storage= 3,340 cf

Plug-Flow detention time= 17.8 min calculated for 14,093 cf (100% of inflow)  
 Center-of-Mass det. time= 17.7 min ( 810.6 - 792.9 )

Volume	Invert	Avail.Storage	Storage Description
#1A	45.00'	3,738 cf	<b>34.75'W x 146.02'L x 3.50'H Field A</b> 17,759 cf Overall - 6,432 cf Embedded = 11,328 cf x 33.0% Voids
#2A	45.50'	6,432 cf	<b>ADS_StormTech SC-740 +Cap x 140</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 140 Chambers in 7 Rows
		10,170 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	45.00'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	48.00'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=1.07 cfs @ 12.49 hrs HW=46.11' (Free Discharge)

↑1=Exfiltration (Exfiltration Controls 1.07 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=45.00' (Free Discharge)

↑2=Sharp-Crested Rectangular Weir( Controls 0.00 cfs)

**Summary for Pond P-6B: Isolator Row #6**

Inflow Area =            29,236 sf, 80.37% Impervious, Inflow Depth = 3.28" for 10-Year event  
 Inflow        =            2.50 cfs @ 12.09 hrs, Volume=            7,993 cf  
 Outflow      =            2.47 cfs @ 12.09 hrs, Volume=            6,528 cf, Atten= 1%, Lag= 0.2 min  
 Primary      =            2.47 cfs @ 12.09 hrs, Volume=            6,528 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 47.93' @ 12.09 hrs Surf.Area= 913 sf Storage= 1,497 cf

Plug-Flow detention time= 109.6 min calculated for 6,516 cf (82% of inflow)  
 Center-of-Mass det. time= 38.2 min ( 844.2 - 806.0 )

Volume	Invert	Avail.Storage	Storage Description
#1A	45.00'	751 cf	<b>6.25'W x 146.02'L x 3.50'H Field A</b> 3,194 cf Overall - 919 cf Embedded = 2,275 cf x 33.0% Voids
#2A	45.50'	919 cf	<b>ADS_StormTech SC-740 +Cap</b> x 20 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		1,670 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	47.75'	<b>5.0' long Sharp-Crested Rectangular Weir X 2.00</b> 2 End Contraction(s)

**Primary OutFlow** Max=2.43 cfs @ 12.09 hrs HW=47.93' (Free Discharge)  
 ↑1=Sharp-Crested Rectangular Weir(Weir Controls 2.43 cfs @ 1.38 fps)

**Summary for Link DP-1: Existing Drainage System - Phase 1**

Inflow Area =            554,769 sf, 78.45% Impervious, Inflow Depth = 0.06" for 10-Year event  
 Inflow        =            1.07 cfs @ 12.47 hrs, Volume=            2,566 cf  
 Primary      =            1.07 cfs @ 12.47 hrs, Volume=            2,566 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs

**Summary for Link DP-2: Post Road**

Inflow Area =            4,789 sf, 61.89% Impervious, Inflow Depth = 3.28" for 10-Year event  
 Inflow        =            0.41 cfs @ 12.09 hrs, Volume=            1,309 cf  
 Primary      =            0.41 cfs @ 12.09 hrs, Volume=            1,309 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs

**2826 Post Road Phase II Modifications - Proposed**    *Type III 24-hr 25-Year Rainfall=6.20"*

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 66

Time span=0.00-28.00 hrs, dt=0.05 hrs, 561 points  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

**SubcatchmentPR-1A: Subwatershed 1A** - Runoff Area=9,000 sf 100.00% Impervious Runoff Depth=5.96"  
Tc=6.0 min CN=98 Runoff=1.23 cfs 4,471 cf

**SubcatchmentPR-1B: Subwatershed 1B** - Runoff Area=30,994 sf 75.91% Impervious Runoff Depth=4.38"  
Tc=6.0 min CN=84 Runoff=3.52 cfs 11,323 cf

**SubcatchmentPR-1D: Bldg 3 & 5-12 and** Runoff Area=286,475 sf 80.60% Impervious Runoff Depth=4.82"  
Tc=6.0 min CN=88 Runoff=35.01 cfs 115,036 cf

**SubcatchmentPR-1E: Portion of Bldg 12 &** Runoff Area=76,715 sf 66.84% Impervious Runoff Depth=3.96"  
Tc=6.0 min CN=80 Runoff=7.97 cfs 25,330 cf

**SubcatchmentPR-1F: Undetained Area** Runoff Area=20,166 sf 0.00% Impervious Runoff Depth=0.69"  
Tc=6.0 min CN=42 Runoff=0.18 cfs 1,152 cf

**SubcatchmentPR-2: Area Discharging to** Runoff Area=4,789 sf 61.89% Impervious Runoff Depth=4.60"  
Tc=6.0 min CN=86 Runoff=0.57 cfs 1,836 cf

**SubcatchmentPR-2A: Subwatershed 2A** - Runoff Area=6,500 sf 100.00% Impervious Runoff Depth=5.96"  
Tc=6.0 min CN=98 Runoff=0.89 cfs 3,229 cf

**SubcatchmentPR-2B: Subwatershed 2B** - Runoff Area=11,917 sf 85.52% Impervious Runoff Depth=4.93"  
Tc=6.0 min CN=89 Runoff=1.48 cfs 4,895 cf

**SubcatchmentPR-3A: Subwatershed 3A** - Runoff Area=6,500 sf 100.00% Impervious Runoff Depth=5.96"  
Tc=6.0 min CN=98 Runoff=0.89 cfs 3,229 cf

**SubcatchmentPR-3B: Subwatershed 3B** - Runoff Area=8,824 sf 100.00% Impervious Runoff Depth=5.96"  
Tc=6.0 min CN=98 Runoff=1.20 cfs 4,384 cf

**SubcatchmentPR-4A: Subwatershed 4A** - Runoff Area=13,000 sf 100.00% Impervious Runoff Depth=5.96"  
Tc=6.0 min CN=98 Runoff=1.77 cfs 6,458 cf

**SubcatchmentPR-4B: Subwatershed 4B** - Runoff Area=13,602 sf 74.92% Impervious Runoff Depth=4.28"  
Tc=6.0 min CN=83 Runoff=1.51 cfs 4,848 cf

**SubcatchmentPR-5A: Subwatershed 5A** - Runoff Area=13,000 sf 100.00% Impervious Runoff Depth=5.96"  
Tc=6.0 min CN=98 Runoff=1.77 cfs 6,458 cf

**SubcatchmentPR-5B: Subwatershed 5B** - Runoff Area=8,940 sf 100.00% Impervious Runoff Depth=5.96"  
Tc=6.0 min CN=98 Runoff=1.22 cfs 4,441 cf

**SubcatchmentPR-6A: Subwatershed 6A** - Runoff Area=19,900 sf 100.00% Impervious Runoff Depth=5.96"  
Tc=6.0 min CN=98 Runoff=2.71 cfs 9,886 cf

**SubcatchmentPR-6B: Subwatershed 6B** - Runoff Area=29,236 sf 80.37% Impervious Runoff Depth=4.60"  
Tc=6.0 min CN=86 Runoff=3.45 cfs 11,207 cf





**Summary for Subcatchment PR-1A: Subwatershed 1A - Roof A**

Runoff = 1.23 cfs @ 12.09 hrs, Volume= 4,471 cf, Depth= 5.96"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 25-Year Rainfall=6.20"

Area (sf)	CN	Description
9,000	98	Roofs, HSG A
9,000	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-1B: Subwatershed 1B - Parking Lot**

Runoff = 3.52 cfs @ 12.09 hrs, Volume= 11,323 cf, Depth= 4.38"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 25-Year Rainfall=6.20"

Area (sf)	CN	Description
* 23,528	98	Paved parking and sidewalks, HSG A
7,466	39	>75% Grass cover, Good, HSG A
30,994	84	Weighted Average
7,466	39	24.09% Pervious Area
23,528	98	75.91% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-1D: Bldg 3 & 5-12 and Pvt**

Runoff = 35.01 cfs @ 12.09 hrs, Volume= 115,036 cf, Depth= 4.82"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 25-Year Rainfall=6.20"

**2826 Post Road Phase II Modifications - Proposed**    *Type III 24-hr 25-Year Rainfall=6.20"*

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 69

Area (sf)	CN	Description
8,805	32	Woods/grass comb., Good, HSG A
2,001	72	Dirt roads, HSG A
28,102	39	>75% Grass cover, Good, HSG A
113,211	98	Roofs, HSG A
113,868	98	Paved parking, HSG A
15,161	68	<50% Grass cover, Poor, HSG A
1,158	30	Woods, Good, HSG A
1,705	98	Roofs, HSG B
2,111	98	Paved parking, HSG B
353	61	>75% Grass cover, Good, HSG B
286,475	88	Weighted Average
55,580	47	19.40% Pervious Area
230,895	98	80.60% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-1E: Portion of Bldg 12 & Pvt Draining to Basin**

Runoff = 7.97 cfs @ 12.09 hrs, Volume= 25,330 cf, Depth= 3.96"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 25-Year Rainfall=6.20"

Area (sf)	CN	Description
14,109	39	>75% Grass cover, Good, HSG A
21,676	98	Roofs, HSG A
29,598	98	Paved parking, HSG A
3,129	72	Dirt roads, HSG A
1,746	68	<50% Grass cover, Poor, HSG A
2,283	36	Woods, Fair, HSG A
2,244	30	Woods, Good, HSG A
1,931	32	Woods/grass comb., Good, HSG A
76,715	80	Weighted Average
25,442	43	33.16% Pervious Area
51,274	98	66.84% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-1F: Undetained Area**

Runoff = 0.18 cfs @ 12.16 hrs, Volume= 1,152 cf, Depth= 0.69"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 25-Year Rainfall=6.20"

**2826 Post Road Phase II Modifications - Proposed**      *Type III 24-hr 25-Year Rainfall=6.20"*

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 70

Area (sf)	CN	Description
5,393	39	>75% Grass cover, Good, HSG A
10,624	36	Woods, Fair, HSG A
183	61	>75% Grass cover, Good, HSG B
3,966	60	Woods, Fair, HSG B
20,166	42	Weighted Average
20,166	42	100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-2: Area Discharging to Post Road**

Runoff = 0.57 cfs @ 12.09 hrs, Volume= 1,836 cf, Depth= 4.60"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 25-Year Rainfall=6.20"

Area (sf)	CN	Description
829	98	Paved parking, HSG A
572	39	>75% Grass cover, Good, HSG A
2,135	98	Paved parking, HSG D
1,253	80	>75% Grass cover, Good, HSG D
4,789	86	Weighted Average
1,825	67	38.11% Pervious Area
2,964	98	61.89% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-2A: Subwatershed 2A - Roof**

Runoff = 0.89 cfs @ 12.09 hrs, Volume= 3,229 cf, Depth= 5.96"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 25-Year Rainfall=6.20"

Area (sf)	CN	Description
6,500	98	Roofs, HSG A
6,500	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-2B: Subwatershed 2B - Parking Lot**

Runoff = 1.48 cfs @ 12.09 hrs, Volume= 4,895 cf, Depth= 4.93"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 25-Year Rainfall=6.20"

	Area (sf)	CN	Description
*	10,191	98	Paved parking and sidewalks, HSG A
	1,726	39	>75% Grass cover, Good, HSG A
	11,917	89	Weighted Average
	1,726	39	14.48% Pervious Area
	10,191	98	85.52% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-3A: Subwatershed 3A - Roof**

Runoff = 0.89 cfs @ 12.09 hrs, Volume= 3,229 cf, Depth= 5.96"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 25-Year Rainfall=6.20"

	Area (sf)	CN	Description
	6,500	98	Roofs, HSG A
	6,500	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-3B: Subwatershed 3B - Parking Lot**

Runoff = 1.20 cfs @ 12.09 hrs, Volume= 4,384 cf, Depth= 5.96"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 25-Year Rainfall=6.20"

	Area (sf)	CN	Description
*	8,824	98	Paved parking and sidewalks, HSG A
	8,824	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-4A: Subwatershed 4A - Roof**

Runoff = 1.77 cfs @ 12.09 hrs, Volume= 6,458 cf, Depth= 5.96"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 25-Year Rainfall=6.20"

Area (sf)	CN	Description
13,000	98	Roofs, HSG A
13,000	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-4B: Subwatershed 4B - Parking Lot**

Runoff = 1.51 cfs @ 12.09 hrs, Volume= 4,848 cf, Depth= 4.28"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 25-Year Rainfall=6.20"

Area (sf)	CN	Description
* 10,191	98	Paved parking and sidewalks, HSG A
3,411	39	>75% Grass cover, Good, HSG A
13,602	83	Weighted Average
3,411	39	25.08% Pervious Area
10,191	98	74.92% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-5A: Subwatershed 5A - Roof**

Runoff = 1.77 cfs @ 12.09 hrs, Volume= 6,458 cf, Depth= 5.96"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 25-Year Rainfall=6.20"

Area (sf)	CN	Description
13,000	98	Roofs, HSG A
13,000	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-5B: Subwatershed 5B - Parking Lot**

Runoff = 1.22 cfs @ 12.09 hrs, Volume= 4,441 cf, Depth= 5.96"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 25-Year Rainfall=6.20"

Area (sf)	CN	Description
* 8,940	98	Paved parking and sidewalks, HSG A
8,940	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-6A: Subwatershed 6A - Roof**

Runoff = 2.71 cfs @ 12.09 hrs, Volume= 9,886 cf, Depth= 5.96"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 25-Year Rainfall=6.20"

Area (sf)	CN	Description
19,900	98	Roofs, HSG A
19,900	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-6B: Subwatershed 6B - Parking Lot**

Runoff = 3.45 cfs @ 12.09 hrs, Volume= 11,207 cf, Depth= 4.60"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 25-Year Rainfall=6.20"

Area (sf)	CN	Description
* 23,498	98	Paved parking and sidewalks, HSG A
5,738	39	>75% Grass cover, Good, HSG A
29,236	86	Weighted Average
5,738	39	19.63% Pervious Area
23,498	98	80.37% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Pond P-1A: UIC #1**

Inflow Area =            39,994 sf, 81.33% Impervious, Inflow Depth = 4.52" for 25-Year event  
 Inflow        =        4.73 cfs @ 12.09 hrs, Volume=            15,069 cf  
 Outflow       =        0.94 cfs @ 12.53 hrs, Volume=            15,075 cf, Atten= 80%, Lag= 26.3 min  
 Discarded =        0.94 cfs @ 12.53 hrs, Volume=            15,075 cf  
 Primary       =        0.00 cfs @ 0.00 hrs, Volume=            0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 48.04' @ 12.53 hrs Surf.Area= 4,161 sf Storage= 4,063 cf

Plug-Flow detention time= (not calculated: outflow precedes inflow)  
 Center-of-Mass det. time= 26.3 min ( 824.0 - 797.7 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	3,108 cf	<b>20.50'W x 202.98'L x 3.50'H Field A</b> 14,564 cf Overall - 5,145 cf Embedded = 9,418 cf x 33.0% Voids
#2A	47.00'	5,145 cf	<b>ADS_StormTech SC-740 +Cap</b> x 112 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 112 Chambers in 4 Rows
		8,253 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.94 cfs @ 12.53 hrs HW=48.04' (Free Discharge)  
 ↑1=**Exfiltration** (Exfiltration Controls 0.94 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)  
 ↑2=**Sharp-Crested Rectangular Weir** ( Controls 0.00 cfs)

**Summary for Pond P-1B: Isolator Row #1**

Inflow Area =            30,994 sf, 75.91% Impervious, Inflow Depth = 4.38" for 25-Year event  
 Inflow        =        3.52 cfs @ 12.09 hrs, Volume=            11,323 cf  
 Outflow       =        3.51 cfs @ 12.09 hrs, Volume=            10,598 cf, Atten= 0%, Lag= 0.1 min  
 Primary       =        3.51 cfs @ 12.09 hrs, Volume=            10,598 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 49.48' @ 12.09 hrs Surf.Area= 468 sf Storage= 767 cf

Plug-Flow detention time= 52.0 min calculated for 10,598 cf (94% of inflow)  
 Center-of-Mass det. time= 17.9 min ( 820.1 - 802.3 )

**2826 Post Road Phase II Modifications - Proposed**    *Type III 24-hr 25-Year Rainfall=6.20"*

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 75

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	388 cf	<b>6.25'W x 74.82'L x 3.50'H Field A</b> 1,637 cf Overall - 459 cf Embedded = 1,177 cf x 33.0% Voids
#2A	47.00'	459 cf	<b>ADS_StormTech SC-740 +Cap</b> x 10 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		848 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>5.0' long Sharp-Crested Rectangular Weir X 2.00</b> 2 End Contraction(s)

**Primary OutFlow** Max=3.43 cfs @ 12.09 hrs HW=49.47' (Free Discharge)

↳ **1=Sharp-Crested Rectangular Weir** (Weir Controls 3.43 cfs @ 1.55 fps)

**Summary for Pond P-1D: Underground Infiltration**

Inflow Area = 286,475 sf, 80.60% Impervious, Inflow Depth = 4.82" for 25-Year event  
 Inflow = 35.01 cfs @ 12.09 hrs, Volume= 115,036 cf  
 Outflow = 9.42 cfs @ 12.45 hrs, Volume= 115,036 cf, Atten= 73%, Lag= 21.7 min  
 Discarded = 5.68 cfs @ 12.45 hrs, Volume= 104,271 cf  
 Primary = 3.75 cfs @ 12.45 hrs, Volume= 10,765 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Peak Elev= 46.65' @ 12.45 hrs Surf.Area= 23,713 sf Storage= 30,253 cf

Plug-Flow detention time= 26.7 min calculated for 114,831 cf (100% of inflow)  
 Center-of-Mass det. time= 26.7 min ( 817.0 - 790.4 )



**2826 Post Road Phase II Modifications - Proposed**      *Type III 24-hr 25-Year Rainfall=6.20"*

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 76

Volume	Invert	Avail.Storage	Storage Description
#1	44.70'	18,217 cf	<b>15.75'W x 1,505.60'L x 3.50'H Crushed Stone</b> 82,996 cf Overall - 27,794 cf Embedded = 55,202 cf x 33.0% Voids
#2	45.20'	1,103 cf	<b>P-1D-A</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 24 Chambers in 3 Rows
#3	45.20'	1,929 cf	<b>P-1D-B</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 42 Chambers in 3 Rows
#4	45.20'	1,240 cf	<b>P-1D-C</b> x 27 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 27 Chambers in 3 Rows
#5	45.20'	965 cf	<b>P-1D-D</b> x 21 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 21 Chambers in 3 Rows
#6	45.20'	1,654 cf	<b>P-1D-E</b> x 36 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 36 Chambers in 3 Rows
#7	45.20'	1,654 cf	<b>P-1D-F</b> x 36 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 36 Chambers in 3 Rows
#8	45.20'	1,103 cf	<b>P-1D-G</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 24 Chambers in 3 Rows
#9	45.20'	1,286 cf	<b>P-1D-H</b> x 28 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 28 Chambers in 2 Rows
#10	45.20'	184 cf	<b>P-1D-H</b> x 4 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#11	45.20'	413 cf	<b>P-1D-H</b> x 9 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#12	45.20'	2,067 cf	<b>P-1D-I</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 45 Chambers in 3 Rows
#13	45.20'	1,929 cf	<b>P-1D-J</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 42 Chambers in 3 Rows
#14	45.20'	2,067 cf	<b>P-1D-K</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap

**2826 Post Road Phase II Modifications - Proposed**      *Type III 24-hr 25-Year Rainfall=6.20"*

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 77

#15	45.20'	1,929 cf	45 Chambers in 3 Rows <b>P-1D-L</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#16	45.20'	2,067 cf	42 Chambers in 3 Rows <b>P-1D-M</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#17	45.20'	1,929 cf	45 Chambers in 3 Rows <b>P-1D-N</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#18	45.20'	2,067 cf	42 Chambers in 3 Rows <b>P-1D-O</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#19	45.20'	1,103 cf	45 Chambers in 3 Rows <b>P-1D-P</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#20	45.20'	1,103 cf	24 Chambers in 3 Rows <b>P-1D-Q</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#21	46.25'	134 cf	<b>18.0" Round Pipe CB5-DMH1</b> -Impervious L= 76.0' S= 0.0031 '/'
#22	45.70'	205 cf	<b>18.0" Round Pipe CB5-CB6</b> -Impervious L= 116.0' S= 0.0025 '/'
#23	46.10'	93 cf	<b>12.0" Round Pipe CB6-CB7</b> -Impervious L= 118.0' S= 0.0033 '/'
#24	46.50'	101 cf	<b>12.0" Round Pipe CB33-CB40</b> -Impervious L= 128.0' S= 0.0098 '/'
#25	46.10'	83 cf	<b>12.0" Round Pipe CB8-CB9</b> -Impervious L= 106.0' S= 0.0036 '/'
#26	45.70'	187 cf	<b>18.0" Round Pipe CB9-CB10</b> -Impervious L= 106.0' S= 0.0027 '/'
#27	46.20'	91 cf	<b>12.0" Round Pipe CB10-CB11</b> -Impervious L= 116.0' S= 0.0025 '/'
#28	45.30'	540 cf	<b>24.0" Round 24" Header Pipe</b> -Impervious L= 172.0'
#29	45.30'	855 cf	<b>4.00'D x 4.00'H CBs</b> x 17 -Impervious
#30	46.00'	50 cf	<b>4.00'D x 4.00'H CB-6</b> -Impervious
#31	46.50'	50 cf	<b>4.00'D x 4.00'H CB-7</b> -Impervious
#32	47.80'	50 cf	<b>4.00'D x 4.00'H CB-40</b> -Impervious
#33	46.50'	50 cf	<b>4.00'D x 4.00'H CB-8</b> -Impervious
#34	46.00'	50 cf	<b>4.00'D x 4.00'H CB-9</b> -Impervious
#35	46.50'	50 cf	<b>4.00'D x 4.00'H CB-11</b> -Impervious
#36	46.50'	50 cf	<b>4.00'D x 4.00'H CB-33</b> -Impervious
		48,651 cf	Total Available Storage

**2826 Post Road Phase II Modifications - Proposed** Type III 24-hr 25-Year Rainfall=6.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 78

Device	Routing	Invert	Outlet Devices
#1	Discarded	44.70'	<b>8.270 in/hr Exfiltration over Wetted area</b> Phase-In= 0.01'
#2	Device 4	45.70'	<b>15.0" W x 21.0" H Vert. Orifice/Grate</b> C= 0.600
#3	Device 4	48.10'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)
#4	Primary	31.40'	<b>24.0" Round Culvert</b> L= 25.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 31.40' / 31.00' S= 0.0160 '/ Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 3.14 sf

**Discarded OutFlow** Max=5.68 cfs @ 12.45 hrs HW=46.65' (Free Discharge)

↳ **1=Exfiltration** (Exfiltration Controls 5.68 cfs)

**Primary OutFlow** Max=3.74 cfs @ 12.45 hrs HW=46.65' (Free Discharge)

↳ **4=Culvert** (Passes 3.74 cfs of 45.09 cfs potential flow)

↳ **2=Orifice/Grate** (Orifice Controls 3.74 cfs @ 3.14 fps)

↳ **3=Sharp-Crested Rectangular Weir** ( Controls 0.00 cfs)

**Summary for Pond P-1E: Infiltration Basin**

Inflow Area =	76,715 sf, 66.84% Impervious,	Inflow Depth = 3.96"	for 25-Year event
Inflow =	7.97 cfs @ 12.09 hrs,	Volume=	25,330 cf
Outflow =	1.03 cfs @ 12.70 hrs,	Volume=	25,330 cf, Atten= 87%, Lag= 36.7 min
Discarded =	1.03 cfs @ 12.70 hrs,	Volume=	25,330 cf
Primary =	0.00 cfs @ 0.00 hrs,	Volume=	0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Peak Elev= 47.01' @ 12.70 hrs Surf.Area= 5,372 sf Storage= 8,968 cf

Plug-Flow detention time= 73.0 min calculated for 25,285 cf (100% of inflow)  
Center-of-Mass det. time= 72.9 min ( 885.7 - 812.8 )

Volume	Invert	Avail.Storage	Storage Description
#1	45.00'	21,635 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
45.00	3,597	0	0
46.00	4,453	4,025	4,025
47.00	5,366	4,910	8,935
48.00	6,336	5,851	14,786
49.00	7,362	6,849	21,635

Device	Routing	Invert	Outlet Devices
#1	Discarded	45.00'	<b>8.270 in/hr Exfiltration over Surface area</b> Phase-In= 0.01'
#2	Primary	48.20'	<b>35.0' long x 8.0' breadth Broad-Crested Rectangular Weir</b> Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.43 2.54 2.70 2.69 2.68 2.68 2.66 2.64 2.64 2.64 2.65 2.65 2.66 2.66 2.68 2.70 2.74

**Discarded OutFlow** Max=1.03 cfs @ 12.70 hrs HW=47.01' (Free Discharge)  
 ↑1=Exfiltration (Exfiltration Controls 1.03 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=45.00' (Free Discharge)  
 ↑2=Broad-Crested Rectangular Weir ( Controls 0.00 cfs)

**Summary for Pond P-2A: UIC #2**

Inflow Area = 18,417 sf, 90.63% Impervious, Inflow Depth = 5.05" for 25-Year event  
 Inflow = 2.36 cfs @ 12.09 hrs, Volume= 7,749 cf  
 Outflow = 0.51 cfs @ 12.50 hrs, Volume= 7,757 cf, Atten= 78%, Lag= 24.8 min  
 Discarded = 0.51 cfs @ 12.50 hrs, Volume= 7,757 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 47.82' @ 12.50 hrs Surf.Area= 2,352 sf Storage= 1,905 cf

Plug-Flow detention time= (not calculated: outflow precedes inflow)  
 Center-of-Mass det. time= 20.9 min ( 804.2 - 783.3 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	1,762 cf	<b>34.75'W x 67.70'L x 3.50'H Field A</b> 8,234 cf Overall - 2,894 cf Embedded = 5,339 cf x 33.0% Voids
#2A	47.00'	2,894 cf	<b>ADS_StormTech SC-740 +Cap</b> x 63 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 63 Chambers in 7 Rows
		4,656 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.51 cfs @ 12.50 hrs HW=47.82' (Free Discharge)  
 ↑1=Exfiltration (Exfiltration Controls 0.51 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)  
 ↑2=Sharp-Crested Rectangular Weir ( Controls 0.00 cfs)

**Summary for Pond P-2B: Isolator Row #2**

Inflow Area = 11,917 sf, 85.52% Impervious, Inflow Depth = 4.93" for 25-Year event  
 Inflow = 1.48 cfs @ 12.09 hrs, Volume= 4,895 cf  
 Outflow = 1.48 cfs @ 12.09 hrs, Volume= 4,519 cf, Atten= 0%, Lag= 0.1 min  
 Primary = 1.48 cfs @ 12.09 hrs, Volume= 4,519 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3

Peak Elev= 49.43' @ 12.09 hrs    Surf.Area= 245 sf    Storage= 391 cf

Plug-Flow detention time= 63.1 min calculated for 4,511 cf (92% of inflow)  
 Center-of-Mass det. time= 23.9 min ( 811.0 - 787.1 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap</b> x 5 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=1.44 cfs @ 12.09 hrs HW=49.43' (Free Discharge)  
 ↑**1=Sharp-Crested Rectangular Weir**(Weir Controls 1.44 cfs @ 1.37 fps)

**Summary for Pond P-3A: UIC #3**

Inflow Area = 15,324 sf, 100.00% Impervious, Inflow Depth = 5.67" for 25-Year event  
 Inflow = 2.08 cfs @ 12.09 hrs, Volume= 7,240 cf  
 Outflow = 0.45 cfs @ 12.50 hrs, Volume= 7,233 cf, Atten= 79%, Lag= 24.7 min  
 Discarded = 0.45 cfs @ 12.50 hrs, Volume= 7,233 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 47.87' @ 12.50 hrs    Surf.Area= 2,031 sf    Storage= 1,711 cf

Plug-Flow detention time= 21.0 min calculated for 7,233 cf (100% of inflow)  
 Center-of-Mass det. time= 20.3 min ( 786.4 - 766.1 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	1,527 cf	<b>30.00'W x 67.70'L x 3.50'H Field A</b> 7,108 cf Overall - 2,481 cf Embedded = 4,627 cf x 33.0% Voids
#2A	47.00'	2,481 cf	<b>ADS_StormTech SC-740 +Cap</b> x 54 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 54 Chambers in 6 Rows
		4,008 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.45 cfs @ 12.50 hrs HW=47.87' (Free Discharge)  
 ↑1=Exfiltration (Exfiltration Controls 0.45 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)  
 ↑2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

**Summary for Pond P-3B: Isolator Row #3**

Inflow Area = 8,824 sf, 100.00% Impervious, Inflow Depth = 5.96" for 25-Year event  
 Inflow = 1.20 cfs @ 12.09 hrs, Volume= 4,384 cf  
 Outflow = 1.20 cfs @ 12.09 hrs, Volume= 4,011 cf, Atten= 0%, Lag= 0.1 min  
 Primary = 1.20 cfs @ 12.09 hrs, Volume= 4,011 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 49.41' @ 12.09 hrs Surf.Area= 245 sf Storage= 389 cf

Plug-Flow detention time= 83.1 min calculated for 4,011 cf (91% of inflow)  
 Center-of-Mass det. time= 38.7 min ( 783.3 - 744.7 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap x 5</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=1.17 cfs @ 12.09 hrs HW=49.40' (Free Discharge)  
 ↑1=Sharp-Crested Rectangular Weir (Weir Controls 1.17 cfs @ 1.28 fps)

**Summary for Pond P-4A: UIC #4**

Inflow Area = 26,602 sf, 87.18% Impervious, Inflow Depth = 4.93" for 25-Year event  
 Inflow = 3.28 cfs @ 12.09 hrs, Volume= 10,937 cf  
 Outflow = 0.59 cfs @ 12.55 hrs, Volume= 10,948 cf, Atten= 82%, Lag= 27.5 min  
 Discarded = 0.59 cfs @ 12.55 hrs, Volume= 10,948 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 48.24' @ 12.55 hrs Surf.Area= 2,674 sf Storage= 2,989 cf

Plug-Flow detention time= (not calculated: outflow precedes inflow)  
 Center-of-Mass det. time= 30.3 min ( 807.7 - 777.5 )

**2826 Post Road Phase II Modifications - Proposed**    *Type III 24-hr 25-Year Rainfall=6.20"*

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 82

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	1,997 cf	<b>39.50'W x 67.70'L x 3.50'H Field A</b> 9,359 cf Overall - 3,308 cf Embedded = 6,051 cf x 33.0% Voids
#2A	47.00'	3,308 cf	<b>ADS_StormTech SC-740 +Cap x 72</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 72 Chambers in 8 Rows
		5,305 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.59 cfs @ 12.55 hrs HW=48.24' (Free Discharge)

↑**1=Exfiltration** (Exfiltration Controls 0.59 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)

↑**2=Sharp-Crested Rectangular Weir**( Controls 0.00 cfs)

**Summary for Pond P-4B: Isolator Row #4**

Inflow Area = 13,602 sf, 74.92% Impervious, Inflow Depth = 4.28" for 25-Year event  
 Inflow = 1.51 cfs @ 12.09 hrs, Volume= 4,848 cf  
 Outflow = 1.51 cfs @ 12.09 hrs, Volume= 4,479 cf, Atten= 0%, Lag= 0.1 min  
 Primary = 1.51 cfs @ 12.09 hrs, Volume= 4,479 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3

Peak Elev= 49.43' @ 12.09 hrs Surf.Area= 245 sf Storage= 391 cf

Plug-Flow detention time= 58.6 min calculated for 4,471 cf (92% of inflow)

Center-of-Mass det. time= 19.8 min ( 824.8 - 805.0 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap x 5</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=1.48 cfs @ 12.09 hrs HW=49.43' (Free Discharge)

↑**1=Sharp-Crested Rectangular Weir**(Weir Controls 1.48 cfs @ 1.38 fps)

**Summary for Pond P-5A: UIC #5**

Inflow Area =            21,940 sf, 100.00% Impervious, Inflow Depth = 5.76" for 25-Year event  
 Inflow        =        2.98 cfs @ 12.09 hrs, Volume=            10,526 cf  
 Outflow      =        0.58 cfs @ 12.52 hrs, Volume=        10,531 cf, Atten= 80%, Lag= 25.9 min  
 Discarded =        0.58 cfs @ 12.52 hrs, Volume=        10,531 cf  
 Primary     =        0.00 cfs @ 0.00 hrs, Volume=            0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 48.04' @ 12.52 hrs Surf.Area= 2,681 sf Storage= 2,604 cf

Plug-Flow detention time= (not calculated: outflow precedes inflow)  
 Center-of-Mass det. time= 24.1 min ( 783.6 - 759.5 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	2,004 cf	<b>44.25'W x 60.58'L x 3.50'H Field A</b> 9,382 cf Overall - 3,308 cf Embedded = 6,074 cf x 33.0% Voids
#2A	47.00'	3,308 cf	<b>ADS_StormTech SC-740 +Cap</b> x 72 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 72 Chambers in 9 Rows
		5,312 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.58 cfs @ 12.52 hrs HW=48.04' (Free Discharge)  
 ↑1=Exfiltration (Exfiltration Controls 0.58 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)  
 ↑2=Sharp-Crested Rectangular Weir ( Controls 0.00 cfs)

**Summary for Pond P-5B: Isolator Row #5**

Inflow Area =            8,940 sf, 100.00% Impervious, Inflow Depth = 5.96" for 25-Year event  
 Inflow        =        1.22 cfs @ 12.09 hrs, Volume=            4,441 cf  
 Outflow      =        1.21 cfs @ 12.09 hrs, Volume=        4,067 cf, Atten= 0%, Lag= 0.1 min  
 Primary     =        1.21 cfs @ 12.09 hrs, Volume=            4,067 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 49.41' @ 12.09 hrs Surf.Area= 245 sf Storage= 389 cf

Plug-Flow detention time= 81.9 min calculated for 4,060 cf (91% of inflow)  
 Center-of-Mass det. time= 38.4 min ( 783.1 - 744.7 )



**2826 Post Road Phase II Modifications - Proposed** Type III 24-hr 25-Year Rainfall=6.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 84

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap x 5</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=1.18 cfs @ 12.09 hrs HW=49.40' (Free Discharge)

↑1=Sharp-Crested Rectangular Weir(Weir Controls 1.18 cfs @ 1.28 fps)

**Summary for Pond P-6A: UIC #6**

Inflow Area = 49,136 sf, 88.32% Impervious, Inflow Depth = 4.80" for 25-Year event  
 Inflow = 6.13 cfs @ 12.09 hrs, Volume= 19,668 cf  
 Outflow = 1.11 cfs @ 12.55 hrs, Volume= 19,674 cf, Atten= 82%, Lag= 27.6 min  
 Discarded = 1.11 cfs @ 12.55 hrs, Volume= 19,674 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 46.70' @ 12.55 hrs Surf.Area= 5,074 sf Storage= 5,602 cf

Plug-Flow detention time= (not calculated: outflow precedes inflow)  
 Center-of-Mass det. time= 31.4 min ( 817.6 - 786.2 )

Volume	Invert	Avail.Storage	Storage Description
#1A	45.00'	3,738 cf	<b>34.75'W x 146.02'L x 3.50'H Field A</b> 17,759 cf Overall - 6,432 cf Embedded = 11,328 cf x 33.0% Voids
#2A	45.50'	6,432 cf	<b>ADS_StormTech SC-740 +Cap x 140</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 140 Chambers in 7 Rows
		10,170 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	45.00'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	48.00'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=1.11 cfs @ 12.55 hrs HW=46.70' (Free Discharge)

↑1=Exfiltration (Exfiltration Controls 1.11 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=45.00' (Free Discharge)

↑2=Sharp-Crested Rectangular Weir( Controls 0.00 cfs)

**Summary for Pond P-6B: Isolator Row #6**

Inflow Area =            29,236 sf, 80.37% Impervious, Inflow Depth = 4.60" for 25-Year event  
 Inflow        =        3.45 cfs @ 12.09 hrs, Volume=            11,207 cf  
 Outflow       =        3.42 cfs @ 12.09 hrs, Volume=            9,782 cf, Atten= 1%, Lag= 0.2 min  
 Primary       =        3.42 cfs @ 12.09 hrs, Volume=            9,782 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 47.97' @ 12.09 hrs Surf.Area= 913 sf Storage= 1,511 cf

Plug-Flow detention time= 88.7 min calculated for 9,782 cf (87% of inflow)  
 Center-of-Mass det. time= 31.6 min ( 828.1 - 796.5 )

Volume	Invert	Avail.Storage	Storage Description
#1A	45.00'	751 cf	<b>6.25'W x 146.02'L x 3.50'H Field A</b> 3,194 cf Overall - 919 cf Embedded = 2,275 cf x 33.0% Voids
#2A	45.50'	919 cf	<b>ADS_StormTech SC-740 +Cap x 20</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		1,670 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	47.75'	<b>5.0' long Sharp-Crested Rectangular Weir X 2.00</b> 2 End Contraction(s)

**Primary OutFlow** Max=3.35 cfs @ 12.09 hrs HW=47.97' (Free Discharge)  
 ↑1=Sharp-Crested Rectangular Weir(Weir Controls 3.35 cfs @ 1.54 fps)

**Summary for Link DP-1: Existing Drainage System - Phase 1**

Inflow Area =            554,769 sf, 78.45% Impervious, Inflow Depth = 0.26" for 25-Year event  
 Inflow        =        3.87 cfs @ 12.44 hrs, Volume=            11,917 cf  
 Primary       =        3.87 cfs @ 12.44 hrs, Volume=            11,917 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs

**Summary for Link DP-2: Post Road**

Inflow Area =            4,789 sf, 61.89% Impervious, Inflow Depth = 4.60" for 25-Year event  
 Inflow        =        0.57 cfs @ 12.09 hrs, Volume=            1,836 cf  
 Primary       =        0.57 cfs @ 12.09 hrs, Volume=            1,836 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs

**2826 Post Road Phase II Modifications - Proposed** Type III 24-hr 100-Year Rainfall=8.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 86

Time span=0.00-28.00 hrs, dt=0.05 hrs, 561 points  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

**SubcatchmentPR-1A: Subwatershed 1A** - Runoff Area=9,000 sf 100.00% Impervious Runoff Depth=8.46"  
Tc=6.0 min CN=98 Runoff=1.72 cfs 6,345 cf

**SubcatchmentPR-1B: Subwatershed 1B** - Runoff Area=30,994 sf 75.91% Impervious Runoff Depth=6.77"  
Tc=6.0 min CN=84 Runoff=5.32 cfs 17,484 cf

**SubcatchmentPR-1D: Bldg 3 & 5-12 and** Runoff Area=286,475 sf 80.60% Impervious Runoff Depth=7.25"  
Tc=6.0 min CN=88 Runoff=51.50 cfs 173,164 cf

**SubcatchmentPR-1E: Portion of Bldg 12 &** Runoff Area=76,715 sf 66.84% Impervious Runoff Depth=6.28"  
Tc=6.0 min CN=80 Runoff=12.43 cfs 40,174 cf

**SubcatchmentPR-1F: Undetained Area** Runoff Area=20,166 sf 0.00% Impervious Runoff Depth=1.79"  
Tc=6.0 min CN=42 Runoff=0.78 cfs 3,001 cf

**SubcatchmentPR-2: Area Discharging to** Runoff Area=4,789 sf 61.89% Impervious Runoff Depth=7.01"  
Tc=6.0 min CN=86 Runoff=0.84 cfs 2,798 cf

**SubcatchmentPR-2A: Subwatershed 2A** - Runoff Area=6,500 sf 100.00% Impervious Runoff Depth=8.46"  
Tc=6.0 min CN=98 Runoff=1.24 cfs 4,582 cf

**SubcatchmentPR-2B: Subwatershed 2B** - Runoff Area=11,917 sf 85.52% Impervious Runoff Depth=7.37"  
Tc=6.0 min CN=89 Runoff=2.16 cfs 7,324 cf

**SubcatchmentPR-3A: Subwatershed 3A** - Runoff Area=6,500 sf 100.00% Impervious Runoff Depth=8.46"  
Tc=6.0 min CN=98 Runoff=1.24 cfs 4,582 cf

**SubcatchmentPR-3B: Subwatershed 3B** - Runoff Area=8,824 sf 100.00% Impervious Runoff Depth=8.46"  
Tc=6.0 min CN=98 Runoff=1.69 cfs 6,221 cf

**SubcatchmentPR-4A: Subwatershed 4A** - Runoff Area=13,000 sf 100.00% Impervious Runoff Depth=8.46"  
Tc=6.0 min CN=98 Runoff=2.49 cfs 9,165 cf

**SubcatchmentPR-4B: Subwatershed 4B** - Runoff Area=13,602 sf 74.92% Impervious Runoff Depth=6.65"  
Tc=6.0 min CN=83 Runoff=2.30 cfs 7,535 cf

**SubcatchmentPR-5A: Subwatershed 5A** - Runoff Area=13,000 sf 100.00% Impervious Runoff Depth=8.46"  
Tc=6.0 min CN=98 Runoff=2.49 cfs 9,165 cf

**SubcatchmentPR-5B: Subwatershed 5B** - Runoff Area=8,940 sf 100.00% Impervious Runoff Depth=8.46"  
Tc=6.0 min CN=98 Runoff=1.71 cfs 6,303 cf

**SubcatchmentPR-6A: Subwatershed 6A** - Runoff Area=19,900 sf 100.00% Impervious Runoff Depth=8.46"  
Tc=6.0 min CN=98 Runoff=3.81 cfs 14,029 cf

**SubcatchmentPR-6B: Subwatershed 6B** - Runoff Area=29,236 sf 80.37% Impervious Runoff Depth=7.01"  
Tc=6.0 min CN=86 Runoff=5.14 cfs 17,082 cf

**2826 Post Road Phase II Modifications - Proposed** Type III 24-hr 100-Year Rainfall=8.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 87

<b>Pond P-1A: UIC #1</b>	Peak Elev=49.27' Storage=7,225 cf Inflow=7.03 cfs 23,100 cf Discarded=1.05 cfs 22,939 cf Primary=0.27 cfs 147 cf Outflow=1.32 cfs 23,086 cf
<b>Pond P-1B: Isolator Row #1</b>	Peak Elev=49.55' Storage=778 cf Inflow=5.32 cfs 17,484 cf Outflow=5.31 cfs 16,756 cf
<b>Pond P-1D: Underground Infiltration</b>	Peak Elev=47.77' Storage=44,690 cf Inflow=51.50 cfs 173,164 cf Discarded=6.33 cfs 138,948 cf Primary=11.23 cfs 34,216 cf Outflow=17.56 cfs 173,164 cf
<b>Pond P-1E: Infiltration Basin</b>	Peak Elev=48.20' Storage=16,053 cf Inflow=12.43 cfs 40,174 cf Discarded=1.25 cfs 40,174 cf Primary=0.00 cfs 0 cf Outflow=1.25 cfs 40,174 cf
<b>Pond P-2A: UIC #2</b>	Peak Elev=48.72' Storage=3,373 cf Inflow=3.40 cfs 11,534 cf Discarded=0.55 cfs 11,541 cf Primary=0.00 cfs 0 cf Outflow=0.55 cfs 11,541 cf
<b>Pond P-2B: Isolator Row #2</b>	Peak Elev=49.48' Storage=395 cf Inflow=2.16 cfs 7,324 cf Outflow=2.16 cfs 6,951 cf
<b>Pond P-3A: UIC #3</b>	Peak Elev=48.72' Storage=2,902 cf Inflow=2.93 cfs 10,430 cf Discarded=0.48 cfs 10,428 cf Primary=0.00 cfs 0 cf Outflow=0.48 cfs 10,428 cf
<b>Pond P-3B: Isolator Row #3</b>	Peak Elev=49.45' Storage=392 cf Inflow=1.69 cfs 6,221 cf Outflow=1.69 cfs 5,848 cf
<b>Pond P-4A: UIC #4</b>	Peak Elev=49.36' Storage=4,733 cf Inflow=4.79 cfs 16,326 cf Discarded=0.64 cfs 15,721 cf Primary=0.84 cfs 605 cf Outflow=1.48 cfs 16,325 cf
<b>Pond P-4B: Isolator Row #4</b>	Peak Elev=49.49' Storage=396 cf Inflow=2.30 cfs 7,535 cf Outflow=2.30 cfs 7,161 cf
<b>Pond P-5A: UIC #5</b>	Peak Elev=49.04' Storage=4,347 cf Inflow=4.20 cfs 15,095 cf Discarded=0.63 cfs 15,107 cf Primary=0.00 cfs 0 cf Outflow=0.63 cfs 15,107 cf
<b>Pond P-5B: Isolator Row #5</b>	Peak Elev=49.45' Storage=392 cf Inflow=1.71 cfs 6,303 cf Outflow=1.71 cfs 5,930 cf
<b>Pond P-6A: UIC #6</b>	Peak Elev=48.11' Storage=9,513 cf Inflow=8.92 cfs 29,678 cf Discarded=1.21 cfs 29,386 cf Primary=0.46 cfs 273 cf Outflow=1.67 cfs 29,659 cf
<b>Pond P-6B: Isolator Row #6</b>	Peak Elev=48.04' Storage=1,532 cf Inflow=5.14 cfs 17,082 cf Outflow=5.11 cfs 15,649 cf
<b>Link DP-1: Existing Drainage System - Phase 1</b>	Inflow=12.38 cfs 38,240 cf Primary=12.38 cfs 38,240 cf
<b>Link DP-2: Post Road</b>	Inflow=0.84 cfs 2,798 cf Primary=0.84 cfs 2,798 cf

**Total Runoff Area = 559,558 sf Runoff Volume = 328,953 cf Average Runoff Depth = 7.05"**  
**21.69% Pervious = 121,354 sf 78.31% Impervious = 438,205 sf**

**Summary for Subcatchment PR-1A: Subwatershed 1A - Roof A**

Runoff = 1.72 cfs @ 12.09 hrs, Volume= 6,345 cf, Depth= 8.46"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 100-Year Rainfall=8.70"

Area (sf)	CN	Description
9,000	98	Roofs, HSG A
9,000	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-1B: Subwatershed 1B - Parking Lot**

Runoff = 5.32 cfs @ 12.09 hrs, Volume= 17,484 cf, Depth= 6.77"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 100-Year Rainfall=8.70"

Area (sf)	CN	Description
* 23,528	98	Paved parking and sidewalks, HSG A
7,466	39	>75% Grass cover, Good, HSG A
30,994	84	Weighted Average
7,466	39	24.09% Pervious Area
23,528	98	75.91% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-1D: Bldg 3 & 5-12 and Pvt**

Runoff = 51.50 cfs @ 12.09 hrs, Volume= 173,164 cf, Depth= 7.25"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 100-Year Rainfall=8.70"

**2826 Post Road Phase II Modifications - Proposed** Type III 24-hr 100-Year Rainfall=8.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 89

Area (sf)	CN	Description
8,805	32	Woods/grass comb., Good, HSG A
2,001	72	Dirt roads, HSG A
28,102	39	>75% Grass cover, Good, HSG A
113,211	98	Roofs, HSG A
113,868	98	Paved parking, HSG A
15,161	68	<50% Grass cover, Poor, HSG A
1,158	30	Woods, Good, HSG A
1,705	98	Roofs, HSG B
2,111	98	Paved parking, HSG B
353	61	>75% Grass cover, Good, HSG B
286,475	88	Weighted Average
55,580	47	19.40% Pervious Area
230,895	98	80.60% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-1E: Portion of Bldg 12 & Pvt Draining to Basin**

Runoff = 12.43 cfs @ 12.09 hrs, Volume= 40,174 cf, Depth= 6.28"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 100-Year Rainfall=8.70"

Area (sf)	CN	Description
14,109	39	>75% Grass cover, Good, HSG A
21,676	98	Roofs, HSG A
29,598	98	Paved parking, HSG A
3,129	72	Dirt roads, HSG A
1,746	68	<50% Grass cover, Poor, HSG A
2,283	36	Woods, Fair, HSG A
2,244	30	Woods, Good, HSG A
1,931	32	Woods/grass comb., Good, HSG A
76,715	80	Weighted Average
25,442	43	33.16% Pervious Area
51,274	98	66.84% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-1F: Undetained Area**

Runoff = 0.78 cfs @ 12.11 hrs, Volume= 3,001 cf, Depth= 1.79"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 100-Year Rainfall=8.70"

**2826 Post Road Phase II Modifications - Proposed** Type III 24-hr 100-Year Rainfall=8.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 90

Area (sf)	CN	Description
5,393	39	>75% Grass cover, Good, HSG A
10,624	36	Woods, Fair, HSG A
183	61	>75% Grass cover, Good, HSG B
3,966	60	Woods, Fair, HSG B
20,166	42	Weighted Average
20,166	42	100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-2: Area Discharging to Post Road**

Runoff = 0.84 cfs @ 12.09 hrs, Volume= 2,798 cf, Depth= 7.01"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 100-Year Rainfall=8.70"

Area (sf)	CN	Description
829	98	Paved parking, HSG A
572	39	>75% Grass cover, Good, HSG A
2,135	98	Paved parking, HSG D
1,253	80	>75% Grass cover, Good, HSG D
4,789	86	Weighted Average
1,825	67	38.11% Pervious Area
2,964	98	61.89% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-2A: Subwatershed 2A - Roof**

Runoff = 1.24 cfs @ 12.09 hrs, Volume= 4,582 cf, Depth= 8.46"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr 100-Year Rainfall=8.70"

Area (sf)	CN	Description
6,500	98	Roofs, HSG A
6,500	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-2B: Subwatershed 2B - Parking Lot**

Runoff = 2.16 cfs @ 12.09 hrs, Volume= 7,324 cf, Depth= 7.37"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 100-Year Rainfall=8.70"

	Area (sf)	CN	Description
*	10,191	98	Paved parking and sidewalks, HSG A
	1,726	39	>75% Grass cover, Good, HSG A
	11,917	89	Weighted Average
	1,726	39	14.48% Pervious Area
	10,191	98	85.52% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-3A: Subwatershed 3A - Roof**

Runoff = 1.24 cfs @ 12.09 hrs, Volume= 4,582 cf, Depth= 8.46"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 100-Year Rainfall=8.70"

	Area (sf)	CN	Description
	6,500	98	Roofs, HSG A
	6,500	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-3B: Subwatershed 3B - Parking Lot**

Runoff = 1.69 cfs @ 12.09 hrs, Volume= 6,221 cf, Depth= 8.46"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 100-Year Rainfall=8.70"

	Area (sf)	CN	Description
*	8,824	98	Paved parking and sidewalks, HSG A
	8,824	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>



**Summary for Subcatchment PR-4A: Subwatershed 4A - Roof**

Runoff = 2.49 cfs @ 12.09 hrs, Volume= 9,165 cf, Depth= 8.46"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 100-Year Rainfall=8.70"

Area (sf)	CN	Description
13,000	98	Roofs, HSG A
13,000	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-4B: Subwatershed 4B - Parking Lot**

Runoff = 2.30 cfs @ 12.09 hrs, Volume= 7,535 cf, Depth= 6.65"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 100-Year Rainfall=8.70"

Area (sf)	CN	Description
* 10,191	98	Paved parking and sidewalks, HSG A
3,411	39	>75% Grass cover, Good, HSG A
13,602	83	Weighted Average
3,411	39	25.08% Pervious Area
10,191	98	74.92% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-5A: Subwatershed 5A - Roof**

Runoff = 2.49 cfs @ 12.09 hrs, Volume= 9,165 cf, Depth= 8.46"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 100-Year Rainfall=8.70"

Area (sf)	CN	Description
13,000	98	Roofs, HSG A
13,000	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-5B: Subwatershed 5B - Parking Lot**

Runoff = 1.71 cfs @ 12.09 hrs, Volume= 6,303 cf, Depth= 8.46"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 100-Year Rainfall=8.70"

Area (sf)	CN	Description
* 8,940	98	Paved parking and sidewalks, HSG A
8,940	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-6A: Subwatershed 6A - Roof**

Runoff = 3.81 cfs @ 12.09 hrs, Volume= 14,029 cf, Depth= 8.46"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 100-Year Rainfall=8.70"

Area (sf)	CN	Description
19,900	98	Roofs, HSG A
19,900	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-6B: Subwatershed 6B - Parking Lot**

Runoff = 5.14 cfs @ 12.09 hrs, Volume= 17,082 cf, Depth= 7.01"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 100-Year Rainfall=8.70"

Area (sf)	CN	Description
* 23,498	98	Paved parking and sidewalks, HSG A
5,738	39	>75% Grass cover, Good, HSG A
29,236	86	Weighted Average
5,738	39	19.63% Pervious Area
23,498	98	80.37% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Pond P-1A: UIC #1**

Inflow Area = 39,994 sf, 81.33% Impervious, Inflow Depth = 6.93" for 100-Year event  
 Inflow = 7.03 cfs @ 12.09 hrs, Volume= 23,100 cf  
 Outflow = 1.32 cfs @ 12.54 hrs, Volume= 23,086 cf, Atten= 81%, Lag= 27.2 min  
 Discarded = 1.05 cfs @ 12.54 hrs, Volume= 22,939 cf  
 Primary = 0.27 cfs @ 12.54 hrs, Volume= 147 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 49.27' @ 12.54 hrs Surf.Area= 4,161 sf Storage= 7,225 cf

Plug-Flow detention time= 47.7 min calculated for 23,045 cf (100% of inflow)  
 Center-of-Mass det. time= 47.2 min ( 834.2 - 787.0 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	3,108 cf	<b>20.50'W x 202.98'L x 3.50'H Field A</b> 14,564 cf Overall - 5,145 cf Embedded = 9,418 cf x 33.0% Voids
#2A	47.00'	5,145 cf	<b>ADS_StormTech SC-740 +Cap</b> x 112 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 112 Chambers in 4 Rows
		8,253 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=1.05 cfs @ 12.54 hrs HW=49.27' (Free Discharge)  
 ↑1=**Exfiltration** (Exfiltration Controls 1.05 cfs)

**Primary OutFlow** Max=0.26 cfs @ 12.54 hrs HW=49.27' (Free Discharge)  
 ↑2=**Sharp-Crested Rectangular Weir** (Weir Controls 0.26 cfs @ 0.88 fps)

**Summary for Pond P-1B: Isolator Row #1**

Inflow Area = 30,994 sf, 75.91% Impervious, Inflow Depth = 6.77" for 100-Year event  
 Inflow = 5.32 cfs @ 12.09 hrs, Volume= 17,484 cf  
 Outflow = 5.31 cfs @ 12.09 hrs, Volume= 16,756 cf, Atten= 0%, Lag= 0.1 min  
 Primary = 5.31 cfs @ 12.09 hrs, Volume= 16,756 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 49.55' @ 12.09 hrs Surf.Area= 468 sf Storage= 778 cf

Plug-Flow detention time= 38.0 min calculated for 16,726 cf (96% of inflow)  
 Center-of-Mass det. time= 14.5 min ( 804.8 - 790.2 )

**2826 Post Road Phase II Modifications - Proposed** Type III 24-hr 100-Year Rainfall=8.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 95

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	388 cf	<b>6.25'W x 74.82'L x 3.50'H Field A</b> 1,637 cf Overall - 459 cf Embedded = 1,177 cf x 33.0% Voids
#2A	47.00'	459 cf	<b>ADS_StormTech SC-740 +Cap</b> x 10 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		848 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>5.0' long Sharp-Crested Rectangular Weir X 2.00</b> 2 End Contraction(s)

**Primary OutFlow** Max=5.19 cfs @ 12.09 hrs HW=49.55' (Free Discharge)

↑**1=Sharp-Crested Rectangular Weir**(Weir Controls 5.19 cfs @ 1.78 fps)

**Summary for Pond P-1D: Underground Infiltration**

Inflow Area = 286,475 sf, 80.60% Impervious, Inflow Depth = 7.25" for 100-Year event  
 Inflow = 51.50 cfs @ 12.09 hrs, Volume= 173,164 cf  
 Outflow = 17.56 cfs @ 12.37 hrs, Volume= 173,164 cf, Atten= 66%, Lag= 16.9 min  
 Discarded = 6.33 cfs @ 12.37 hrs, Volume= 138,948 cf  
 Primary = 11.23 cfs @ 12.37 hrs, Volume= 34,216 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Peak Elev= 47.77' @ 12.37 hrs Surf.Area= 23,713 sf Storage= 44,690 cf

Plug-Flow detention time= 28.7 min calculated for 172,855 cf (100% of inflow)  
 Center-of-Mass det. time= 28.7 min ( 808.2 - 779.5 )

**2826 Post Road Phase II Modifications - Proposed** Type III 24-hr 100-Year Rainfall=8.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 96

Volume	Invert	Avail.Storage	Storage Description
#1	44.70'	18,217 cf	<b>15.75'W x 1,505.60'L x 3.50'H Crushed Stone</b> 82,996 cf Overall - 27,794 cf Embedded = 55,202 cf x 33.0% Voids
#2	45.20'	1,103 cf	<b>P-1D-A</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 24 Chambers in 3 Rows
#3	45.20'	1,929 cf	<b>P-1D-B</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 42 Chambers in 3 Rows
#4	45.20'	1,240 cf	<b>P-1D-C</b> x 27 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 27 Chambers in 3 Rows
#5	45.20'	965 cf	<b>P-1D-D</b> x 21 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 21 Chambers in 3 Rows
#6	45.20'	1,654 cf	<b>P-1D-E</b> x 36 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 36 Chambers in 3 Rows
#7	45.20'	1,654 cf	<b>P-1D-F</b> x 36 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 36 Chambers in 3 Rows
#8	45.20'	1,103 cf	<b>P-1D-G</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 24 Chambers in 3 Rows
#9	45.20'	1,286 cf	<b>P-1D-H</b> x 28 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 28 Chambers in 2 Rows
#10	45.20'	184 cf	<b>P-1D-H</b> x 4 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#11	45.20'	413 cf	<b>P-1D-H</b> x 9 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#12	45.20'	2,067 cf	<b>P-1D-I</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 45 Chambers in 3 Rows
#13	45.20'	1,929 cf	<b>P-1D-J</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 42 Chambers in 3 Rows
#14	45.20'	2,067 cf	<b>P-1D-K</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap

**2826 Post Road Phase II Modifications - Proposed** Type III 24-hr 100-Year Rainfall=8.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 97

#15	45.20'	1,929 cf	45 Chambers in 3 Rows <b>P-1D-L</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#16	45.20'	2,067 cf	42 Chambers in 3 Rows <b>P-1D-M</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#17	45.20'	1,929 cf	45 Chambers in 3 Rows <b>P-1D-N</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#18	45.20'	2,067 cf	42 Chambers in 3 Rows <b>P-1D-O</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#19	45.20'	1,103 cf	45 Chambers in 3 Rows <b>P-1D-P</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#20	45.20'	1,103 cf	24 Chambers in 3 Rows <b>P-1D-Q</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#21	46.25'	134 cf	<b>18.0" Round Pipe CB5-DMH1</b> -Impervious L= 76.0' S= 0.0031 '/'
#22	45.70'	205 cf	<b>18.0" Round Pipe CB5-CB6</b> -Impervious L= 116.0' S= 0.0025 '/'
#23	46.10'	93 cf	<b>12.0" Round Pipe CB6-CB7</b> -Impervious L= 118.0' S= 0.0033 '/'
#24	46.50'	101 cf	<b>12.0" Round Pipe CB33-CB40</b> -Impervious L= 128.0' S= 0.0098 '/'
#25	46.10'	83 cf	<b>12.0" Round Pipe CB8-CB9</b> -Impervious L= 106.0' S= 0.0036 '/'
#26	45.70'	187 cf	<b>18.0" Round Pipe CB9-CB10</b> -Impervious L= 106.0' S= 0.0027 '/'
#27	46.20'	91 cf	<b>12.0" Round Pipe CB10-CB11</b> -Impervious L= 116.0' S= 0.0025 '/'
#28	45.30'	540 cf	<b>24.0" Round 24" Header Pipe</b> -Impervious L= 172.0'
#29	45.30'	855 cf	<b>4.00'D x 4.00'H CBs</b> x 17 -Impervious
#30	46.00'	50 cf	<b>4.00'D x 4.00'H CB-6</b> -Impervious
#31	46.50'	50 cf	<b>4.00'D x 4.00'H CB-7</b> -Impervious
#32	47.80'	50 cf	<b>4.00'D x 4.00'H CB-40</b> -Impervious
#33	46.50'	50 cf	<b>4.00'D x 4.00'H CB-8</b> -Impervious
#34	46.00'	50 cf	<b>4.00'D x 4.00'H CB-9</b> -Impervious
#35	46.50'	50 cf	<b>4.00'D x 4.00'H CB-11</b> -Impervious
#36	46.50'	50 cf	<b>4.00'D x 4.00'H CB-33</b> -Impervious
		48,651 cf	Total Available Storage

**2826 Post Road Phase II Modifications - Proposed** Type III 24-hr 100-Year Rainfall=8.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 98

Device	Routing	Invert	Outlet Devices
#1	Discarded	44.70'	<b>8.270 in/hr Exfiltration over Wetted area</b> Phase-In= 0.01'
#2	Device 4	45.70'	<b>15.0" W x 21.0" H Vert. Orifice/Grate</b> C= 0.600
#3	Device 4	48.10'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)
#4	Primary	31.40'	<b>24.0" Round Culvert</b> L= 25.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 31.40' / 31.00' S= 0.0160 '/ Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 3.14 sf

**Discarded OutFlow** Max=6.32 cfs @ 12.37 hrs HW=47.77' (Free Discharge)

↑1=**Exfiltration** (Exfiltration Controls 6.32 cfs)

**Primary OutFlow** Max=11.20 cfs @ 12.37 hrs HW=47.77' (Free Discharge)

↑4=**Culvert** (Passes 11.20 cfs of 46.81 cfs potential flow)

↑2=**Orifice/Grate** (Orifice Controls 11.20 cfs @ 5.12 fps)

↑3=**Sharp-Crested Rectangular Weir** ( Controls 0.00 cfs)

**Summary for Pond P-1E: Infiltration Basin**

Inflow Area =	76,715 sf, 66.84% Impervious,	Inflow Depth = 6.28"	for 100-Year event
Inflow =	12.43 cfs @ 12.09 hrs,	Volume=	40,174 cf
Outflow =	1.25 cfs @ 12.92 hrs,	Volume=	40,174 cf, Atten= 90%, Lag= 49.8 min
Discarded =	1.25 cfs @ 12.92 hrs,	Volume=	40,174 cf
Primary =	0.00 cfs @ 0.00 hrs,	Volume=	0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Peak Elev= 48.20' @ 12.92 hrs Surf.Area= 6,538 sf Storage= 16,053 cf

Plug-Flow detention time= 118.6 min calculated for 40,174 cf (100% of inflow)  
Center-of-Mass det. time= 118.6 min ( 918.3 - 799.8 )

Volume	Invert	Avail.Storage	Storage Description
#1	45.00'	21,635 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
45.00	3,597	0	0
46.00	4,453	4,025	4,025
47.00	5,366	4,910	8,935
48.00	6,336	5,851	14,786
49.00	7,362	6,849	21,635

Device	Routing	Invert	Outlet Devices
#1	Discarded	45.00'	<b>8.270 in/hr Exfiltration over Surface area</b> Phase-In= 0.01'
#2	Primary	48.20'	<b>35.0' long x 8.0' breadth Broad-Crested Rectangular Weir</b> Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.43 2.54 2.70 2.69 2.68 2.68 2.66 2.64 2.64 2.64 2.65 2.65 2.66 2.66 2.68 2.70 2.74

**Discarded OutFlow** Max=1.25 cfs @ 12.92 hrs HW=48.20' (Free Discharge)  
 ↑1=Exfiltration (Exfiltration Controls 1.25 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=45.00' (Free Discharge)  
 ↑2=Broad-Crested Rectangular Weir( Controls 0.00 cfs)

**Summary for Pond P-2A: UIC #2**

Inflow Area = 18,417 sf, 90.63% Impervious, Inflow Depth = 7.51" for 100-Year event  
 Inflow = 3.40 cfs @ 12.09 hrs, Volume= 11,534 cf  
 Outflow = 0.55 cfs @ 12.57 hrs, Volume= 11,541 cf, Atten= 84%, Lag= 28.8 min  
 Discarded = 0.55 cfs @ 12.57 hrs, Volume= 11,541 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 48.72' @ 12.57 hrs Surf.Area= 2,352 sf Storage= 3,373 cf

Plug-Flow detention time= (not calculated: outflow precedes inflow)  
 Center-of-Mass det. time= 38.8 min ( 812.7 - 773.8 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	1,762 cf	<b>34.75'W x 67.70'L x 3.50'H Field A</b> 8,234 cf Overall - 2,894 cf Embedded = 5,339 cf x 33.0% Voids
#2A	47.00'	2,894 cf	<b>ADS_StormTech SC-740 +Cap</b> x 63 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 63 Chambers in 7 Rows
		4,656 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.55 cfs @ 12.57 hrs HW=48.72' (Free Discharge)  
 ↑1=Exfiltration (Exfiltration Controls 0.55 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)  
 ↑2=Sharp-Crested Rectangular Weir( Controls 0.00 cfs)

**Summary for Pond P-2B: Isolator Row #2**

Inflow Area = 11,917 sf, 85.52% Impervious, Inflow Depth = 7.37" for 100-Year event  
 Inflow = 2.16 cfs @ 12.09 hrs, Volume= 7,324 cf  
 Outflow = 2.16 cfs @ 12.09 hrs, Volume= 6,951 cf, Atten= 0%, Lag= 0.1 min  
 Primary = 2.16 cfs @ 12.09 hrs, Volume= 6,951 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3



**2826 Post Road Phase II Modifications - Proposed** Type III 24-hr 100-Year Rainfall=8.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 100

Peak Elev= 49.48' @ 12.09 hrs Surf.Area= 245 sf Storage= 395 cf

Plug-Flow detention time= 47.7 min calculated for 6,939 cf (95% of inflow)  
Center-of-Mass det. time= 19.5 min ( 796.0 - 776.6 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap x 5</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=2.11 cfs @ 12.09 hrs HW=49.48' (Free Discharge)  
 ↳ **1=Sharp-Crested Rectangular Weir**(Weir Controls 2.11 cfs @ 1.56 fps)

**Summary for Pond P-3A: UIC #3**

Inflow Area = 15,324 sf, 100.00% Impervious, Inflow Depth = 8.17" for 100-Year event  
 Inflow = 2.93 cfs @ 12.09 hrs, Volume= 10,430 cf  
 Outflow = 0.48 cfs @ 12.56 hrs, Volume= 10,428 cf, Atten= 84%, Lag= 28.4 min  
 Discarded = 0.48 cfs @ 12.56 hrs, Volume= 10,428 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 48.72' @ 12.56 hrs Surf.Area= 2,031 sf Storage= 2,902 cf

Plug-Flow detention time= 36.1 min calculated for 10,428 cf (100% of inflow)  
 Center-of-Mass det. time= 36.0 min ( 793.6 - 757.6 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	1,527 cf	<b>30.00'W x 67.70'L x 3.50'H Field A</b> 7,108 cf Overall - 2,481 cf Embedded = 4,627 cf x 33.0% Voids
#2A	47.00'	2,481 cf	<b>ADS_StormTech SC-740 +Cap x 54</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 54 Chambers in 6 Rows
		4,008 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.48 cfs @ 12.56 hrs HW=48.72' (Free Discharge)  
 ↑1=Exfiltration (Exfiltration Controls 0.48 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)  
 ↑2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

**Summary for Pond P-3B: Isolator Row #3**

Inflow Area = 8,824 sf, 100.00% Impervious, Inflow Depth = 8.46" for 100-Year event  
 Inflow = 1.69 cfs @ 12.09 hrs, Volume= 6,221 cf  
 Outflow = 1.69 cfs @ 12.09 hrs, Volume= 5,848 cf, Atten= 0%, Lag= 0.1 min  
 Primary = 1.69 cfs @ 12.09 hrs, Volume= 5,848 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 49.45' @ 12.09 hrs Surf.Area= 245 sf Storage= 392 cf

Plug-Flow detention time= 64.6 min calculated for 5,837 cf (94% of inflow)  
 Center-of-Mass det. time= 31.0 min ( 771.2 - 740.2 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap x 5</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=1.64 cfs @ 12.09 hrs HW=49.44' (Free Discharge)  
 ↑1=Sharp-Crested Rectangular Weir (Weir Controls 1.64 cfs @ 1.43 fps)

**Summary for Pond P-4A: UIC #4**

Inflow Area = 26,602 sf, 87.18% Impervious, Inflow Depth = 7.36" for 100-Year event  
 Inflow = 4.79 cfs @ 12.09 hrs, Volume= 16,326 cf  
 Outflow = 1.48 cfs @ 12.42 hrs, Volume= 16,325 cf, Atten= 69%, Lag= 19.6 min  
 Discarded = 0.64 cfs @ 12.42 hrs, Volume= 15,721 cf  
 Primary = 0.84 cfs @ 12.42 hrs, Volume= 605 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 49.36' @ 12.42 hrs Surf.Area= 2,674 sf Storage= 4,733 cf

Plug-Flow detention time= 47.0 min calculated for 16,325 cf (100% of inflow)  
 Center-of-Mass det. time= 46.9 min ( 817.3 - 770.3 )

**2826 Post Road Phase II Modifications - Proposed** Type III 24-hr 100-Year Rainfall=8.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 102

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	1,997 cf	<b>39.50'W x 67.70'L x 3.50'H Field A</b> 9,359 cf Overall - 3,308 cf Embedded = 6,051 cf x 33.0% Voids
#2A	47.00'	3,308 cf	<b>ADS_StormTech SC-740 +Cap</b> x 72 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 72 Chambers in 8 Rows
		5,305 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.64 cfs @ 12.42 hrs HW=49.35' (Free Discharge)

↑**1=Exfiltration** (Exfiltration Controls 0.64 cfs)

**Primary OutFlow** Max=0.79 cfs @ 12.42 hrs HW=49.35' (Free Discharge)

↑**2=Sharp-Crested Rectangular Weir** (Weir Controls 0.79 cfs @ 1.29 fps)

**Summary for Pond P-4B: Isolator Row #4**

Inflow Area = 13,602 sf, 74.92% Impervious, Inflow Depth = 6.65" for 100-Year event  
 Inflow = 2.30 cfs @ 12.09 hrs, Volume= 7,535 cf  
 Outflow = 2.30 cfs @ 12.09 hrs, Volume= 7,161 cf, Atten= 0%, Lag= 0.1 min  
 Primary = 2.30 cfs @ 12.09 hrs, Volume= 7,161 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3

Peak Elev= 49.49' @ 12.09 hrs Surf.Area= 245 sf Storage= 396 cf

Plug-Flow detention time= 43.6 min calculated for 7,148 cf (95% of inflow)

Center-of-Mass det. time= 16.2 min ( 808.9 - 792.7 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap</b> x 5 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=2.25 cfs @ 12.09 hrs HW=49.49' (Free Discharge)

↑**1=Sharp-Crested Rectangular Weir** (Weir Controls 2.25 cfs @ 1.59 fps)

**Summary for Pond P-5A: UIC #5**

Inflow Area = 21,940 sf, 100.00% Impervious, Inflow Depth = 8.26" for 100-Year event  
 Inflow = 4.20 cfs @ 12.09 hrs, Volume= 15,095 cf  
 Outflow = 0.63 cfs @ 12.58 hrs, Volume= 15,107 cf, Atten= 85%, Lag= 29.8 min  
 Discarded = 0.63 cfs @ 12.58 hrs, Volume= 15,107 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 49.04' @ 12.58 hrs Surf.Area= 2,681 sf Storage= 4,347 cf

Plug-Flow detention time= (not calculated: outflow precedes inflow)  
 Center-of-Mass det. time= 42.6 min ( 794.8 - 752.3 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	2,004 cf	<b>44.25"W x 60.58"L x 3.50"H Field A</b> 9,382 cf Overall - 3,308 cf Embedded = 6,074 cf x 33.0% Voids
#2A	47.00'	3,308 cf	<b>ADS_StormTech SC-740 +Cap</b> x 72 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 72 Chambers in 9 Rows
		5,312 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.63 cfs @ 12.58 hrs HW=49.04' (Free Discharge)  
 ↑1=Exfiltration (Exfiltration Controls 0.63 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)  
 ↑2=Sharp-Crested Rectangular Weir ( Controls 0.00 cfs)

**Summary for Pond P-5B: Isolator Row #5**

Inflow Area = 8,940 sf, 100.00% Impervious, Inflow Depth = 8.46" for 100-Year event  
 Inflow = 1.71 cfs @ 12.09 hrs, Volume= 6,303 cf  
 Outflow = 1.71 cfs @ 12.09 hrs, Volume= 5,930 cf, Atten= 0%, Lag= 0.1 min  
 Primary = 1.71 cfs @ 12.09 hrs, Volume= 5,930 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 49.45' @ 12.09 hrs Surf.Area= 245 sf Storage= 392 cf

Plug-Flow detention time= 63.9 min calculated for 5,919 cf (94% of inflow)  
 Center-of-Mass det. time= 30.7 min ( 770.9 - 740.2 )

**2826 Post Road Phase II Modifications - Proposed** Type III 24-hr 100-Year Rainfall=8.70"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 104

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap</b> x 5 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=1.66 cfs @ 12.09 hrs HW=49.44' (Free Discharge)

↑**1=Sharp-Crested Rectangular Weir**(Weir Controls 1.66 cfs @ 1.44 fps)

**Summary for Pond P-6A: UIC #6**

Inflow Area =	49,136 sf, 88.32% Impervious,	Inflow Depth = 7.25" for 100-Year event
Inflow =	8.92 cfs @ 12.09 hrs,	Volume= 29,678 cf
Outflow =	1.67 cfs @ 12.54 hrs,	Volume= 29,659 cf, Atten= 81%, Lag= 27.1 min
Discarded =	1.21 cfs @ 12.54 hrs,	Volume= 29,386 cf
Primary =	0.46 cfs @ 12.54 hrs,	Volume= 273 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3

Peak Elev= 48.11' @ 12.54 hrs Surf.Area= 5,074 sf Storage= 9,513 cf

Plug-Flow detention time= 54.7 min calculated for 29,659 cf (100% of inflow)

Center-of-Mass det. time= 54.2 min ( 831.9 - 777.7 )

Volume	Invert	Avail.Storage	Storage Description
#1A	45.00'	3,738 cf	<b>34.75'W x 146.02'L x 3.50'H Field A</b> 17,759 cf Overall - 6,432 cf Embedded = 11,328 cf x 33.0% Voids
#2A	45.50'	6,432 cf	<b>ADS_StormTech SC-740 +Cap</b> x 140 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 140 Chambers in 7 Rows
		10,170 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	45.00'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	48.00'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=1.21 cfs @ 12.54 hrs HW=48.11' (Free Discharge)

↑**1=Exfiltration** (Exfiltration Controls 1.21 cfs)

**Primary OutFlow** Max=0.44 cfs @ 12.54 hrs HW=48.11' (Free Discharge)

↑**2=Sharp-Crested Rectangular Weir**(Weir Controls 0.44 cfs @ 1.06 fps)

**Summary for Pond P-6B: Isolator Row #6**

Inflow Area = 29,236 sf, 80.37% Impervious, Inflow Depth = 7.01" for 100-Year event  
 Inflow = 5.14 cfs @ 12.09 hrs, Volume= 17,082 cf  
 Outflow = 5.11 cfs @ 12.09 hrs, Volume= 15,649 cf, Atten= 1%, Lag= 0.2 min  
 Primary = 5.11 cfs @ 12.09 hrs, Volume= 15,649 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 48.04' @ 12.09 hrs Surf.Area= 913 sf Storage= 1,532 cf

Plug-Flow detention time= 68.3 min calculated for 15,621 cf (91% of inflow)  
 Center-of-Mass det. time= 26.3 min ( 811.3 - 785.0 )

Volume	Invert	Avail.Storage	Storage Description
#1A	45.00'	751 cf	<b>6.25'W x 146.02'L x 3.50'H Field A</b> 3,194 cf Overall - 919 cf Embedded = 2,275 cf x 33.0% Voids
#2A	45.50'	919 cf	<b>ADS_StormTech SC-740 +Cap x 20</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		1,670 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	47.75'	<b>5.0' long Sharp-Crested Rectangular Weir X 2.00</b> 2 End Contraction(s)

**Primary OutFlow** Max=5.00 cfs @ 12.09 hrs HW=48.04' (Free Discharge)  
 ↑#1=Sharp-Crested Rectangular Weir (Weir Controls 5.00 cfs @ 1.76 fps)

**Summary for Link DP-1: Existing Drainage System - Phase 1**

Inflow Area = 554,769 sf, 78.45% Impervious, Inflow Depth = 0.83" for 100-Year event  
 Inflow = 12.38 cfs @ 12.40 hrs, Volume= 38,240 cf  
 Primary = 12.38 cfs @ 12.40 hrs, Volume= 38,240 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs




**Summary for Link DP-2: Post Road**

Inflow Area = 4,789 sf, 61.89% Impervious, Inflow Depth = 7.01" for 100-Year event  
 Inflow = 0.84 cfs @ 12.09 hrs, Volume= 2,798 cf  
 Primary = 0.84 cfs @ 12.09 hrs, Volume= 2,798 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs

**ATTACHMENT 3**

**MODIFIED WATER QUALITY CALCULATIONS**



**Routing Diagram for 2826 Post Road Phase II Modifications - Proposed**

Prepared by {enter your company name here}, Printed 10/6/2022  
 HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC



## 2826 Post Road Phase II Modifications - Proposed

Prepared by {enter your company name here}

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Printed 10/6/2022

Page 2

### Area Listing (all nodes)

Area (sq-ft)	CN	Description (subcatchment-numbers)
16,907	68	<50% Grass cover, Poor, HSG A (PR-1D, PR-1E)
66,517	39	>75% Grass cover, Good, HSG A (PR-1B, PR-1D, PR-1E, PR-1F, PR-2, PR-2B, PR-4B, PR-6B)
536	61	>75% Grass cover, Good, HSG B (PR-1D, PR-1F)
1,253	80	>75% Grass cover, Good, HSG D (PR-2)
5,130	72	Dirt roads, HSG A (PR-1D, PR-1E)
85,172	98	Paved parking and sidewalks, HSG A (PR-1B, PR-2B, PR-3B, PR-4B, PR-5B, PR-6B)
144,295	98	Paved parking, HSG A (PR-1D, PR-1E, PR-2)
2,111	98	Paved parking, HSG B (PR-1D)
2,135	98	Paved parking, HSG D (PR-2)
202,787	98	Roofs, HSG A (PR-1A, PR-1D, PR-1E, PR-2A, PR-3A, PR-4A, PR-5A, PR-6A)
1,705	98	Roofs, HSG B (PR-1D)
12,907	36	Woods, Fair, HSG A (PR-1E, PR-1F)
3,966	60	Woods, Fair, HSG B (PR-1F)
3,402	30	Woods, Good, HSG A (PR-1D, PR-1E)
10,736	32	Woods/grass comb., Good, HSG A (PR-1D, PR-1E)
<b>559,558</b>	<b>86</b>	<b>TOTAL AREA</b>

## 2826 Post Road Phase II Modifications - Proposed

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 3

### Soil Listing (all nodes)

Area (sq-ft)	Soil Group	Subcatchment Numbers
547,852	HSG A	PR-1A, PR-1B, PR-1D, PR-1E, PR-1F, PR-2, PR-2A, PR-2B, PR-3A, PR-3B, PR-4A, PR-4B, PR-5A, PR-5B, PR-6A, PR-6B
8,318	HSG B	PR-1D, PR-1F
0	HSG C	
3,388	HSG D	PR-2
0	Other	
<b>559,558</b>		<b>TOTAL AREA</b>

## 2826 Post Road Phase II Modifications - Proposed

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 4

### Ground Covers (all nodes)

HSG-A (sq-ft)	HSG-B (sq-ft)	HSG-C (sq-ft)	HSG-D (sq-ft)	Other (sq-ft)	Total (sq-ft)	Ground Cover
16,907	0	0	0	0	16,907	<50% Grass cover, Poor
66,517	536	0	1,253	0	68,307	>75% Grass cover, Good
5,130	0	0	0	0	5,130	Dirt roads
144,295	2,111	0	2,135	0	148,541	Paved parking
85,172	0	0	0	0	85,172	Paved parking and sidewalks
202,787	1,705	0	0	0	204,492	Roofs
12,907	3,966	0	0	0	16,873	Woods, Fair
3,402	0	0	0	0	3,402	Woods, Good
10,736	0	0	0	0	10,736	Woods/grass comb., Good
<b>547,852</b>	<b>8,318</b>	<b>0</b>	<b>3,388</b>	<b>0</b>	<b>559,558</b>	<b>TOTAL AREA</b>

## 2826 Post Road Phase II Modifications - Proposed

Prepared by {enter your company name here}

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Printed 10/6/2022

Page 5

### Pipe Listing (all nodes)

Line#	Node Number	In-Invert (feet)	Out-Invert (feet)	Length (feet)	Slope (ft/ft)	n	Diam/Width (inches)	Height (inches)	Inside-Fill (inches)
1	P-1D	31.40	31.00	25.0	0.0160	0.012	24.0	0.0	0.0

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr WQV Rainfall=1.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 6

Time span=0.00-28.00 hrs, dt=0.05 hrs, 561 points  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

**SubcatchmentPR-1A: Subwatershed 1A** - Runoff Area=9,000 sf 100.00% Impervious Runoff Depth=0.99"  
Tc=6.0 min CN=98 Runoff=0.22 cfs 739 cf

**SubcatchmentPR-1B: Subwatershed 1B** - Runoff Area=30,994 sf 75.91% Impervious Runoff Depth=0.25"  
Tc=6.0 min CN=84 Runoff=0.17 cfs 636 cf

**SubcatchmentPR-1D: Bldg 3 & 5-12 and** Runoff Area=286,475 sf 80.60% Impervious Runoff Depth=0.38"  
Tc=6.0 min CN=88 Runoff=2.68 cfs 8,960 cf

**SubcatchmentPR-1E: Portion of Bldg 12 &** Runoff Area=76,715 sf 66.84% Impervious Runoff Depth=0.15"  
Tc=6.0 min CN=80 Runoff=0.18 cfs 979 cf

**SubcatchmentPR-1F: Undetained Area** Runoff Area=20,166 sf 0.00% Impervious Runoff Depth=0.00"  
Tc=6.0 min CN=42 Runoff=0.00 cfs 0 cf

**SubcatchmentPR-2: Area Discharging to** Runoff Area=4,789 sf 61.89% Impervious Runoff Depth=0.31"  
Tc=6.0 min CN=86 Runoff=0.03 cfs 122 cf

**SubcatchmentPR-2A: Subwatershed 2A** - Runoff Area=6,500 sf 100.00% Impervious Runoff Depth=0.99"  
Tc=6.0 min CN=98 Runoff=0.16 cfs 534 cf

**SubcatchmentPR-2B: Subwatershed 2B** - Runoff Area=11,917 sf 85.52% Impervious Runoff Depth=0.41"  
Tc=6.0 min CN=89 Runoff=0.13 cfs 412 cf

**SubcatchmentPR-3A: Subwatershed 3A** - Runoff Area=6,500 sf 100.00% Impervious Runoff Depth=0.99"  
Tc=6.0 min CN=98 Runoff=0.16 cfs 534 cf

**SubcatchmentPR-3B: Subwatershed 3B** - Runoff Area=8,824 sf 100.00% Impervious Runoff Depth=0.99"  
Tc=6.0 min CN=98 Runoff=0.22 cfs 725 cf

**SubcatchmentPR-4A: Subwatershed 4A** - Runoff Area=13,000 sf 100.00% Impervious Runoff Depth=0.99"  
Tc=6.0 min CN=98 Runoff=0.32 cfs 1,068 cf

**SubcatchmentPR-4B: Subwatershed 4B** - Runoff Area=13,602 sf 74.92% Impervious Runoff Depth=0.22"  
Tc=6.0 min CN=83 Runoff=0.06 cfs 249 cf

**SubcatchmentPR-5A: Subwatershed 5A** - Runoff Area=13,000 sf 100.00% Impervious Runoff Depth=0.99"  
Tc=6.0 min CN=98 Runoff=0.32 cfs 1,068 cf

**SubcatchmentPR-5B: Subwatershed 5B** - Runoff Area=8,940 sf 100.00% Impervious Runoff Depth=0.99"  
Tc=6.0 min CN=98 Runoff=0.22 cfs 734 cf

**SubcatchmentPR-6A: Subwatershed 6A** - Runoff Area=19,900 sf 100.00% Impervious Runoff Depth=0.99"  
Tc=6.0 min CN=98 Runoff=0.49 cfs 1,635 cf

**SubcatchmentPR-6B: Subwatershed 6B** - Runoff Area=29,236 sf 80.37% Impervious Runoff Depth=0.31"  
Tc=6.0 min CN=86 Runoff=0.21 cfs 744 cf

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr WQV Rainfall=1.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 7

<b>Pond P-1A: UIC #1</b>	Peak Elev=46.51' Storage=13 cf Inflow=0.22 cfs 739 cf Discarded=0.21 cfs 739 cf Primary=0.00 cfs 0 cf Outflow=0.21 cfs 739 cf
<b>Pond P-1B: Isolator Row #1</b>	Peak Elev=48.84' Storage=636 cf Inflow=0.17 cfs 636 cf Outflow=0.00 cfs 0 cf
<b>Pond P-1D: Underground Infiltration</b>	Peak Elev=44.74' Storage=301 cf Inflow=2.68 cfs 8,960 cf Discarded=2.48 cfs 8,960 cf Primary=0.00 cfs 0 cf Outflow=2.48 cfs 8,960 cf
<b>Pond P-1E: Infiltration Basin</b>	Peak Elev=45.01' Storage=33 cf Inflow=0.18 cfs 979 cf Discarded=0.16 cfs 979 cf Primary=0.00 cfs 0 cf Outflow=0.16 cfs 979 cf
<b>Pond P-2A: UIC #2</b>	Peak Elev=46.51' Storage=9 cf Inflow=0.16 cfs 571 cf Discarded=0.15 cfs 571 cf Primary=0.00 cfs 0 cf Outflow=0.15 cfs 571 cf
<b>Pond P-2B: Isolator Row #2</b>	Peak Elev=49.25' Storage=375 cf Inflow=0.13 cfs 412 cf Outflow=0.00 cfs 37 cf
<b>Pond P-3A: UIC #3</b>	Peak Elev=46.51' Storage=10 cf Inflow=0.18 cfs 880 cf Discarded=0.16 cfs 880 cf Primary=0.00 cfs 0 cf Outflow=0.16 cfs 880 cf
<b>Pond P-3B: Isolator Row #3</b>	Peak Elev=49.28' Storage=377 cf Inflow=0.22 cfs 725 cf Outflow=0.11 cfs 346 cf
<b>Pond P-4A: UIC #4</b>	Peak Elev=46.52' Storage=18 cf Inflow=0.32 cfs 1,068 cf Discarded=0.31 cfs 1,068 cf Primary=0.00 cfs 0 cf Outflow=0.31 cfs 1,068 cf
<b>Pond P-4B: Isolator Row #4</b>	Peak Elev=48.29' Storage=249 cf Inflow=0.06 cfs 249 cf Outflow=0.00 cfs 0 cf
<b>Pond P-5A: UIC #5</b>	Peak Elev=46.52' Storage=18 cf Inflow=0.32 cfs 1,420 cf Discarded=0.31 cfs 1,420 cf Primary=0.00 cfs 0 cf Outflow=0.31 cfs 1,420 cf
<b>Pond P-5B: Isolator Row #5</b>	Peak Elev=49.28' Storage=377 cf Inflow=0.22 cfs 734 cf Outflow=0.12 cfs 352 cf
<b>Pond P-6A: UIC #6</b>	Peak Elev=45.02' Storage=28 cf Inflow=0.49 cfs 1,635 cf Discarded=0.47 cfs 1,635 cf Primary=0.00 cfs 0 cf Outflow=0.47 cfs 1,635 cf
<b>Pond P-6B: Isolator Row #6</b>	Peak Elev=46.43' Storage=744 cf Inflow=0.21 cfs 744 cf Outflow=0.00 cfs 0 cf
<b>Link DP-1: Existing Drainage System - Phase 1</b>	Inflow=0.00 cfs 0 cf Primary=0.00 cfs 0 cf
<b>Link DP-2: Post Road</b>	Inflow=0.03 cfs 122 cf Primary=0.03 cfs 122 cf

**Total Runoff Area = 559,558 sf Runoff Volume = 19,139 cf Average Runoff Depth = 0.41"**  
**21.69% Pervious = 121,354 sf 78.31% Impervious = 438,205 sf**

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr WQV Rainfall=1.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 8

**Summary for Subcatchment PR-1A: Subwatershed 1A - Roof A**

Runoff = 0.22 cfs @ 12.09 hrs, Volume= 739 cf, Depth= 0.99"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr WQV Rainfall=1.20"

Area (sf)	CN	Description
9,000	98	Roofs, HSG A
9,000	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-1B: Subwatershed 1B - Parking Lot**

Runoff = 0.17 cfs @ 12.11 hrs, Volume= 636 cf, Depth= 0.25"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr WQV Rainfall=1.20"

Area (sf)	CN	Description
* 23,528	98	Paved parking and sidewalks, HSG A
7,466	39	>75% Grass cover, Good, HSG A
30,994	84	Weighted Average
7,466	39	24.09% Pervious Area
23,528	98	75.91% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-1D: Bldg 3 & 5-12 and Pvt**

Runoff = 2.68 cfs @ 12.10 hrs, Volume= 8,960 cf, Depth= 0.38"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr WQV Rainfall=1.20"

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr WQV Rainfall=1.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 9

Area (sf)	CN	Description
8,805	32	Woods/grass comb., Good, HSG A
2,001	72	Dirt roads, HSG A
28,102	39	>75% Grass cover, Good, HSG A
113,211	98	Roofs, HSG A
113,868	98	Paved parking, HSG A
15,161	68	<50% Grass cover, Poor, HSG A
1,158	30	Woods, Good, HSG A
1,705	98	Roofs, HSG B
2,111	98	Paved parking, HSG B
353	61	>75% Grass cover, Good, HSG B
286,475	88	Weighted Average
55,580	47	19.40% Pervious Area
230,895	98	80.60% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-1E: Portion of Bldg 12 & Pvt Draining to Basin**

Runoff = 0.18 cfs @ 12.14 hrs, Volume= 979 cf, Depth= 0.15"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr WQV Rainfall=1.20"

Area (sf)	CN	Description
14,109	39	>75% Grass cover, Good, HSG A
21,676	98	Roofs, HSG A
29,598	98	Paved parking, HSG A
3,129	72	Dirt roads, HSG A
1,746	68	<50% Grass cover, Poor, HSG A
2,283	36	Woods, Fair, HSG A
2,244	30	Woods, Good, HSG A
1,931	32	Woods/grass comb., Good, HSG A
76,715	80	Weighted Average
25,442	43	33.16% Pervious Area
51,274	98	66.84% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-1F: Undetained Area**

Runoff = 0.00 cfs @ 0.00 hrs, Volume= 0 cf, Depth= 0.00"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr WQV Rainfall=1.20"



**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr WQV Rainfall=1.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 10

Area (sf)	CN	Description
5,393	39	>75% Grass cover, Good, HSG A
10,624	36	Woods, Fair, HSG A
183	61	>75% Grass cover, Good, HSG B
3,966	60	Woods, Fair, HSG B
20,166	42	Weighted Average
20,166	42	100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-2: Area Discharging to Post Road**

Runoff = 0.03 cfs @ 12.10 hrs, Volume= 122 cf, Depth= 0.31"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr WQV Rainfall=1.20"

Area (sf)	CN	Description
829	98	Paved parking, HSG A
572	39	>75% Grass cover, Good, HSG A
2,135	98	Paved parking, HSG D
1,253	80	>75% Grass cover, Good, HSG D
4,789	86	Weighted Average
1,825	67	38.11% Pervious Area
2,964	98	61.89% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry,</b>

**Summary for Subcatchment PR-2A: Subwatershed 2A - Roof**

Runoff = 0.16 cfs @ 12.09 hrs, Volume= 534 cf, Depth= 0.99"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr WQV Rainfall=1.20"

Area (sf)	CN	Description
6,500	98	Roofs, HSG A
6,500	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr WQV Rainfall=1.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 11

**Summary for Subcatchment PR-2B: Subwatershed 2B - Parking Lot**

Runoff = 0.13 cfs @ 12.10 hrs, Volume= 412 cf, Depth= 0.41"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr WQV Rainfall=1.20"

	Area (sf)	CN	Description
*	10,191	98	Paved parking and sidewalks, HSG A
	1,726	39	>75% Grass cover, Good, HSG A
	11,917	89	Weighted Average
	1,726	39	14.48% Pervious Area
	10,191	98	85.52% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry, SEG A

**Summary for Subcatchment PR-3A: Subwatershed 3A - Roof**

Runoff = 0.16 cfs @ 12.09 hrs, Volume= 534 cf, Depth= 0.99"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr WQV Rainfall=1.20"

	Area (sf)	CN	Description
	6,500	98	Roofs, HSG A
	6,500	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry, SEG A

**Summary for Subcatchment PR-3B: Subwatershed 3B - Parking Lot**

Runoff = 0.22 cfs @ 12.09 hrs, Volume= 725 cf, Depth= 0.99"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr WQV Rainfall=1.20"

	Area (sf)	CN	Description
*	8,824	98	Paved parking and sidewalks, HSG A
	8,824	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry, SEG A

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr WQV Rainfall=1.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 12

**Summary for Subcatchment PR-4A: Subwatershed 4A - Roof**

Runoff = 0.32 cfs @ 12.09 hrs, Volume= 1,068 cf, Depth= 0.99"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr WQV Rainfall=1.20"

Area (sf)	CN	Description
13,000	98	Roofs, HSG A
13,000	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-4B: Subwatershed 4B - Parking Lot**

Runoff = 0.06 cfs @ 12.11 hrs, Volume= 249 cf, Depth= 0.22"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr WQV Rainfall=1.20"

Area (sf)	CN	Description
* 10,191	98	Paved parking and sidewalks, HSG A
3,411	39	>75% Grass cover, Good, HSG A
13,602	83	Weighted Average
3,411	39	25.08% Pervious Area
10,191	98	74.92% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-5A: Subwatershed 5A - Roof**

Runoff = 0.32 cfs @ 12.09 hrs, Volume= 1,068 cf, Depth= 0.99"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr WQV Rainfall=1.20"

Area (sf)	CN	Description
13,000	98	Roofs, HSG A
13,000	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr WQV Rainfall=1.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 13

**Summary for Subcatchment PR-5B: Subwatershed 5B - Parking Lot**

Runoff = 0.22 cfs @ 12.09 hrs, Volume= 734 cf, Depth= 0.99"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr WQV Rainfall=1.20"

Area (sf)	CN	Description
* 8,940	98	Paved parking and sidewalks, HSG A
8,940	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-6A: Subwatershed 6A - Roof**

Runoff = 0.49 cfs @ 12.09 hrs, Volume= 1,635 cf, Depth= 0.99"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr WQV Rainfall=1.20"

Area (sf)	CN	Description
19,900	98	Roofs, HSG A
19,900	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

**Summary for Subcatchment PR-6B: Subwatershed 6B - Parking Lot**

Runoff = 0.21 cfs @ 12.10 hrs, Volume= 744 cf, Depth= 0.31"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
Type III 24-hr WQV Rainfall=1.20"

Area (sf)	CN	Description
* 23,498	98	Paved parking and sidewalks, HSG A
5,738	39	>75% Grass cover, Good, HSG A
29,236	86	Weighted Average
5,738	39	19.63% Pervious Area
23,498	98	80.37% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					<b>Direct Entry, SEG A</b>

# 2826 Post Road Phase II Modifications - Proposed

Type III 24-hr WQV Rainfall=1.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 14

## Summary for Pond P-1A: UIC #1

Inflow Area = 39,994 sf, 81.33% Impervious, Inflow Depth = 0.22" for WQV event  
Inflow = 0.22 cfs @ 12.09 hrs, Volume= 739 cf  
Outflow = 0.21 cfs @ 12.10 hrs, Volume= 739 cf, Atten= 3%, Lag= 0.9 min  
Discarded = 0.21 cfs @ 12.10 hrs, Volume= 739 cf  
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
Peak Elev= 46.51' @ 12.10 hrs Surf.Area= 4,161 sf Storage= 13 cf

Plug-Flow detention time= 1.0 min calculated for 739 cf (100% of inflow)  
Center-of-Mass det. time= 1.0 min ( 783.0 - 782.0 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	3,108 cf	<b>20.50'W x 202.98'L x 3.50'H Field A</b> 14,564 cf Overall - 5,145 cf Embedded = 9,418 cf x 33.0% Voids
#2A	47.00'	5,145 cf	<b>ADS_StormTech SC-740 +Cap</b> x 112 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 112 Chambers in 4 Rows
		8,253 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.81 cfs @ 12.10 hrs HW=46.51' (Free Discharge)  
↑1=Exfiltration (Exfiltration Controls 0.81 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)  
↑2=Sharp-Crested Rectangular Weir ( Controls 0.00 cfs)

## Summary for Pond P-1B: Isolator Row #1

Inflow Area = 30,994 sf, 75.91% Impervious, Inflow Depth = 0.25" for WQV event  
Inflow = 0.17 cfs @ 12.11 hrs, Volume= 636 cf  
Outflow = 0.00 cfs @ 0.00 hrs, Volume= 0 cf, Atten= 100%, Lag= 0.0 min  
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
Peak Elev= 48.84' @ 24.40 hrs Surf.Area= 468 sf Storage= 636 cf

Plug-Flow detention time= (not calculated: initial storage exceeds outflow)  
Center-of-Mass det. time= (not calculated: no outflow)

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr WQV Rainfall=1.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 15

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	388 cf	<b>6.25'W x 74.82'L x 3.50'H Field A</b> 1,637 cf Overall - 459 cf Embedded = 1,177 cf x 33.0% Voids
#2A	47.00'	459 cf	<b>ADS_StormTech SC-740 +Cap</b> x 10 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		848 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>5.0' long Sharp-Crested Rectangular Weir X 2.00</b> 2 End Contraction(s)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)

↑1=Sharp-Crested Rectangular Weir( Controls 0.00 cfs)

**Summary for Pond P-1D: Underground Infiltration**

Inflow Area = 286,475 sf, 80.60% Impervious, Inflow Depth = 0.38" for WQV event  
 Inflow = 2.68 cfs @ 12.10 hrs, Volume= 8,960 cf  
 Outflow = 2.48 cfs @ 12.14 hrs, Volume= 8,960 cf, Atten= 7%, Lag= 2.1 min  
 Discarded = 2.48 cfs @ 12.14 hrs, Volume= 8,960 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs  
 Peak Elev= 44.74' @ 12.14 hrs Surf.Area= 23,713 sf Storage= 301 cf

Plug-Flow detention time= 2.0 min calculated for 8,944 cf (100% of inflow)  
 Center-of-Mass det. time= 2.0 min ( 866.3 - 864.3 )

## 2826 Post Road Phase II Modifications - Proposed

Type III 24-hr WQV Rainfall=1.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 16

Volume	Invert	Avail.Storage	Storage Description
#1	44.70'	18,217 cf	<b>15.75'W x 1,505.60'L x 3.50'H Crushed Stone</b> 82,996 cf Overall - 27,794 cf Embedded = 55,202 cf x 33.0% Voids
#2	45.20'	1,103 cf	<b>P-1D-A</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 24 Chambers in 3 Rows
#3	45.20'	1,929 cf	<b>P-1D-B</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 42 Chambers in 3 Rows
#4	45.20'	1,240 cf	<b>P-1D-C</b> x 27 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 27 Chambers in 3 Rows
#5	45.20'	965 cf	<b>P-1D-D</b> x 21 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 21 Chambers in 3 Rows
#6	45.20'	1,654 cf	<b>P-1D-E</b> x 36 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 36 Chambers in 3 Rows
#7	45.20'	1,654 cf	<b>P-1D-F</b> x 36 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 36 Chambers in 3 Rows
#8	45.20'	1,103 cf	<b>P-1D-G</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 24 Chambers in 3 Rows
#9	45.20'	1,286 cf	<b>P-1D-H</b> x 28 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 28 Chambers in 2 Rows
#10	45.20'	184 cf	<b>P-1D-H</b> x 4 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#11	45.20'	413 cf	<b>P-1D-H</b> x 9 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#12	45.20'	2,067 cf	<b>P-1D-I</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 45 Chambers in 3 Rows
#13	45.20'	1,929 cf	<b>P-1D-J</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 42 Chambers in 3 Rows
#14	45.20'	2,067 cf	<b>P-1D-K</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr WQV Rainfall=1.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 17

#15	45.20'	1,929 cf	45 Chambers in 3 Rows <b>P-1D-L</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#16	45.20'	2,067 cf	42 Chambers in 3 Rows <b>P-1D-M</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#17	45.20'	1,929 cf	45 Chambers in 3 Rows <b>P-1D-N</b> x 42 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#18	45.20'	2,067 cf	42 Chambers in 3 Rows <b>P-1D-O</b> x 45 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#19	45.20'	1,103 cf	45 Chambers in 3 Rows <b>P-1D-P</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#20	45.20'	1,103 cf	24 Chambers in 3 Rows <b>P-1D-Q</b> x 24 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
#21	46.25'	134 cf	<b>18.0" Round Pipe CB5-DMH1</b> -Impervious L= 76.0' S= 0.0031 '/'
#22	45.70'	205 cf	<b>18.0" Round Pipe CB5-CB6</b> -Impervious L= 116.0' S= 0.0025 '/'
#23	46.10'	93 cf	<b>12.0" Round Pipe CB6-CB7</b> -Impervious L= 118.0' S= 0.0033 '/'
#24	46.50'	101 cf	<b>12.0" Round Pipe CB33-CB40</b> -Impervious L= 128.0' S= 0.0098 '/'
#25	46.10'	83 cf	<b>12.0" Round Pipe CB8-CB9</b> -Impervious L= 106.0' S= 0.0036 '/'
#26	45.70'	187 cf	<b>18.0" Round Pipe CB9-CB10</b> -Impervious L= 106.0' S= 0.0027 '/'
#27	46.20'	91 cf	<b>12.0" Round Pipe CB10-CB11</b> -Impervious L= 116.0' S= 0.0025 '/'
#28	45.30'	540 cf	<b>24.0" Round 24" Header Pipe</b> -Impervious L= 172.0'
#29	45.30'	855 cf	<b>4.00'D x 4.00'H CBs</b> x 17 -Impervious
#30	46.00'	50 cf	<b>4.00'D x 4.00'H CB-6</b> -Impervious
#31	46.50'	50 cf	<b>4.00'D x 4.00'H CB-7</b> -Impervious
#32	47.80'	50 cf	<b>4.00'D x 4.00'H CB-40</b> -Impervious
#33	46.50'	50 cf	<b>4.00'D x 4.00'H CB-8</b> -Impervious
#34	46.00'	50 cf	<b>4.00'D x 4.00'H CB-9</b> -Impervious
#35	46.50'	50 cf	<b>4.00'D x 4.00'H CB-11</b> -Impervious
#36	46.50'	50 cf	<b>4.00'D x 4.00'H CB-33</b> -Impervious

48,651 cf Total Available Storage



**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr WQV Rainfall=1.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 18

Device	Routing	Invert	Outlet Devices
#1	Discarded	44.70'	<b>8.270 in/hr Exfiltration over Wetted area</b> Phase-In= 0.01'
#2	Device 4	45.70'	<b>15.0" W x 21.0" H Vert. Orifice/Grate</b> C= 0.600
#3	Device 4	48.10'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)
#4	Primary	31.40'	<b>24.0" Round Culvert</b> L= 25.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 31.40' / 31.00' S= 0.0160 '/ Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 3.14 sf

**Discarded OutFlow** Max=4.56 cfs @ 12.14 hrs HW=44.74' (Free Discharge)

↑1=**Exfiltration** (Exfiltration Controls 4.56 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=44.70' (Free Discharge)

↑4=**Culvert** (Passes 0.00 cfs of 41.88 cfs potential flow)

↑2=**Orifice/Grate** ( Controls 0.00 cfs)

↑3=**Sharp-Crested Rectangular Weir** ( Controls 0.00 cfs)

**Summary for Pond P-1E: Infiltration Basin**

Inflow Area =	76,715 sf, 66.84% Impervious, Inflow Depth = 0.15" for WQV event
Inflow =	0.18 cfs @ 12.14 hrs, Volume= 979 cf
Outflow =	0.16 cfs @ 12.22 hrs, Volume= 979 cf, Atten= 11%, Lag= 4.7 min
Discarded =	0.16 cfs @ 12.22 hrs, Volume= 979 cf
Primary =	0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs

Peak Elev= 45.01' @ 12.22 hrs Surf.Area= 3,605 sf Storage= 33 cf

Plug-Flow detention time= 3.5 min calculated for 977 cf (100% of inflow)

Center-of-Mass det. time= 3.5 min ( 923.8 - 920.4 )

Volume	Invert	Avail.Storage	Storage Description
#1	45.00'	21,635 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
45.00	3,597	0	0
46.00	4,453	4,025	4,025
47.00	5,366	4,910	8,935
48.00	6,336	5,851	14,786
49.00	7,362	6,849	21,635

Device	Routing	Invert	Outlet Devices
#1	Discarded	45.00'	<b>8.270 in/hr Exfiltration over Surface area</b> Phase-In= 0.01'
#2	Primary	48.20'	<b>35.0' long x 8.0' breadth Broad-Crested Rectangular Weir</b> Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.43 2.54 2.70 2.69 2.68 2.68 2.66 2.64 2.64 2.64 2.65 2.65 2.66 2.66 2.68 2.70 2.74

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr WQV Rainfall=1.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 19

**Discarded OutFlow** Max=0.62 cfs @ 12.22 hrs HW=45.01' (Free Discharge)

↑1=Exfiltration (Exfiltration Controls 0.62 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=45.00' (Free Discharge)

↑2=Broad-Crested Rectangular Weir( Controls 0.00 cfs)

**Summary for Pond P-2A: UIC #2**

Inflow Area = 18,417 sf, 90.63% Impervious, Inflow Depth = 0.37" for WQV event  
 Inflow = 0.16 cfs @ 12.09 hrs, Volume= 571 cf  
 Outflow = 0.15 cfs @ 12.10 hrs, Volume= 571 cf, Atten= 3%, Lag= 0.9 min  
 Discarded = 0.15 cfs @ 12.10 hrs, Volume= 571 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3

Peak Elev= 46.51' @ 12.10 hrs Surf.Area= 2,352 sf Storage= 9 cf

Plug-Flow detention time= 1.0 min calculated for 570 cf (100% of inflow)

Center-of-Mass det. time= 1.0 min ( 817.5 - 816.5 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	1,762 cf	<b>34.75'W x 67.70'L x 3.50'H Field A</b> 8,234 cf Overall - 2,894 cf Embedded = 5,339 cf x 33.0% Voids
#2A	47.00'	2,894 cf	<b>ADS_StormTech SC-740 +Cap</b> x 63 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 63 Chambers in 7 Rows
		4,656 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.46 cfs @ 12.10 hrs HW=46.51' (Free Discharge)

↑1=Exfiltration (Exfiltration Controls 0.46 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)

↑2=Sharp-Crested Rectangular Weir( Controls 0.00 cfs)

**Summary for Pond P-2B: Isolator Row #2**

Inflow Area = 11,917 sf, 85.52% Impervious, Inflow Depth = 0.41" for WQV event  
 Inflow = 0.13 cfs @ 12.10 hrs, Volume= 412 cf  
 Outflow = 0.00 cfs @ 19.90 hrs, Volume= 37 cf, Atten= 98%, Lag= 468.0 min  
 Primary = 0.00 cfs @ 19.90 hrs, Volume= 37 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr WQV Rainfall=1.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 20

Peak Elev= 49.25' @ 19.90 hrs Surf.Area= 245 sf Storage= 375 cf

Plug-Flow detention time= 606.8 min calculated for 37 cf (9% of inflow)  
Center-of-Mass det. time= 450.9 min ( 1,309.0 - 858.1 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap x 5</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=0.00 cfs @ 19.90 hrs HW=49.25' (Free Discharge)  
 ↳ **1=Sharp-Crested Rectangular Weir** (Weir Controls 0.00 cfs @ 0.11 fps)

**Summary for Pond P-3A: UIC #3**

Inflow Area = 15,324 sf, 100.00% Impervious, Inflow Depth = 0.69" for WQV event  
 Inflow = 0.18 cfs @ 12.27 hrs, Volume= 880 cf  
 Outflow = 0.16 cfs @ 12.29 hrs, Volume= 880 cf, Atten= 11%, Lag= 1.7 min  
 Discarded = 0.16 cfs @ 12.29 hrs, Volume= 880 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 46.51' @ 12.29 hrs Surf.Area= 2,031 sf Storage= 10 cf

Plug-Flow detention time= 1.0 min calculated for 878 cf (100% of inflow)  
 Center-of-Mass det. time= 1.0 min ( 831.6 - 830.6 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	1,527 cf	<b>30.00'W x 67.70'L x 3.50'H Field A</b> 7,108 cf Overall - 2,481 cf Embedded = 4,627 cf x 33.0% Voids
#2A	47.00'	2,481 cf	<b>ADS_StormTech SC-740 +Cap x 54</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 54 Chambers in 6 Rows
		4,008 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

# 2826 Post Road Phase II Modifications - Proposed

Type III 24-hr WQV Rainfall=1.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 21

**Discarded OutFlow** Max=0.40 cfs @ 12.29 hrs HW=46.51' (Free Discharge)

↑1=Exfiltration (Exfiltration Controls 0.40 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)

↑2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

## Summary for Pond P-3B: Isolator Row #3

Inflow Area = 8,824 sf, 100.00% Impervious, Inflow Depth = 0.99" for WQV event  
 Inflow = 0.22 cfs @ 12.09 hrs, Volume= 725 cf  
 Outflow = 0.11 cfs @ 12.27 hrs, Volume= 346 cf, Atten= 49%, Lag= 11.0 min  
 Primary = 0.11 cfs @ 12.27 hrs, Volume= 346 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 49.28' @ 12.25 hrs Surf.Area= 245 sf Storage= 377 cf

Plug-Flow detention time= 240.3 min calculated for 345 cf (48% of inflow)  
 Center-of-Mass det. time= 123.5 min ( 905.5 - 782.0 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap x 5</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=0.08 cfs @ 12.27 hrs HW=49.28' (Free Discharge)

↑1=Sharp-Crested Rectangular Weir (Weir Controls 0.08 cfs @ 0.53 fps)

## Summary for Pond P-4A: UIC #4

Inflow Area = 26,602 sf, 87.18% Impervious, Inflow Depth = 0.48" for WQV event  
 Inflow = 0.32 cfs @ 12.09 hrs, Volume= 1,068 cf  
 Outflow = 0.31 cfs @ 12.10 hrs, Volume= 1,068 cf, Atten= 3%, Lag= 0.9 min  
 Discarded = 0.31 cfs @ 12.10 hrs, Volume= 1,068 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
 Peak Elev= 46.52' @ 12.10 hrs Surf.Area= 2,674 sf Storage= 18 cf

Plug-Flow detention time= 1.0 min calculated for 1,068 cf (100% of inflow)  
 Center-of-Mass det. time= 1.0 min ( 783.0 - 782.0 )

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr WQV Rainfall=1.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 22

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	1,997 cf	<b>39.50'W x 67.70'L x 3.50'H Field A</b> 9,359 cf Overall - 3,308 cf Embedded = 6,051 cf x 33.0% Voids
#2A	47.00'	3,308 cf	<b>ADS_StormTech SC-740 +Cap x 72</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 72 Chambers in 8 Rows
		5,305 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.52 cfs @ 12.10 hrs HW=46.52' (Free Discharge)

↑**1=Exfiltration** (Exfiltration Controls 0.52 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)

↑**2=Sharp-Crested Rectangular Weir**( Controls 0.00 cfs)

**Summary for Pond P-4B: Isolator Row #4**

Inflow Area = 13,602 sf, 74.92% Impervious, Inflow Depth = 0.22" for WQV event  
 Inflow = 0.06 cfs @ 12.11 hrs, Volume= 249 cf  
 Outflow = 0.00 cfs @ 0.00 hrs, Volume= 0 cf, Atten= 100%, Lag= 0.0 min  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3

Peak Elev= 48.29' @ 24.40 hrs Surf.Area= 245 sf Storage= 249 cf

Plug-Flow detention time= (not calculated: initial storage exceeds outflow)

Center-of-Mass det. time= (not calculated: no outflow)

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap x 5</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)

↑**1=Sharp-Crested Rectangular Weir**( Controls 0.00 cfs)

## 2826 Post Road Phase II Modifications - Proposed

Type III 24-hr WQV Rainfall=1.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 23

### Summary for Pond P-5A: UIC #5

Inflow Area = 21,940 sf, 100.00% Impervious, Inflow Depth = 0.78" for WQV event  
Inflow = 0.32 cfs @ 12.09 hrs, Volume= 1,420 cf  
Outflow = 0.31 cfs @ 12.10 hrs, Volume= 1,420 cf, Atten= 3%, Lag= 0.9 min  
Discarded = 0.31 cfs @ 12.10 hrs, Volume= 1,420 cf  
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
Peak Elev= 46.52' @ 12.10 hrs Surf.Area= 2,681 sf Storage= 18 cf

Plug-Flow detention time= 1.1 min calculated for 1,420 cf (100% of inflow)  
Center-of-Mass det. time= 1.0 min ( 813.5 - 812.5 )

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	2,004 cf	<b>44.25'W x 60.58'L x 3.50'H Field A</b> 9,382 cf Overall - 3,308 cf Embedded = 6,074 cf x 33.0% Voids
#2A	47.00'	3,308 cf	<b>ADS_StormTech SC-740 +Cap</b> x 72 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 72 Chambers in 9 Rows
		5,312 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	46.50'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	49.20'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.52 cfs @ 12.10 hrs HW=46.52' (Free Discharge)  
↑1=Exfiltration (Exfiltration Controls 0.52 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=46.50' (Free Discharge)  
↑2=Sharp-Crested Rectangular Weir ( Controls 0.00 cfs)

### Summary for Pond P-5B: Isolator Row #5

Inflow Area = 8,940 sf, 100.00% Impervious, Inflow Depth = 0.99" for WQV event  
Inflow = 0.22 cfs @ 12.09 hrs, Volume= 734 cf  
Outflow = 0.12 cfs @ 12.27 hrs, Volume= 352 cf, Atten= 47%, Lag= 10.8 min  
Primary = 0.12 cfs @ 12.27 hrs, Volume= 352 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
Peak Elev= 49.28' @ 12.25 hrs Surf.Area= 245 sf Storage= 377 cf

Plug-Flow detention time= 239.6 min calculated for 351 cf (48% of inflow)  
Center-of-Mass det. time= 123.0 min ( 905.0 - 782.0 )

**2826 Post Road Phase II Modifications - Proposed**

Type III 24-hr WQV Rainfall=1.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 24

Volume	Invert	Avail.Storage	Storage Description
#1A	46.50'	207 cf	<b>6.25'W x 39.22'L x 3.50'H Field A</b> 858 cf Overall - 230 cf Embedded = 628 cf x 33.0% Voids
#2A	47.00'	230 cf	<b>ADS_StormTech SC-740 +Cap x 5</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		437 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	49.25'	<b>6.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Primary OutFlow** Max=0.09 cfs @ 12.27 hrs HW=49.28' (Free Discharge)

↑1=Sharp-Crested Rectangular Weir(Weir Controls 0.09 cfs @ 0.54 fps)

**Summary for Pond P-6A: UIC #6**

Inflow Area = 49,136 sf, 88.32% Impervious, Inflow Depth = 0.40" for WQV event  
 Inflow = 0.49 cfs @ 12.09 hrs, Volume= 1,635 cf  
 Outflow = 0.47 cfs @ 12.10 hrs, Volume= 1,635 cf, Atten= 3%, Lag= 0.9 min  
 Discarded = 0.47 cfs @ 12.10 hrs, Volume= 1,635 cf  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3

Peak Elev= 45.02' @ 12.10 hrs Surf.Area= 5,074 sf Storage= 28 cf

Plug-Flow detention time= 1.0 min calculated for 1,632 cf (100% of inflow)

Center-of-Mass det. time= 1.0 min ( 783.0 - 782.0 )

Volume	Invert	Avail.Storage	Storage Description
#1A	45.00'	3,738 cf	<b>34.75'W x 146.02'L x 3.50'H Field A</b> 17,759 cf Overall - 6,432 cf Embedded = 11,328 cf x 33.0% Voids
#2A	45.50'	6,432 cf	<b>ADS_StormTech SC-740 +Cap x 140</b> Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 140 Chambers in 7 Rows
		10,170 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	45.00'	<b>8.410 in/hr Exfiltration over Wetted area</b>
#2	Primary	48.00'	<b>4.0' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)

**Discarded OutFlow** Max=0.99 cfs @ 12.10 hrs HW=45.02' (Free Discharge)

↑1=Exfiltration (Exfiltration Controls 0.99 cfs)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=45.00' (Free Discharge)

↑2=Sharp-Crested Rectangular Weir( Controls 0.00 cfs)

## 2826 Post Road Phase II Modifications - Proposed

Type III 24-hr WQV Rainfall=1.20"

Prepared by {enter your company name here}

Printed 10/6/2022

HydroCAD® 10.00-26 s/n 03396 © 2020 HydroCAD Software Solutions LLC

Page 25

### Summary for Pond P-6B: Isolator Row #6

Inflow Area = 29,236 sf, 80.37% Impervious, Inflow Depth = 0.31" for WQV event  
Inflow = 0.21 cfs @ 12.10 hrs, Volume= 744 cf  
Outflow = 0.00 cfs @ 0.00 hrs, Volume= 0 cf, Atten= 100%, Lag= 0.0 min  
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs / 3  
Peak Elev= 46.43' @ 24.40 hrs Surf.Area= 913 sf Storage= 744 cf

Plug-Flow detention time= (not calculated: initial storage exceeds outflow)  
Center-of-Mass det. time= (not calculated: no outflow)

Volume	Invert	Avail.Storage	Storage Description
#1A	45.00'	751 cf	<b>6.25'W x 146.02'L x 3.50'H Field A</b> 3,194 cf Overall - 919 cf Embedded = 2,275 cf x 33.0% Voids
#2A	45.50'	919 cf	<b>ADS_StormTech SC-740 +Cap x 20 Inside #1</b> Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap
		1,670 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	47.75'	<b>5.0' long Sharp-Crested Rectangular Weir X 2.00</b> 2 End Contraction(s)

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=45.00' (Free Discharge)  
↑#1=Sharp-Crested Rectangular Weir( Controls 0.00 cfs)

### Summary for Link DP-1: Existing Drainage System - Phase 1

Inflow Area = 554,769 sf, 78.45% Impervious, Inflow Depth = 0.00" for WQV event  
Inflow = 0.00 cfs @ 0.00 hrs, Volume= 0 cf  
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs

### Summary for Link DP-2: Post Road

Inflow Area = 4,789 sf, 61.89% Impervious, Inflow Depth = 0.31" for WQV event  
Inflow = 0.03 cfs @ 12.10 hrs, Volume= 122 cf  
Primary = 0.03 cfs @ 12.10 hrs, Volume= 122 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-28.00 hrs, dt= 0.05 hrs